

(12) **United States Patent**
Auyeung et al.

(10) **Patent No.:** **US 9,542,870 B2**
(45) **Date of Patent:** ***Jan. 10, 2017**

(54) **BILLBOARD AND LIGHTING ASSEMBLY WITH HEAT SINK AND THREE-PART LENS**

F21V 29/83; F21V 29/89; F21V 5/007; F21Y 2105/16

See application file for complete search history.

(71) Applicant: **Ultravision Technologies, LLC**, Dallas, TX (US)

(56) **References Cited**

(72) Inventors: **David Siucheong Auyeung**, Carrollton, TX (US); **William Y. Hall**, Dallas, TX (US); **Simon Magarill**, Mountain View, CA (US)

U.S. PATENT DOCUMENTS

2,254,961 A 9/1941 Lawrence et al.
4,235,285 A 11/1980 Johnson et al.
(Continued)

(73) Assignee: **Ultravision Technologies, LLC**, Dallas, TX (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CA 2615706 A1 9/2006
CN 201925854 U 8/2011
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

"The Lighting Handbook," 8-17, IES 10th Edition, Dec. 6, 2011, 2 pages.

(Continued)

(21) Appl. No.: **15/216,595**

(22) Filed: **Jul. 21, 2016**

(65) **Prior Publication Data**

US 2016/0329005 A1 Nov. 10, 2016

Related U.S. Application Data

(63) Continuation of application No. 15/162,278, filed on May 23, 2016, which is a continuation of application (Continued)

(51) **Int. Cl.**
F21V 1/00 (2006.01)
F21V 11/00 (2015.01)
(Continued)

(52) **U.S. Cl.**
CPC **G09F 13/22** (2013.01); **F21V 5/007** (2013.01); **F21V 29/745** (2015.01);
(Continued)

(58) **Field of Classification Search**
CPC F21V 29/745; F21V 29/76; F21V 29/763;

Primary Examiner — Andrew Coughlin


Assistant Examiner — Alexander Garlen

(74) *Attorney, Agent, or Firm* — Slater Matsil, LLP

(57) **ABSTRACT**

A lighting assembly includes a substantially planar substrate and a number of light emitting diodes (LEDs) arranged in rows on a first surface of the substrate. The rows extend along a longitudinal axis of the substrate. The lighting assembly also includes a number of optical elements, each including a three-part lens. Each optical element is proximate an associated LED such that each optical element overlies a single LED and each LED underlies a single optical element. A heat sink is thermally coupled to a second surface of the substrate that is opposite the first surface. The heat sink has a first section substantially parallel to the substrate and a number of fins extending away from the first section and substantially perpendicular thereto. A longitudinal axis of each fin is substantially perpendicular to the longitudinal axis of the substrate.

25 Claims, 13 Drawing Sheets



Related U.S. Application Data

No. 14/992,680, filed on Jan. 11, 2016, now Pat. No. 9,349,307, which is a continuation of application No. 14/635,907, filed on Mar. 2, 2015, now Pat. No. 9,234,642, which is a continuation of application No. 13/836,517, filed on Mar. 15, 2013, now Pat. No. 8,974,077.

(60) Provisional application No. 61/677,346, filed on Jul. 30, 2012.

(51) Int. Cl.

G09F 13/22 (2006.01)
F21V 29/74 (2015.01)
F21V 29/76 (2015.01)
F21V 29/83 (2015.01)
F21V 5/00 (2015.01)
F21V 29/89 (2015.01)

(52) U.S. Cl.

CPC **F21V 29/763** (2015.01); **F21V 29/83** (2015.01); **F21V 29/89** (2015.01); **F21Y 2105/16** (2016.08); **F21Y 2115/10** (2016.08); **G09F 2013/222** (2013.01)

(56) References Cited**U.S. PATENT DOCUMENTS**

4,679,118	A	7/1987	Johnson et al.	7,513,639	B2	4/2009	Wang
5,036,248	A	7/1991	McEwan et al.	7,513,653	B1	4/2009	Liu et al.
5,083,194	A	1/1992	Bartilson	7,549,777	B2	6/2009	Huang
5,329,426	A	7/1994	Villani	7,618,162	B1	11/2009	Parkyn et al.
5,384,940	A	1/1995	Soule et al.	7,618,163	B2	11/2009	Wilcox
5,818,640	A	10/1998	Watanabe et al.	7,654,684	B1	2/2010	Wight et al.
5,857,767	A	1/1999	Hochstein	7,665,862	B2	2/2010	Villard
5,896,093	A	4/1999	Sjobom	7,674,019	B2	3/2010	Parkyn et al.
5,924,788	A	7/1999	Parkyn, Jr.	7,686,469	B2	3/2010	Ruud et al.
5,926,320	A	7/1999	Parkyn, Jr. et al.	7,736,019	B2	6/2010	Shimada et al.
6,045,240	A	4/2000	Hochstein	7,748,863	B1	7/2010	Holman et al.
6,274,924	B1	8/2001	Carey et al.	7,753,561	B2	7/2010	Chaves et al.
6,364,507	B1	4/2002	Yang	7,753,564	B2	7/2010	Cheng et al.
6,428,189	B1	8/2002	Hochstein	7,841,750	B2	11/2010	Wilcox et al.
6,517,218	B2	2/2003	Hochstein	7,857,483	B2	12/2010	Storch et al.
6,536,923	B1	3/2003	Merz	7,866,851	B2	1/2011	Chang
6,547,423	B2	4/2003	Marshall et al.	7,896,522	B2	3/2011	Heller et al.
6,582,103	B1	6/2003	Popovich	7,905,634	B2	3/2011	Agurok et al.
6,607,286	B2	8/2003	West et al.	7,942,559	B2	5/2011	Holder et al.
6,674,096	B2	1/2004	Sommers	7,952,262	B2	5/2011	Wilcox et al.
6,741,351	B2	5/2004	Marshall et al.	7,959,326	B2	6/2011	Laporte
6,783,269	B2	8/2004	Pashley et al.	7,980,733	B2	7/2011	Shih et al.
6,784,603	B2	8/2004	Pelka et al.	7,997,761	B2	8/2011	Peck et al.
6,799,864	B2	10/2004	Bohler et al.	8,002,435	B2	8/2011	Laporte
6,837,605	B2	1/2005	Reill	8,035,119	B2	10/2011	Ng et al.
6,864,513	B2	3/2005	Lin et al.	8,052,303	B2	11/2011	Lo et al.
6,896,381	B2	5/2005	Benitez et al.	8,056,614	B2	11/2011	Chen et al.
6,918,684	B2	7/2005	Harvey	8,092,049	B2	1/2012	Kinnune et al.
6,948,838	B2	9/2005	Kunstler	8,192,048	B2	6/2012	Kristoffersen et al.
7,006,306	B2	2/2006	Falicoff et al.	8,201,970	B2	6/2012	Wang et al.
7,009,213	B2	3/2006	Camras et al.	8,210,723	B2	7/2012	Peck et al.
7,048,400	B2	5/2006	Murasko et al.	8,215,814	B2	7/2012	Marcoux
7,118,236	B2	10/2006	Hahm et al.	8,235,553	B2	8/2012	Minami et al.
7,144,135	B2	12/2006	Martin et al.	8,246,219	B2	8/2012	Teng et al.
7,153,002	B2	12/2006	Kim et al.	8,262,252	B2	9/2012	Bergman et al.
7,159,997	B2	1/2007	Reo et al.	8,267,551	B2	9/2012	Lin
7,246,931	B2	7/2007	Hsieh et al.	8,273,158	B2	9/2012	Jarrier et al.
7,336,195	B2	2/2008	van de Ven	8,308,331	B2	11/2012	Loh
7,339,202	B2	3/2008	Chiu et al.	8,310,158	B2	11/2012	Coplin et al.
7,375,381	B2	5/2008	Shimizu et al.	8,330,387	B2	12/2012	York et al.
7,390,117	B2	6/2008	Leatherdale et al.	8,338,841	B2	12/2012	Lerman et al.
7,396,146	B2	7/2008	Wang	8,348,461	B2	1/2013	Wilcox et al.
7,410,275	B2	8/2008	Sommers et al.	8,360,613	B2	1/2013	Little, Jr.
7,434,964	B1	10/2008	Zheng et al.	8,376,585	B2	2/2013	Noeth
7,458,706	B1	12/2008	Liu et al.	8,408,737	B2	4/2013	Wright et al.
7,478,915	B1	1/2009	Pedersen	8,454,194	B2	6/2013	Liu
				8,454,215	B2	6/2013	Bollmann
				8,465,178	B2	6/2013	Wilcox et al.
				8,469,552	B2	6/2013	Moeller
				8,547,023	B2	10/2013	Chang et al.
				8,567,987	B2	10/2013	Wronski
				8,573,815	B2	11/2013	Mallory et al.
				8,577,434	B2	11/2013	Merchant et al.
				8,585,253	B2	11/2013	Duong et al.
				8,602,599	B2	12/2013	Zimmer et al.
				8,610,357	B2	12/2013	Stoll et al.
				8,622,574	B2	1/2014	Liu
				8,628,217	B2	1/2014	Moshtagh
				8,632,225	B2	1/2014	Koo et al.
				8,651,693	B2	2/2014	Josefowicz et al.
				8,662,704	B2	3/2014	Carraher et al.
				8,733,981	B2	5/2014	Jiang et al.
				8,789,967	B2	7/2014	Gordin et al.
				8,801,221	B2	8/2014	Lin et al.
				8,835,958	B2	9/2014	Hsieh
				8,858,024	B2	10/2014	Wu et al.
				8,864,344	B2	10/2014	Jiang et al.
				8,870,410	B2	10/2014	Auyeung
				8,870,413	B2	10/2014	Auyeung
				8,876,325	B2	11/2014	Lu et al.
				8,922,734	B2	12/2014	Lin
				8,931,934	B2	1/2015	Lin
				9,046,293	B2	6/2015	Pelka et al.
				9,182,101	B2	11/2015	Nakamura et al.
				2003/0099105	A1	5/2003	Watson
				2004/0004827	A1	1/2004	Guest
				2005/0018428	A1	1/2005	Harvey
				2005/0047170	A1	3/2005	Hilburger et al.
				2005/0151141	A1	7/2005	Grotsch et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0076568	A1	4/2006	Keller et al.	
2006/0081863	A1	4/2006	Kim et al.	
2006/0146531	A1	7/2006	Reo et al.	
2006/0245083	A1	11/2006	Chou et al.	
2007/0201225	A1	8/2007	Holder et al.	
2007/0257270	A1	11/2007	Lu et al.	
2007/0279904	A1	12/2007	Tasch et al.	
2008/0073663	A1	3/2008	Chang	
2008/0080179	A1	4/2008	Giorgi	
2008/0084693	A1	4/2008	Shimada et al.	
2008/0084701	A1	4/2008	Van De Ven et al.	
2008/0180014	A1	7/2008	Tzeng et al.	
2008/0212319	A1	9/2008	Klipstein	
2008/0247173	A1	10/2008	Danek et al.	
2008/0273327	A1 *	11/2008	Wilcox	F21S 2/005 362/267
2009/0097265	A1	4/2009	Sun et al.	
2009/0154158	A1 *	6/2009	Cheng	F21V 5/007 362/237
2009/0180281	A1	7/2009	Ahland, III et al.	
2009/0256459	A1	10/2009	Liu	
2009/0267474	A1 *	10/2009	Zhou	F21K 9/00 313/12
2009/0273933	A1	11/2009	Woodward et al.	
2009/0290338	A1	11/2009	Heller et al.	
2009/0296407	A1	12/2009	Bailey	
2009/0303711	A1	12/2009	Remus et al.	
2010/0008094	A1	1/2010	Shuai et al.	
2010/0014289	A1	1/2010	Thomas et al.	
2010/0014290	A1	1/2010	Wilcox	
2010/0027271	A1	2/2010	Wilcox et al.	
2010/0039810	A1	2/2010	Holder et al.	
2010/0046225	A1	2/2010	Zheng	
2010/0085774	A1	4/2010	Park	
2010/0118531	A1	5/2010	Montagne	
2010/0128488	A1	5/2010	Marcoux	
2010/0172135	A1	7/2010	Holder et al.	
2010/0195330	A1	8/2010	Schaefer et al.	
2010/0232155	A1	9/2010	Wang	
2010/0296267	A1	11/2010	Yu et al.	
2010/0296283	A1	11/2010	Taskar et al.	
2010/0302785	A1	12/2010	Zhou	
2010/0302786	A1	12/2010	Wilcox et al.	
2011/0002120	A1	1/2011	Song et al.	
2011/0031887	A1	2/2011	Stoll et al.	
2011/0038151	A1	2/2011	Carragher et al.	
2011/0063857	A1	3/2011	Li et al.	
2011/0068708	A1	3/2011	Coplin et al.	
2011/0075409	A1	3/2011	Zheng	
2011/0149548	A1	6/2011	Yang et al.	
2011/0170283	A1	7/2011	Chan	
2011/0205744	A1	8/2011	Kim	
2011/0219650	A1	9/2011	Wright et al.	
2011/0242807	A1	10/2011	Little, Jr. et al.	
2011/0242816	A1	10/2011	Chowdhury et al.	
2011/0278633	A1	11/2011	Clifford	
2011/0280003	A1	11/2011	Hsu et al.	
2012/0014115	A1	1/2012	Park et al.	
2012/0043560	A1 *	2/2012	Wu	F21V 19/003 257/88
2012/0080699	A1	4/2012	Chowdhury et al.	
2012/0087125	A1	4/2012	Liu	
2012/0163005	A1	6/2012	Liu	
2012/0201022	A1	8/2012	van De Ven et al.	
2012/0250321	A1	10/2012	Blincoe et al.	
2012/0307495	A1	12/2012	Shih	
2013/0010468	A1	1/2013	Stoll et al.	
2013/0057861	A1	3/2013	Ishii et al.	
2013/0063970	A1	3/2013	Oh	
2013/0135861	A1	5/2013	Chen et al.	
2013/0163005	A1	6/2013	Liu	
2013/0193850	A1	8/2013	Demuyne et al.	
2013/0270585	A1	10/2013	Mei et al.	
2013/0291414	A1	11/2013	Cegnar	
2013/0335979	A1	12/2013	Lauret et al.	

2014/0016326	A1	1/2014	Dieker et al.
2014/0029253	A1	1/2014	Auyeung
2014/0029259	A1	1/2014	Auyeung
2014/0029274	A1	1/2014	Auyeung
2014/0085905	A1	3/2014	Broughton
2014/0104851	A1	4/2014	Auyeung
2014/0112007	A1	4/2014	Auyeung
2014/0168963	A1	6/2014	Stone et al.
2014/0168998	A1	6/2014	Tang et al.
2014/0268761	A1	9/2014	Raleigh et al.
2014/0373348	A1	12/2014	Li

FOREIGN PATENT DOCUMENTS

CN	202629916	U	12/2012
CN	102889549	A	1/2013
DE	202005016441	U1	2/2007
EP	1078301	A1	2/2001
EP	1528603	A2	5/2005
EP	1988576	A1	11/2008
EP	2039985	A2	3/2009
EP	2092859	A1	8/2009
EP	2172696	A1	4/2010
EP	2378337	A2	10/2011
EP	2416062	A2	2/2012
EP	2448021	A2	5/2012
EP	2553331	A1	2/2013
EP	2622267	A1	8/2013
GB	2421584	A	6/2006
JP	2003195790	A	7/2003
JP	2005024706	A	1/2005
JP	2005217094	A	8/2005
JP	2005327820	A	11/2005
JP	2007035951	A	2/2007
JP	2007281260	A	10/2007
JP	2011060575	A	3/2011
JP	2012054115	A	3/2012
JP	2012113276	A	6/2012
WO	2004051223	A2	6/2004
WO	2006033770	A2	3/2006
WO	2006126123	A1	11/2006
WO	2008047335	A1	4/2008
WO	2008122941	A1	10/2008
WO	2009064607	A1	5/2009
WO	2010010494	A1	1/2010
WO	2010033545	A2	3/2010
WO	2010130732	A1	11/2010
WO	2011041813	A1	4/2011
WO	2011042837	A1	4/2011
WO	2011123267	A1	10/2011
WO	2012021718	A1	2/2012
WO	2012095242	A1	7/2012
WO	2012121718	A1	9/2012

OTHER PUBLICATIONS

Jeon, H. et al., Illuminance Distribution and Photosynthetic Photon Flux Density Characteristics of LED Lighting with Periodic Lattice Arrangements, Transactions on Electrical and Electronic Materials, vol. 13, No. 1, Feb. 25, 2012, pp. 16-18.

Jiang, J., "Optical design of a freeform TIR lens for LED street-light," Optik—International Journal for Light and Electron Optics, vol. 121, Issue 19, Oct. 2010, pp. 1761-1765.

Defendants Corrected Joint Invalidity Contentions, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-108.

Keller, A., "Signs of the Times," *Floridatrend.com*, Dec. 2011, pp. 50-53.

Lakkio, O., "Winning the Optical Challenges in LED Street Lighting," *Digi-Key*, May 27, 2011, 5 pages.

"Billie—The Bright Answer for Billboard Lighting," *Ledil Product Release*, Dec. 8, 2013, 2 pages.

"LEDIL Standard Optics for Osram LEDs," *Ledil*, Jan. 2011, 60 pages.

"Strada 6in1 Module for Streeting Lighting," *Ledil*, 2010, 1 page, <<http://ledil.fi/sites/default/files/Documents/Technical/Articles/Article_2.pdf>>.

(56)

References Cited

OTHER PUBLICATIONS

- LEDIL, "Who is LEDIL?," www.ledil.com, Mar. 22, 2011, 17 pages.
- LEDIL, "Who is LEDIL?," www.ledil.com, May 22, 2011, 68 pages.
- Lee, S. et al., "Driving Performance and Digital Billboards Final Report," Virginia Tech Transportation Institute, Center for Automotive Safety Research, Mar. 22, 2007, 90 pages.
- Lighting Solutions Techzone Magazine, "Look Inside Today's Lighting Technology," Digi-Key Corporation, TZL112.US, Jun. 7, 2011, 76 pages.
- Lo, Y. et al., "Optical Design of a Butterfly Lens for a Street Light Based on a Double-Cluster LED," *Microelectronics Reliability*, vol. 52, May 2011, pp. 889-893.
- Luminautics, "LED Display Primer," 2011, pp. 1-21.
- Luo, X. et al., "Automated Optimization of an Aspheric Light-Emitting Diode Lens for Uniform Illumination," *Applied Optics*, vol. 50, No. 20, Jul. 2011, pp. 3412-3418.
- Moreno, I., "Configuration of LED Arrays for Uniform Illumination," *Proc. Of SPIE*, vol. 5622, Oct. 2004, pp. 113-718.
- "LED Ad-Poster Billboard Luminaire," *Neptun*, Jan. 2012, 1 page.
- "LED Ad-Poster Billboard Luminaire," *Neptun*, May 25, 2011, 1 page.
- "Street Lighting with LED Lights Sources Application Note," OSRAM Opto Semiconductors, Jan. 2009, pp. 1-10.
- Qin, Z. et al., "Analysis of Condition for Uniform Lighting Generated by Array of Light Emitting Diodes with Large View Angle," *Optics Express*, vol. 18, No. 16, Aug. 2010, pp. 17460-17476.
- Ramane, D. et al., "Automated Test Jig for Uniformity Evaluation of Luminaires," *IJAET*, vol. 3, No. 1, Mar. 2012, pp. 41-47.
- "Starbeam," Thorlux Lighting, Brochure, Aug. 2012, 8 pages.
- "Starbeam," Thorlux Lighting, Brochure, Jul. 2015, 4 pages.
- "Starbeam," Thorlux Lighting, Brochure, Mar. 2014, 16 pages.
- "Starbeam," Thorlux Lighting, Technical Information, Mar. 2014, 10 pages.
- "Starflood," Thorlux Lighting, Brochure, Mar. 2016, 16 pages.
- "Starflood; High performance mini LED floodlights," Thorlux Lighting, Retrieved Jul. 21, 2016, 16 pages, <<<http://www.thorlux.com/luminaires/starflood>>>.
- "General Catalog—2012," Thorlux Lighting, Dec. 2012, 164 pages.
- Tsai, J. et al., "LED Backlight Module by a Lightguide-Diffusive Component With Tetrahedron Reflector Array," *J. Display Tech.*, vol. 8, No. 6, Jun. 2012, pp. 321-328.
- Wang, K. et al., "Freeform LED Lens for Rectangularly Prescribed Illumination," *J. Opt. A: Pure Appl. Opt.*, No. 11, Aug. 2009, 105501, 10 pages.
- Wang, K. et al., "New reversing design method for LED uniform illumination," *Optics Express*, vol. 19, Issue S4, Jul. 4, 2011, pp. A830-A840.
- West, R.S. et al., "43.4: High Brightness Direct Led Backlight for LCD-TV," *SID 03 Digest*, May 2003, 4 pages.
- Wu, D. et al., "Freeform Lens Design for Uniform Illumination with Extended Source," 2011 IN▼ I Conf. Elecs. Packaging Tech. & High Density Packaging, Aug. 2011, pp. 1085-1089.
- Wu, R. et al., "Optimization Design of Irradiance Array for LED Uniform Rectangular Illumination," *Applied Optics*, vol. 1, No. 13, May 2012, pp. 2257-2263.
- Zhenrong, Z. et al., "Freeform Surface Lens for LED Uniform Illumination," *Applied Optics*, vol. 48, No. 35, Dec. 2009, pp. 6627-6634.
- Zhu, Z. et al., "Uniform Illumination Design by Configuration of LED Array and Diffuse Reflection Surface for Color Vision Application," *J. Display tech*, vol. 7, No. 2, Feb. 2011, pp. 84-89.
- Defendant Irvin International, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-41 (see p. 39).
- Lamar's First Amended Answer and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 8, 2016, pp. 1-61 (see p. 53).
- LED Professional Review, Issue 17, Jan./Feb. 2010, 52 pages.
- LED Professional Review, Issue 18, Mar./Apr. 2010, 64 pages.
- LED Professional Review, Issue 19, May/Jun. 2010, 64 pages.
- LED Professional Review, Issue 20, Jul./Aug. 2010, 48 pages.
- LED Professional Review, Issue 21, Sep./Oct. 2010, 64 pages.
- LED Professional Review, Issue 22, Nov./Dec. 2010, 60 pages.
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Amended Answer, Affirmative Defenses and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 27, 2016, pp. 1-43 (see p. 38).
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Answer and Affirmative Defenses to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-37.
- Dieker, et al., U.S. Appl. No. 61/659,828, filed Jun. 14, 2012, "Asymmetric Area Lighting Lens with Improved Uniformity," 14 pages.
- Whang, et al., "Designing Uniform Illumination Systems by Surface-Tailored Lens and Configurations of LED Arrays," *IEEE 2009, Journal of Display Technology*, vol. 5, No. 3, Mar. 2009, pp. 94-103.
- Lee, S., "How to Select a Heat Sink," <http://www.electronics-cooling.com/1995/06/how-to-select-a-heat-sink/>, Jun. 1, 1995, pp. 1-10.
- Steigerwald, et al., "Illumination with Solid State Lighting Technology," *IEEE Journal on Selected Topics in Quantum Electronics*, vol. 8, No. 2, Mar./Apr. 2002, pp. 310-320.
- Kim, Yu-Sin, et al., "Development of a Numerical Model for the Luminous Intensity Distribution of a Planar Prism LED Luminaire for Applying an Optimization Algorithm," *Luekos*, vol. 9, No. 1, Jul. 2012, pp. 57-72.
- Lee, Hsiao-Wen, et al., "Improvement of Illumination Uniformity for LED Flat Panel Light by Using Micro-Secondary Lens Array," *Optics Express*, vol. 20, No. S6, Nov. 5, 2012, 11 pages.
- Liu, Peng, et al., "Optimized Design of LED Freeform Lens for Uniform Circular Illumination," *Journal of Zhejiang University—Science C (Computers & Electronics)*, 2012, pp. 929-936.
- Office Action Summary received in U.S. Appl. No. 14/630,500, mailed Dec. 31, 2015, pp. 1, 20-26.
- Parkyn, William A., "Segmented Illumination Lenses for Steplighting and Wall-Washing," *SPIE Conference on Current Development in Optical Design and Optical Engineering VIII*, Denver, Colorado, Jul. 1999, *SPIE* vol. 3779, pp. 363-370.
- Lee S., "How to Select a Heat Sink," <http://www.electronics-cooling.com/1995/06/how-to-select-a-heat-sink/>, Jun. 1, 1995, pp. 1-10.
- Cheng, et al., "The Research of LED Arrays for Uniform Illumination," *Advances in Information Sciences and Service Sciences (AISS)*, vol. 4, No. 10, Jun. 2012, pp. 174-182.
- Arik, M., "Thermal Management of LEDs: Package to System," *Third International Conference on Solid State Lighting*, *Proc. of SPIE*, vol. 5187, Jan. 21, 2012, pp. 64-75.
- Tracepro, "LED Reflector and Lens Simulation Using TracePro Illumination Design and Analysis Software," White Paper, Oct. 2013, 11 pages.
- Hubbell Lighting, "Universal Lighting Technologies Invention Disclosure," Jun. 14, 2012, 15 pages.
- Adaptive Micro Systems, LLC, "Signs—Sealed and Delivered! Adaptive's Approach to Heat Management," Mar. 2008, 2 pages.
- "Advanced Lighting Guidelines," 2001 Edition, New Buildings Institute, Inc., Jul. 20, 2001, 394 pages.
- Barco, "DB-x20 Digital Billboard Out-of-Home Media LED Screen," Apr. 2009, 6 pages.
- Batinsey, J., "Outdoor Lighting Ordinance Guide," Jun. 2006, 17 pages.
- Chang, R. et al., "LED Backlight Module by Lightguide-Diffusive Component," *Journal of Display Technology*, vol. 8, No. 2, Feb. 2012, pp. 79-86.
- Chen, C. et al., "P-72: Inclined LED Array for Large-Sized Backlight System," *Society for Information Display, International Symposium, Digest of Technical Papers, SID 05 Digest*, May 2005, pp. 558-561.
- "Unified Development Code," Chapter 10 of the Tyler Code of Ordinances, City of Tyler, Apr. 23, 2008, 378 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Defendants Invalidity Contentions, Appendix A, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-19.

Defendants Invalidity Contentions, ExhibitA01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-80.

Defendants Invalidity Contentions, ExhibitA02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-74.

Defendants Invalidity Contentions, ExhibitA03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitA04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-53.

Defendants Invalidity Contentions, ExhibitB01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidity Contentions, ExhibitB02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-36.

Defendants Invalidity Contentions, ExhibitB03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-21.

Defendants Invalidity Contentions, ExhibitB04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-27.

Defendants Invalidity Contentions, ExhibitC01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitC02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-67.

Defendants Invalidity Contentions, ExhibitC03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-35.

Defendants Invalidity Contentions, ExhibitC04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-87.

Defendants Invalidity Contentions, ExhibitC05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-51.

Defendants Invalidity Contentions, ExhibitC06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-79.

Defendants Invalidity Contentions, ExhibitD01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-109.

Defendants Invalidity Contentions, ExhibitD02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-186.

Defendants Invalidity Contentions, ExhibitD03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-111.

Defendants Invalidity Contentions, ExhibitD05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-135.

Defendants Invalidity Contentions, ExhibitE01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-169.

Defendants Invalidity Contentions, ExhibitE02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-192.

Defendants Invalidity Contentions, ExhibitE03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-443.

Defendants Invalidity Contentions, ExhibitE04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-171.

Defendants Invalidity Contentions, ExhibitF01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidity Contentions, ExhibitF02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-13.

Defendants Invalidity Contentions, ExhibitF03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-100.

Defendants Invalidity Contentions, ExhibitG01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-30.

Defendants Invalidity Contentions, ExhibitG02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-11.

Defendants Invalidity Contentions, ExhibitG03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-94.

Defendants Invalidity Contentions, ExhibitH01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-60.

Defendants Invalidity Contentions, ExhibitH02 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-26.

Defendants Invalidity Contentions, ExhibitH03 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-71.

Defendants Invalidity Contentions, ExhibitH04 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-151.

Defendants Invalidity Contentions, ExhibitH05 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-181.

Defendants Invalidity Contentions, ExhibitI01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-168.

Deepa, R. et al., "Modeling and Simulation of Multielement LED Source," The Illuminating Engineering Institute of Japan, Journal of Light & Visual Environment, vol. 35, No. 1, Jun. 21, 2011, pp. 34-41.

Deepa, R. et al., Optimization of multi-element LED source for uniform illumination of plane surface, Optical Society of America, Optics Express, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.

Design & Engineering Services, "Advanced Lighting Systems for Externally Lit Billboards," ET 08.12 Report, Southern California Edison, Jan. 4, 2010, 58 pages.

Ding, Y., "Freeform LED lens for uniform illumination," Optics Express, vol. 16, No. 17, Aug. 18, 2008, 9 pages.

Huang, K. et al., "Free-form lens design for LED indoor illumination," Proc. of SPIE, vol. 7852, Nov. 15, 2010, pp. 78521 D-1-78521 D-8.

"The Lighting Handbook," 12-18, IES 10th Edition, Dec. 6, 2011, 1 page.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C







FIG. 1D






FIG. 3C




FIG. 4B








FIG. 4A






FIG. 6A





FIG. 6B






FIG. 7A





FIG. 7B






FIG. 8B












FIG. 8C





1

BILLBOARD AND LIGHTING ASSEMBLY WITH HEAT SINK AND THREE-PART LENS

This is a continuation of Ser. No. 15/162,278, filed May 23, 2016, which is a continuation of Ser. No. 14/992,680, filed Jan. 11, 2016, which is a continuation of U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015, which is a continuation of U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013, which claims the benefit of U.S. Provisional Application No. 61/677,346, filed on Jul. 30, 2012, which applications are hereby incorporated herein by reference.

The following patents and applications are related:

U.S. patent application Ser. No. 61/677,340, filed Jul. 20, 2012 (now expired)

U.S. patent application Ser. No. 61/677,346, filed Jul. 30, 2012 (now expired)

U.S. patent application Ser. No. 61/677,352, filed Jul. 30, 2012 (now expired)

U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013 (now U.S. Pat. No. 8,974,077)

U.S. patent application Ser. No. 13/836,612, filed Mar. 15, 2013 (now U.S. Pat. No. 8,870,410)

U.S. patent application Ser. No. 13/836,710, filed Mar. 15, 2013 (now U.S. Pat. No. 9,062,873)

U.S. patent application Ser. No. 14/137,306, filed Dec. 30, 2013 (now U.S. Pat. No. 8,985,806)

U.S. patent application Ser. No. 14/137,343, filed Dec. 20, 2013 (now U.S. Pat. No. 8,870,413)

U.S. patent application Ser. No. 14/137,380, filed Dec. 20, 2013 (now U.S. Pat. No. 9,068,738)

U.S. patent application Ser. No. 14/630,500, filed Feb 24, 2015 (co-pending)

U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015 (now U.S. Pat. No. 9,234,642)

U.S. patent application Ser. No. 14/706,634, filed May 7, 2015 (now U.S. Pat. No. 9,212,803)

U.S. patent application Ser. No. 14/968,520, filed Dec. 14, 2015 (co-pending)

U.S. patent application Ser. No. 14/992,680, filed Jan. 11, 2016 (now U.S. Pat. No. 9,349,307)

U.S. patent application Ser. No. 15/162,278, filed May 23, 2016 (co-pending)

U.S. patent application Ser. No. 15/208,483, filed Jul. 12, 2016 (co-pending)

U.S. patent application Ser. No. 15/208,521, filed Jul. 12, 2016 (co-pending)

TECHNICAL FIELD

The following disclosure relates to lighting systems and, more particularly, to lighting systems using light emitting diodes to externally illuminate signs.

SUMMARY

The present invention, in one aspect thereof, comprises a back panel for use in a light emitting diode (LED) lighting assembly. An extruded substrate formed of a thermally conductive material is provided, the substrate having a plurality of fins extending from a first side of the substrate, each of the fins having a substantially rectangular shape oriented so that a longitudinal axis of the fin is substantially parallel to a longitudinal axis of the substrate. At least some of the fins include a hole formed through the fin to enable heated air to rise through the fins. A plurality of LEDs are mounted on a second side of the substrate, and oriented in

2

a longitudinal orientation with the fins oriented parallel to the bottom edge of a surface to be illuminated, such that heat rises perpendicular to the surface of the fin.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding, reference is now made to the following description taken in conjunction with the accompanying Drawings in which:

FIG. 1A illustrates one embodiment of a billboard that may be externally lighted by one or more lighting assemblies;

FIGS. 1B-1D illustrate embodiments of angular positions of the lighting assembly of FIG. 1 relative to the billboard;

FIG. 2 illustrates one embodiment of a lighting assembly that may be used to light the billboard of FIG. 1;

FIGS. 3A and 3B illustrate one embodiment of a back panel that may be used in the lighting assembly of FIG. 2;

FIG. 3C illustrates one embodiment of the back panel of FIGS. 3A and 3B with a light panel and an optics panel that may also be used in the lighting assembly of FIG. 2;

FIGS. 4A and 4B illustrate one embodiment of a light panel that may be used with the lighting assembly of FIG. 2;

FIG. 5A, 5B, 5C and 5D illustrate one embodiment of an optics panel that may be used with the lighting assembly of FIG. 2;

FIGS. 6A-6C illustrate a more detailed embodiment of the lighting assembly of FIG. 2;

FIGS. 7A and 7B illustrate an embodiment of a back panel that may be used with the lighting assembly of FIGS. 6A-6C;

FIG. 8A illustrates an embodiment of an LED assembly and an optics panel that may be used with the lighting assembly of FIG. 6;

FIGS. 8B-8J illustrates embodiments of the optics panel of FIG. 8A and optical elements that may be used to form part of the optics panel; and

FIG. 9 illustrates a more detailed embodiment of the lighting assembly of FIG. 2.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Billboards, such as those commonly used for advertising in cities and along roads, often have a picture and/or text that must be externally illuminated to be visible in low-light conditions. As technology has advanced and introduced new lighting devices such as the light emitting diode (LED), such advances have been applied to billboards. However, current lighting designs have limitations and improvements are needed. Although billboards are used herein for purposes of example, it is understood that the present disclosure may be applied to lighting for any type of sign that is externally illuminated.

Referring to FIG. 1A, one embodiment of a billboard **100** is illustrated. The billboard **100** includes a surface **102** onto which a picture and/or text may be painted, mounted, or otherwise affixed. The surface **102** may be any size, such as a commonly used size having a width of forty-eight feet wide and a height of fourteen feet. The surface **102** may be provided by placing a backing material on a frame **104** made of steel and/or other materials. The frame **104** may be mounted on one or more support poles **106**, which may be considered part of the frame **104** or separate from the frame

104. The billboard **100** may include a walkway or other support structure **108** that enables the surface **102** to be more easily accessed.

One or more lighting assemblies **110** may be coupled to the walkway **108** (e.g., to a safety rail or to the walkway itself) and/or to another structural member of the billboard **100** to illuminate some or all of the surface **102** in low light conditions. The lighting assembly **110** may be mounted at or near a top edge **112** of the billboard **100**, a bottom edge **114** of the billboard **100**, a right edge **116** of the billboard **100**, and/or a bottom edge **118** of the billboard **100**. The lighting assembly **110** may be centered (e.g., located in approximately the center of the billboard **100**) or off center as illustrated in FIG. 1A.

With additional reference to FIGS. 1B-1D, a surface **120** of the lighting assembly **110** may be parallel with respect to the surface **102** of the billboard **100** (FIG. 1B), may be perpendicular with respect to the surface **102** (FIG. 1C), or may be angled with respect to the surface **102** (FIG. 1D). It is understood that the lighting assembly **110** may be placed in many different orientations and locations relative to the billboard **100** and to one another, and the illustrated positions are only for purposes of example. Furthermore, it is understood that references to “top,” “bottom,” “left,” and “right” are used in the present disclosure for purposes of description and do not necessarily denote a fixed position. For example, the billboard **100** may be turned on end, and the referenced “top,” “bottom,” “left,” and “right” edges may still be readily identifiable although the “top” edge would be the “left” edge or the “right” edge.

One problem with current lighting technology is that it can be difficult to direct light only onto the surface **102** and even more difficult to do so evenly. This may be due partly to the placement of the lighting assembly **110**, as shown in FIGS. 1B-1D. As the lighting assembly **110** is off center relative to the surface **102**, light emitted from the lighting assembly **110** may not evenly strike the surface **102**. One problem with uneven illumination is that certain parts of the surface **102** may be more brightly illuminated than other parts. This creates “hot spots” that may be undesirable. Attempting to evenly illuminate the surface **102** may cause light to be directed past the edges **112**, **114**, **116**, and **118** as attempts are made to balance out hot spots in particular areas. However, light that does not strike the surface **102** is wasted and may create problems (e.g., light pollution), as well as waste illumination that could be used for the surface **102**.

In addition to the difficulties of evenly illuminating the surface **102**, the use of LEDs in an exterior lighting environment involves issues such as heat dissipation and protecting the LEDs against environmental conditions such as moisture. The presence of moving mechanical features such as fans that may be used to provide increased airflow for cooling may create additional reliability problems. Due to the difficulty and expense of replacing and/or repairing the lighting assembly **110** in combination with the desire to provide consistent lighting while minimizing downtime, such issues should be addressed in a manner that enhances reliability and uptime.

Referring to FIG. 2, one embodiment of a lighting assembly **200** is illustrated. The lighting assembly **200** provides a more detailed embodiment of the lighting assembly **110** of FIG. 1. The lighting assembly **200** includes a back panel **202**, a light panel **204** (e.g., a printed circuit board (PCB)) having a plurality of LEDs (not shown) mounted thereon, and an optics panel **206**. As will be described below in more detailed examples, light from the LEDs of the light panel

204 may be directed by the optics panel **206** to illuminate the surface **102** of the billboard **100** of FIG. 1. The back panel **202** may be configured to serve as a supporting substrate for the light panel **204** and optics panel **206**, as well as to dissipate heat produced by the LEDs.

It is understood that any of the back panel **202**, light panel **204**, and optics panel **206** may actually be two or more physical substrates rather than a single panel as illustrated in FIG. 2. Furthermore, it is understood that there may be additional panels positioned behind the back panel **202**, in front of the optics panel **206**, and/or between the back panel **202** and light panel **204** and/or between the light panel **204** and optics panel **206**.

Referring to FIGS. 3A-3C, one embodiment of the back panel **202** is illustrated with a front surface **302** and a back surface **304**. The back panel **202** includes a top edge **306**, a bottom edge **308**, a right edge **310**, and a left edge **312**. The panel **202** may be formed of one or more thermally conductive materials (e.g., aluminum) and/or other materials.

The front surface **302** provides a mounting surface for the light panel **204**. In some embodiments, the front surface **302** of the panel **202** may include one or more protrusions **314a** and **314b** that are substantially parallel to the top edge **306**. The protrusions **314a** and **314b** may be configured to protect the light panel **204** from moisture. Although only two protrusions **314a** and **314b** are illustrated, it is understood that a single protrusion may be provided or three or more protrusions may be provided. Furthermore, such protrusions may vary in length, shape (e.g., may have angled or curved surfaces), orientation, and/or location on the front surface **302**.

Referring specifically to FIG. 3C, a light panel **204** and an optical panel **206** may be mounted under the protrusion **314a** (FIG. 3C). Moisture running down the front surface **302** in the direction of arrow **316** may strike the protrusion **314a** and be directed away from the light panel **204** and optical panel **206** as shown by arrow **318**. Although not shown, moisture may also be directed length down the protrusion **314a**. Accordingly, protrusion **314a** may serve as a gutter and aid in directing moisture away from a joint **320** where the optical panel **206** abuts the front surface **302**. This may be beneficial even when a moisture resistant compound is used to seal the joint **320**. In embodiments where there are multiple light panels **204** arranged vertically on the front surface **302**, there may be a protrusion positioned above each light panel **204**. For example, the protrusion **314a** may be positioned directly above one light panel **204** and the protrusion **314b** may be positioned directly above another light panel **204**.

Referring specifically to FIG. 3B, the back surface **304** may be configured to increase heat dissipation. For example, the back surface **304** may be configured with a heat sink provided by fins **322a-322N**, where N denotes a total number of fins. The fins **322a-322N** increase the surface area of the back surface **304**, thereby providing for additional heat dissipation to the surrounding air. The fins **322a-322N** may be formed as part of the panel **202** or may be otherwise coupled to the panel **202** (e.g., may be part of a discrete heat sink that is coupled to the back surface **304**). Some or all of the fins **322a-322N** may be angled, as shown by fins **322a** and **322b**. In some embodiments, holes (not shown) may be provided in some or all of the fins **322a-322N** to aid in air circulation. In such embodiments, the holes may cause a chimney effect in which heated air rises through the holes and is replaced by cooler air. This may be particularly effective in environments where natural air movement is limited.

5

Referring to FIGS. 4A and 4B, one embodiment of a single PCB 402 of the light panel 204 is illustrated. In the present example, the light panel 204 may include multiple PCBs 402, although it is understood that any number of PCBs may be used based on design issues such as the amount of illumination needed, the amount of illumination provided by a single PCB 402, the size of the surface 102 of the billboard 100, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section, the PCB 402 includes a front surface 404, a back surface 406, a top edge 408, a bottom edge 410, a right edge 412, and a left edge 414.

The PCB 402 may include one or more strings of LEDs 416, with multiple LEDs 416 in a string. For example, a string may include eight LEDs 416 and each PCB 402 may include two strings for a total of sixteen LEDs 416. In this configuration, a light panel 204 having eight PCBs 402 would include ninety-six LEDs 416. It is understood that although the PCBs 402 are shown as being substantially identical, they may be different in terms of size, shape, and other factors for a single light panel 204.

In the present example, the LEDs 416 are surface mounted, but it is understood that the LEDs 416 may be coupled to the panel 204 using through hole or another coupling process. The surface mounted configuration may ensure that a maximum surface area of each LED 416 is in contact with the PCB 402, which is in turn in contact with the back panel 202 responsible for heat dissipation. Each string of LEDs may receive a constant current with the current divided evenly among the LEDs 416.

Referring to FIGS. 5A, 5B, 5C and 5D, one embodiment of a single lens panel 500 of the optics panel 206 is illustrated. In the present example, the optics panel 206 may include multiple lens panels 500, although it is understood that any number of lens panels may be used based on design issues such as the number, arrangement, and orientation of the LEDs 416, the size of the surface 102, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section that is configured for use with the PCB 402 of FIG. 4, a single lens panel 500 includes a front surface 502, a back surface 504, a top side 506, a bottom side 508, a right side 510, and a left side 512. The sides 506, 508, 510, and 512 may form a cavity into which the PCB 402 may fit, thereby providing protection for the PCB 402 from environmental conditions such as moisture.

The lens panel 500 may include a beveled or angled top side 506 and/or bottom side 508 as illustrated in FIG. 5B. The beveling/angling may aid in preventing moisture from reaching the PCB 402 under the lens panel 500, as water will more readily flow from the area of the joint 320 (FIG. 3C) due to the angled surface than if the top side 506 was relatively flat.

The lens panel 500 may include multiple optical elements 514. A single optical element 514 may be provided for each LED 416, a single optical element 514 may be provided for multiple LEDs 416, and/or multiple optical elements 514 may be provided for a single LED 416. In some embodiments, the optical elements 514 may be provided by a single multi-layer optical element system provided by the lens panel 500.

In the present example, the optical elements 514 are configured so that the light emitted from each LED 416 is projected onto the entire surface 102 of the billboard 100. In other words, if all other LEDs 416 were switched off except for a single LED 416, the entire surface 102 would be illuminated at the level of illumination provided by the single LED 416. In one embodiment, the rectangular target

6

area of the surface 102 would be evenly illuminated by the LED 416, while areas beyond the edges 112, 114, 116, and 118 would receive no illumination at all or at least a minimal amount of illumination from the LED 416. What is meant by “evenly” is that the illumination with a uniformity that achieves a 3:1 ratio of the average illumination to the minimum. Thus, by designing the lens in such a manner, when all LEDs are operating, the light from the collective thereof will illuminate the surface at the 3:1 ratio. When one or more LEDs fail, the overall illumination decreases, but the uniformity maintains the same uniformity. Also, as described hereinabove, the “surface” refers to the surface that is associated with a particular LED panel. It may be that an overall illuminated surface is segmented and multiple panels are provided, each associated with a particular segment.

FIG. 5C illustrates a detail of the lens assembly. Each of the diodes 416 is mounted on the board 408 at a minimum distance. Overlying the board and LEDs 416 is transparent lens substrate 520. This substrate 520 has a plurality of lens structures 522, each associated with one of the LEDs 416, such that each of the LEDs 416 has the light emitted therefrom directed outward towards the surface, each lens structure being substantially the same. The minimum distance is designed such that overlapping light from adjacent LEDs does not create interference patterns and result in dead spots on the surface. The lens structure 522 is designed to create the 3:1 uniformity and also, the lens structure is designed to “direct” the light from an edge of the surface to cover the entire surface. This is shown by the angle of the light rays in FIG. 5C. Also, the beveled edge 530 will basically surround the PCB 402, thus protecting it from moisture. The lens substrate 520 is secured with screws (not shown).

FIG. 5D illustrates a detail of the lens structure 522. This structure includes an interior surface 524 and an exterior surface 526 that shapes and directs the light in the correct pattern. This is an acrylic material. With such a design, the lighting assembly can be disposed at an edge of the surface to illuminate the entire surface.

In some embodiments, as shown in FIG. 1, two lighting assemblies 110 may be used. Each lighting assembly may be powered by a separate power supply (not shown), and may be configured to illuminate the entire surface 102. In such an embodiment, if one power supply fails, the remaining lighting assembly 110 will still illuminate the entire surface 102, although at a lesser intensity than when both lighting assemblies 110 are functioning. This provides evenly distributed illumination when both lighting assemblies 110 are functioning correctly, and continues to provide evenly distributed illumination when one lighting assembly 110 malfunctions. Accordingly, the entire surface 102 of the billboard 100 may be illuminated even when an entire lighting assembly 110 has malfunctioned and is providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies 110.

Furthermore, in some embodiments as described above, each LED 416 of a single lighting assembly 110 may be configured via the optical elements 514 to illuminate the entire surface 102. In such embodiments, if one or more LEDs 416 or strings of LEDs fails, the remaining LEDs 416 will still illuminate the entire surface 102, although at a lesser intensity than when the failed LEDs 416 are functioning. This provides evenly distributed illumination when all LEDs 416 are functioning correctly, and continues to provide evenly distributed illumination when one or more LEDs are malfunctioning. Accordingly, the billboard 100

may be illuminated even when multiple LEDs **416** have malfunctioned and are providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies **110**.

It is understood that some embodiments may direct substantially all illumination from a lighting assembly **110** evenly across the surface **102** while some illumination is not evenly distributed. For example, substantially all LEDs **416** may be directed to each evenly illuminate the surface **102** with the exception of a relatively small number of LEDs **416**. In such cases, the illumination provided by the remaining LED or LEDs **416** may be directed to one or more portions of the surface **102**. If done properly, this may be accomplished while minimizing any noticeable unevenness in the overall illumination, even if one of the remaining LEDs **416** malfunctions. For example, the lighting assembly **110** may be configured to direct the illumination provided by one LED **416** to only the left half of the surface **102**, while directing the illumination from another LED **416** to only the right half of the surface **102**. The loss of one of these two LEDs may not noticeably impact the illumination of the surface **102**. It is understood that such variations are within the scope of this disclosure.

In embodiments where the illumination is evenly distributed across the surface **102**, it is understood that the optics panel **206** may be configured specifically for the light panel **204** and the surface **102**. For example, assuming the surface **102** is forty-eight feet wide and sixteen feet high, the lens panel **500** of FIG. **5** may be specifically designed for use with the PCB **402** of FIG. **4**. This design may be based on the particular layout of the PCB **402** (e.g., the number and arrangement of the LEDs **416**), the amount of illumination provided by the LEDs **416**, the size of the surface **102**, the distance between the lens panel **500** and the surface **102**, the angle at which the lens panel **500** is mounted relative to the surface **102** (e.g., FIGS. **1B-1D**), and/or other factors. Accordingly, changes in any of these factors may entail a change in the design of the lens panel **500** in order to again evenly distribute the illumination provided by each LED **416** across the entire surface **102**. It is understood that various standard configurations of the lighting assembly **110** may be developed for various billboard and/or other externally illuminated signs so that a particular configuration may be provided based on the parameters associated with a particular billboard and/or externally illuminated sign.

Referring to FIGS. **6A-6C**, one embodiment of a lighting assembly **600** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **600** includes a back panel **602**, a light panel formed by multiple LED assemblies (denoted by reference number **800** in FIG. **8A**), and an optics panel formed by multiple lens panels **604**. Accordingly, as described previously, the light panel **204** in the current example is represented by multiple LED assemblies **800** and the optics panel **206** is represented by multiple lens panels **604**. In the present embodiment, the lighting assembly **600** includes four LED assemblies **800** and four lens panels **604**.

Although various attachment mechanisms (e.g., threaded screws, bolts, and/or other fasteners) may be used to couple the lens panels and LED assemblies to the back panel **602**, the present embodiment uses multiple threaded fasteners **605** (e.g., screws) that extend through the lens panels and the LED assemblies and engage threaded holes in the back panel **602**.

The lighting assembly **600** is also illustrated with a mounting plate **606** that couples to the back panel **602** and to an adjustable mounting bracket **608**. The adjustable

mounting bracket **608** may be used to couple the lighting assembly **600** to a portion of the billboard **100** (FIG. **1**) and/or to another support member. A power supply enclosure **610** may be coupled to the mounting plate **606** and configured contain a power supply (not shown) capable of supplying power to LEDs of the LED assemblies **800**. It is noted that separating the power supply from the back panel **602** may aid in heat dissipation by the back panel **602** as it does not have to dissipate heat from the power supply to the same extent as if the power supply was mounted directly to the back panel **602**.

The location of the power supply may also be beneficial as snow not melted by the heat produced by the LED may be melted by heat produced by the power supply. This may aid in reducing snow buildup on the LEDs.

With additional reference to FIGS. **7A** and **7B**, one embodiment of the back panel of FIG. **602** is illustrated. A front surface **700** includes multiple protrusions **702** that may be configured to protect the light panels (not shown) against moisture as previously described. The front surface **700** may include additional protrusions **704**.

A back surface **706** includes multiple fins **708** that form a heat sink to aid in the dissipation of heat from the back panel **602**. In the present example, the fins **708** are substantially rectangular in shape. In the present example, the back panel **602** is extruded and the fins **708** run parallel to the top edge with a longitudinal axis of each fin **708** being substantially parallel to a longitudinal axis of the back panel **602**. Forming the fins **708** in a vertical manner is possible, but may increase the cost of the back panel **602** due to the extrusion process. As shown, the fins **708** may be substantially perpendicular to the back surface **706**, and/or may be angled. In the present example, the fins **708** are angled such that near the top of the back panel **702**, the fins **708** are angled towards the top.

Because the fins **708** are parallel to the top edge, heat may be trapped due to its inability to rise vertically. Accordingly, holes **710** may be present in some or all of the fins **708** (marked but not actually visible in the side view of FIG. **7B**) to provide paths for the heat to rise vertically in spite of the orientation of the fins **708**. The holes **710** may create a chimney effect that increases air flow across the fins **708** and aids in the cooling process. In some embodiments, some or all of the fins **708** may be angled such that heat is not trapped.

The back surface **706** may also include a groove **712** that is configured to receive a tongue of the mounting plate **606** in a tongue-in-groove manner.

With additional reference to FIGS. **8A-8J**, embodiments of a single LED assembly **800** and a single lens panel **604** that may be used with the lighting assembly **600** are illustrated. As shown, the single LED assembly **800** and the single optics panel **604** may be configured for use together.

Referring specifically to FIG. **8A**, the LED assembly **800** includes a substrate **802** (e.g., a PCB) onto which are mounted multiple LEDs **804**. In the present example, the LED assembly **800** includes two strings of eight LEDs **804** each for a total of sixteen LEDs **804**. It is understood that this is merely an example, and there may be more or fewer LEDs **804** on the light panel **800**, and the LEDs **804** may be arranged in many different ways on the substrate **802**.

Referring also to FIGS. **8B-8J**, the optics panel **604** may include optical elements **806** arranged on an upper surface **808** of the optics panel **604**. The optics panel **604** may further include sides **810**, **812**, **814**, and **816** that are configured to fit around the edge of the substrate **802** of the light panel **800**. The bottom edge of each side **810**, **812**, **814**, and

816 abuts the front surface **700** of the back panel **602** and may be sealed to the front surface **700** using a moisture resistant sealant.

As shown in FIGS. **8D-8H**, a single optical element **806** may include multiple lens elements designed to distribute the illumination provided by a single LED **804** across a surface such as the surface **102** of FIG. **1**. A first lens element **820** may be positioned proximate to the LED **804**, and additional lens elements **822**, **824**, and **826** may be positioned above the lens element **820**. Multiple optical elements **806** may be combined and formed as a single optics panel **604** that is configured to operate with the LED assembly **800**.

Referring to FIG. **9**, another embodiment of a lighting assembly **900** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **900** is similar to the lighting assembly **600** of FIG. **6**, but includes six LED assemblies rather than the four six LED assemblies of the lighting assembly **600**. It is understood that the lighting assembly **900** may require a larger power supply than the lighting assembly **600** (e.g., a one hundred and fifty watt power supply instead of a one hundred and twenty watt power supply).

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. An apparatus comprising a lighting assembly for illumination of an area, the lighting assembly comprising:

a substantially planar substrate;

a plurality of light emitting diodes (LEDs) arranged in a plurality of rows on a first surface of the substrate, the rows extending along a longitudinal axis in a plane of the first surface of the substrate;

a plurality of optical elements, wherein each optical element of the plurality of optical elements is proximate an associated LED of the plurality of LEDs such that each optical element overlies a single LED and each LED underlies a single optical element, each optical element comprising a first part, a second part and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak relative to the substrate, the peak being spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED; and

a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the substrate so that each and every LED is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate.

2. The apparatus of claim **1**, wherein substantially planar substrate comprises a single substrate.

3. The apparatus of claim **1**, wherein each optical element of the plurality of optical elements is separate from other optical elements of the plurality of optical elements.

4. The apparatus of claim **1**, wherein the heat sink comprises a discrete heat sink.

5. The apparatus of claim **1**, wherein the heat sink comprises an aluminum heat sink.

6. The apparatus of claim **1**, wherein the fins are substantially flat.

7. The apparatus of claim **1**, wherein the LEDs are arranged in only two rows.

8. The apparatus of claim **1**, further comprising a power supply that is separated from the substrate.

9. The apparatus of claim **1**, further comprising a billboard comprising the area, wherein the lighting assembly is located adjacent the billboard to illuminate the area, the fins extending in a direction away from the billboard.

10. The apparatus of claim **1**, further comprising a billboard comprising the area, wherein the lighting assembly is located adjacent the billboard to illuminate all of the area when a subset of the LEDs is not generating any light.

11. The apparatus of claim **1**, further comprising a billboard comprising the area, wherein the optical elements are configured so that failure of one or more LEDs of the lighting assembly will cause an illumination level of light impinging the area to decrease while a uniformity of the light impinging the area remains substantially the same as compared to when all LEDs are operational.

12. An apparatus comprising a lighting assembly for illumination of an area, the lighting assembly comprising:

a substantially planar substrate;

a plurality of light emitting diodes (LEDs) arranged in a plurality of rows on a first surface of the substrate, wherein the LEDs are arranged in only two rows, the rows extending along a longitudinal axis in a plane of the first surface of the substrate;

a plurality of optical elements attached to the substrate by threaded fasteners, wherein each optical element of the plurality of optical elements is separate from other optical elements of the plurality of optical elements, and wherein each optical element of the plurality of optical elements is proximate an associated LED of the plurality of LEDs such that each optical element overlies a single LED and each LED underlies a single optical element, wherein each optical element includes a first part, a second part and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak relative to the substrate, the peak being spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED;

a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the substrate so that each and every LED is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, each fin extending along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate, and

11

wherein the first section of the heat sink includes a portion that extends past the substrate in a direction away from the fins; and

a power supply that is separated from the substrate.

13. A billboard comprising:

a support structure;

a display surface mounted on the support structure; and

a lighting assembly located so as to be able to illuminate a portion of the display surface during operation, wherein the lighting assembly comprises:

a substantially planar substrate;

a plurality of light emitting diodes (LEDs) arranged in a plurality of rows on a first surface of the substrate;

a plurality of optical elements, wherein each optical element of the plurality of optical elements is proximate an associated LED of the plurality of LEDs such that each optical element overlies a single LED and each LED underlies a single optical element, wherein each optical element includes a first part, a second part and a third part, wherein the first part comprises a first curved surface, wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak relative to the substrate, the peak being spaced from the region between the first part and the second part, and wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED; and

a heat sink thermally coupled to a second surface of the substrate, the second surface opposite the first surface, the heat sink comprising a first section substantially parallel to the substrate so that each and every LED of the plurality of LEDs is separated from the heat sink by the substrate, the heat sink further comprising a plurality of fins extending away from the first section and substantially perpendicular thereto, wherein the first section of the heat sink includes a portion that extends past the substrate in a direction away from the fins.

14. The billboard of claim **13**, wherein the rows of LEDs extend along a longitudinal axis in a plane of the first surface of the substrate, and wherein each fin extends along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate.

15. The billboard of claim **13**, wherein the optical elements are configured so that failure of one or more LEDs of the lighting assembly will cause an illumination level of light impinging the portion of the display surface to decrease while uniformity of the light impinging the portion of the display surface remains substantially the same as compared to when all LEDs are operational.

16. The billboard of claim **13**, wherein the lighting assembly further comprises a second planar substrate with LEDs arranged thereon, the second substrate arranged in a common orientation with the substrate so that all of the LEDs of the substrate and the second substrate are arranged in a common orientation, wherein all of the substrate and the second substrate are mounted in a single assembly.

17. The billboard of claim **16**, wherein the heat sink extends across both the substrate and the second substrate.

18. The billboard of claim **13**, further comprising a second lighting assembly located adjacent the lighting assembly and

12

located so as to be able to illuminate a second portion of the display surface during operation, wherein the second lighting assembly comprises:

a second substantially planar substrate;

a second plurality of light emitting diodes (LEDs) arranged in a plurality of rows on a first surface of the second substrate, wherein the rows of the second plurality of LEDs extend along a longitudinal axis in a plane of the first surface of the second substrate;

a second plurality of optical elements, wherein each optical element of the second plurality of optical elements is proximate an associated LED of the second plurality of LEDs such that each optical element of the second plurality overlies a single LED and each LED of the second plurality underlies a single optical element; and

a second heat sink thermally coupled to a second surface of the second substrate, the second surface opposite the first surface, the second heat sink comprising a first section substantially parallel to the second substrate so that each and every LED of the second plurality of LEDs is separated from the second heat sink by the second substrate, the second heat sink further comprising a second plurality of fins extending away from the first section of the second heat sink and substantially perpendicular thereto, wherein the first section of the second heat sink includes a portion that extends past the second substrate in a direction away from the second plurality of fins, wherein each fin extends along an axis in the plane of the first surface of the second substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the second substrate.

19. The billboard of claim **18**, wherein the display surface has visual media content displayed thereon, the visual media content comprising a picture and/or text;

wherein the display surface has a width of forty-eight feet along each of an upper edge and a lower edge of the display surface and a height of fourteen feet along each of a left side edge and a right side edge of the display surface;

wherein the portion of the display surface extends from the lower edge to the upper edge adjacent the left side edge and the second portion extends from the lower edge to the upper edge adjacent the right side edge, the portion and the second portion together extending from the left side edge to the right side edge;

wherein the lighting assembly is configured to illuminate the portion of the display surface; and

wherein the second lighting assembly is configured to illuminate the second portion of the display surface.

20. The billboard of claim **19**, wherein the display surface can be illuminated using only the lighting assembly and the second lighting assembly so that the visual media content can be viewed without additional light.

21. A method of illuminating visual media content on a billboard display surface using a lighting assembly that comprises a power supply and a lighting unit that includes a substrate, a plurality of light emitting diodes (LEDs) arranged on the substrate, a plurality of optical elements, and a heat sink, the method comprising:

directing light from the LEDs toward a portion of the billboard display surface such that the light from the lighting unit illuminates the visual media content on the portion of the billboard display surface with an illumination level and a uniformity; and

13

directing heat generated by the LEDs away from the optical elements using the heat sink;
 wherein the plurality of LEDs are arranged in a plurality of rows on a first surface of the substrate, the rows extending along a longitudinal axis in a plane of the first surface of the substrate;
 wherein each optical element of the plurality of optical elements is proximate an associated LED of the plurality of LEDs such that each optical element overlies a single LED and each LED underlies a single optical element;
 wherein each optical element of the plurality of optical elements is separate from other optical elements of the plurality of optical elements;
 wherein each optical element includes a first part, a second part and a third part;
 wherein the first part comprises a first curved surface;
 wherein the second part comprises a second curved surface that intersects with the first curved surface at a region between the first part and the second part, wherein the first part and the second part each have a peak relative to the substrate, the peak being spaced from the region between the first part and the second part;
 wherein the third part extends beyond the region between the first part and the second part in a direction away from the associated LED;
 wherein the heat sink is thermally coupled to a second surface of the substrate, the second surface opposite the first surface;
 wherein each and every LED of the plurality of LEDs is separated from the heat sink by the substrate;
 wherein the heat sink comprises a first section substantially parallel to the substrate and a plurality of fins extending away from the first section and substantially perpendicular thereto; and

14

wherein each fin extends along an axis in the plane of the first surface of the substrate, the axis for each fin being substantially perpendicular to the longitudinal axis of the first surface of the substrate.

22. The method of claim 21, wherein directing light from the LEDs comprises providing power to the LEDs from the power supply, wherein the power supply is separated from the substrate so that the heat sink does not dissipate heat from the power supply to the same extent as if the power supply was mounted directly to the substrate.

23. The method of claim 21, further comprising directing light from a second lighting unit toward the portion of the billboard display surface at the same time as directing light from the LEDs toward the portion of the billboard display surface.

24. The method of claim 21, further comprising directing light from a second lighting unit toward a second portion of the billboard display surface at the same time as directing light from the LEDs toward the portion of the billboard display surface, wherein the visual media content can be viewed using only the light directed from the lighting unit and the second lighting unit.

25. The method of claim 21, wherein directing light from the LEDs comprises illuminating the visual media content on the portion of the billboard display surface with the illumination level and the uniformity, wherein the optical elements are configured so that failure of one or more LEDs of the lighting unit will cause the illumination level of the light impinging the portion of the billboard display surface to decrease while the uniformity of the light impinging the portion of the billboard display surface remains substantially the same.

* * * * *