

Earthmover Tyres



Driven The World Over®





REM-1

REM-1

FEATURES AND BENEFITS:



(G2/L2)
GRADER

- All-purpose tread design to provide exceptional traction and even wear.
- Wide footprint offers excellent flotation and smooth ride.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
13.00R24	★	40KM/H	1296	352	30	8.00TG	146	3000kg/375kpa	G2/L2
14.00R24	★	40KM/H	1365	385	30	8.00TG	153	3650kg/375kpa	G2/L2



REM-2

REM-2



(E3/L3)
EARTHMOVER
LOADER

- Enhanced self-cleaning design for all purpose applications.
- Multi-function, non-directional tread design for optimum usage on equipment.
- Superior traction in sand, stone, mud and other surfaces.
- OEM Certified.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
17.5R25	★	50KM/H	1340	448	27	14.00/1.5	157	4125kg/350kpa	E3/L3
		10KM/H	1340	448	27	14.00/1.5	176	7100kg/450kpa	
17.5R25	★★	50KM/H	1480	527	31	17.00/2.0	168	5600kg/350kpa	E3/L3
		10KM/H	1480	527	31	17.00/2.0	186	9500kg/450kpa	
20.5R25	★	50KM/H	1617	600	36	19.5/2.5	176	7100kg/350kpa	E3/L3
		10KM/H	1617	600	36	19.5/2.5	195	12150kg/450kpa	
20.5R25	★★	50KM/H	1748	695	37.5	22.00/3.0	184	9000kg/350kpa	E3/L3
		10KM/H	1748	695	37.5	22.00/3.0	202	15000kg/450kpa	
23.5R25	★	50KM/H	1340	448	27	14.00/1.5	167	5450kg/450kpa	E3/L3
		10KM/H	1340	448	27	14.00/1.5	182	8500kg/575kpa	
23.5R25	★★	50KM/H	1480	527	31	17.00/2.0	177	7300kg/450kpa	E3/L3
		10KM/H	1480	527	31	17.00/2.0	193	11500kg/575kpa	
26.5R25	★	50KM/H	1617	600	36	19.50/2.5	185	9250kg/450kpa	E3/L3
		10KM/H	1617	600	36	19.50/2.5	201	14500kg/575kpa	
26.5R25	★★	50KM/H	1748	695	37.5	22.00/3.0	193	11500kg/450kpa	E3/L3
		10KM/H	1748	695	37.5	22.00/3.0	209	18500kg/575kpa	
29.5R25	★★	50KM/H	1860	748	40	25.00/3.5	200	14000kg/450kpa	E3/L3
		10KM/H	1860	748	40	25.00/3.5	216	22400kg/575kpa	



REM-15

REM-15

FEATURES AND BENEFITS:

- Tread design to provide good traction and grip.
- Open pattern design is suitable for soft ground.
- Wide footprint improves the tyre abrasion resistant performance.



(E3/L3)
EARTHMOVER
LOADER

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
17.5R25	★	10KM/H	1340	458	29	14.00/1.5	176	7100kg/450kpa	L2
	★★	10KM/H	1340	458	29	14.00/1.5	182	8500kg/575kpa	L2



REM-10

REM-10

FEATURES AND BENEFITS:

- Multi-function, non-directional tread design for optimum usage on equipment.
- Superior traction in sand, stone, mud and other surfaces enhanced smooth ride and even wear.



(E3+/L3+)
HAULAGE
ARTICULATED

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
26.5R25	★★	50KM/H	1754	695	40.5	22.00/3.0	193	11500kg/450kpa	E3/L3
	★★	10KM/H	1754	695	40.5	22.00/3.0	209	18500kg/575kpa	E3/L3
29.5R25	★★	50KM/H	1868	748	44	25.00/3.5	200	14000kg/450kpa	E3/L3
	★★	10KM/H	1868	748	44	25.00/3.5	216	22400kg/575kpa	E3/L3



REM-8

REM-8

FEATURES AND BENEFITS:



(MCS)
HIGH SPEED CRANE

- High speed mobile crane tire designed for both on & off highway applications.
- New generation tread pattern increases traction while minimizing fuel consumption.
- DOT approved for on highway use.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
14.00R24	★★★	70KM/H	1364	396	25	10.00W	170	6340kg/1000kPa	E2
14.00R25	★★★	70KM/H	1364	396	25	10.00/1.5	170	6340kg/1000kPa	E2
385/95R25	★★	80KM/H	1364	396	25	10.00/1.5	170	6000kg/900kPa	E2
385/95R25	/	90KM/H	1364	396	25	10.00/1.5	170	6000kg/900kPa	E2
16.00R25	★★★	70KM/H	1488	432	26	11.25/2.0	177	7400kg/900kPa	E2
16.00R25	★★	80KM/H	1488	432	26	11.25/2.0	174	6700kg/900kPa	E2
20.5R25	★★	70KM/H	1490	540	31	17.00/2.0	179	7757kg/703kPa	E2



REM-18

REM-18

FEATURES AND BENEFITS:



(L5)
LOADER

- Extra deep open pattern provides excellent traction.
- Excellent puncture resistance and cut resistant performance.
- Reinforced carcass ensures longer using life.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
35/65R33	★	10KM/H	2056	934	98	28.00/3.5	217	23000kg/500kPa	L5
	★★	10KM/H	2056	934	98	28.00/3.5	223	27250kg/650kPa	L5



REM-12

REM-12

FEATURES AND BENEFITS:



(L5)
MINING LOADER

- Extra deep tread provides excellent traction.
- Good puncture resistance and cut resistant performance.
- Reinforced shoulder design can adapt harsh operation condition.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
17.5R25	★	6KM/H	1400	470	66.5	14.00/1.5	174	6600kg/450kPa	L5
	★★	6KM/H	1400	470	66.5	14.00/1.5	182	8500kg/575kPa	
26.5R25	★	10KM/H	1800	690	92	22.00/3.0	202	15000kg/450kpa	L5
	★★	10KM/H	1800	690	92	22.00/3.0	209	18500kg/575kpa	
29.5R25	★	10KM/H	1905	775	100	25.00/3.5	208	18000kg/450kpa	L5
	★★	10KM/H	1905	775	100	25.00/3.5	216	22400kg/575kpa	



REM-19

REM-19

FEATURES AND BENEFITS:



(L5)
LOADER

- Non-directional tread pattern with center rib provides enhanced traction
- Wide footprint for stability; center riding rib for ride comfort
- Special cut/chip resistance compounds extend tyre life and promote retreadability

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
20.5R25	★	10KM/H	1530	536	72	17.00/2.0	186	9500kg/450kpa	L5
	★★	10KM/H					193	11500kg/575kpa	
23.5R25	★	10KM/H	1662	612	78	19.50/2.5	195	12150kg/450kpa	L5
	★★	10KM/H					201	14500kg/575kpa	
26.5R25	★	10KM/H	1800	690	92	22.00/3.0	202	15000kg/450kpa	L5
	★★	10KM/H					209	18500kg/575kpa	L5
29.5R25	★	10KM/H	1905	775	100	25.00/3.5	208	18000kg/450kpa	L5
	★★	10KM/H					216	22400kg/575kpa	L5



REM-7

REM-7

FEATURES AND BENEFITS:

- Suitable for large scale shovel machinery
- Optimized block design improves traction and handling performance
- Reasonable optimization of grounding area helps abrasion-resistance



(E3)
EARTHMOVER
LOADER

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
33.25R29	★★	50KM/H	2060	850	45	27.00/3.5	209	18500kg/500kpa	E3



REM-9

REM-9

FEATURES AND BENEFITS:

- Deep tread groove provides good traction.
- High strength special steel wire ensures tyre safety.
- Using special curing technology in order to ensure reliable product quality.



(E4)
HAULAGE

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
26.5R25	★★	50KM/H	1782	672	55	22.00/3.0	193	11500kg/450kpa	E4
		10KM/H	1782	672	55	22.00/3.0	209	18500kg/575kpa	E4
29.5R25	★★	50KM/H	1905	750	60	25.00/3.5	200	14000kg/450kpa	E4
		10KM/H	1905	750	60	25.00/3.5	216	22400kg/575kpa	E4
18.00R33	★★	50KM/H	1865	498	53	13.00/2.5	191	10900kg/650kpa	E4
		10KM/H	1865	498	53	13.00/2.5	209	18500kg/800kpa	E4
21.00R33	★★	50KM/H	1964	565	55	15.00/3.0	200	14000kg/650kpa	E4
		10KM/H	1964	565	55	15.00/3.0	218	23600kg/800kpa	E4
24.00R35	★★	50KM/H	2160	652	69	17.00/3.5	209	18500kg/650kpa	E4
		10KM/H	2160	652	69	17.00/3.5	227	30750kg/800kpa	E4



REM-28S

REM-28S

FEATURES AND BENEFITS:

- Excellent traction for snow and ice conditions.
- Wide footprint offers excellent floatation and smooth ride.
- For use on loaders and graders where enhanced winter performance is required.



(E2)
EARTHMOVER
LOADER

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
385/95R24	★★	50KM/H	1360	396	25	10.00	168	5600kg/700kPa	E2
385/95R25	★★★	70KM/H	1360	396	25	10.00/1.5	170	6340kg/1000kPa	E2
17.5R25	★★	50KM/H	1340	455	27	14.00/1.5	167	5450kg/525kPa	E2
		10KM/H	1340	455	27	14.00/1.5	182	8500kg/650kPa	E2
20.5R25	★★	50KM/H	1484	540	31	17.00/2.0	177	7300kg/525kPa	E2
		10KM/H	1484	540	31	17.00/2.0	193	11500kg/650kPa	E2
23.5R25	★★	50KM/H	1617	600	36	19.50/2.5	185	9250kg/450kPa	E2
		10KM/H	1617	600	36	19.50/2.5	201	14500kg/575kPa	E2



REM-21

REM-21

FEATURES AND BENEFITS:

- New designed tire pattern provides tyre strong traction and handling.
- Enhanced tyre crown and shoulder design improves tire-resistance against gnaw and puncture.
- Enhanced tyre design provide better tearing-resistance performance and extends service life.



(E3/L3)
EARTHMOVER
LOADER

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
14.00R24	★★★	50KM/H	1366	375	28	10.00/1.5	169	5800kg/700kPa	E3/L3
	★★★	10KM/H	1366	375	28	10.00/1.5	188	10000kg/950kPa	E3/L3
14.00R25	★★★	50KM/H	1366	375	28	10.00/1.5	169	5800kg/700kPa	E3/L3
	★★★	10KM/H	1366	375	28	10.00/1.5	188	10000kg/950kPa	E3/L3
16.00R25	★★★	10KM/H	1495	435	30	11.25/2.0	197	12850kg/900kPa	L3



REM-9

REM-9

FEATURES AND BENEFITS:



(E4)
HAULAGE

- Deep tread groove provides good traction.
- High strength special steel wire ensures tyre safety.
- Using special curing technology in order to ensure reliable product quality.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
27.00R49	★★	50KM/H	2696	750	75	19.50/4.0	223	27250kg/700(TRA)kpa	E4



REM-11

REM-11

FEATURES AND BENEFITS:



(E4)
HAULAGE

- High strength steel wire ensures tyre safety and life under high load operation condition.
- Using special curing technology ensures reliable product quality.
- Special pattern design provides excellent handling and traction performance, extending tyre using life.
- Special tread compound meets the demand of handling performance and improves the abrasion resistance performance.
- The protection of sidewall effectively prevents damage under complex operation condition.

TYRE SIZE	LOAD SYMBOL	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	NOTE
33.00R51	★★	50KM/H	3060	890	88	24.00/5.0	223	38750kg/700(TRA)kpa	E4
36.00R51	★★	50KM/H	3240	980	90	26.00/5.0		46250kg/700(TRA)kpa	E4
37.00R57	★★	50KM/H	3425	1040	98	27.00/6.0		53000kg/725(CAS)kpa	E4
40.00R57	★★	50KM/H	3590	1110	98	29.00/6.0		60000kg/725(CAS)kpa	E4