

Industrial Tyres



Driven The World Over®





REM-3

REM-3

FEATURES AND BENEFITS:



(SS)
SKID STEER

Specially designed for skid steer loaders

- Reinforced tread and sidewall design provides good anti-puncture performance.
- New pattern design ensures excellent abrasion resistance performance.
- Special tread compound provides good antistatic performance.

TYRE SIZE	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	SPEED SYMBOL
10R16.5	25KM/H	773	264	18.5	8.25	128	1800kg/375kPa	A5
12R16.5	25KM/H	832	315	23	9.75	141	2575kg/375kPa	A5



REM-6

REM-6

FEATURES AND BENEFITS:



(IND)
INDUSTRIAL
LUG

An excellent tyre used on forklifts, terminal tractors and other industrial equipment.

- Flat tread pattern for maximum performance.
- Operations confidence.
- Optimal stability.

TYRE SIZE	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	SPEED SYMBOL
5.00R8	25KM/H	468	137	24.5	3.00D	111	1090kg/1000kPa	A5
6.00R9	25KM/H	540	162	25	4.00E	121	1450kg/1000kPa	A5
6.50R10	25KM/H	585	180	27	5.0	128	1800kg/1000kPa	A5
7.00R12	25KM/H	670	190	28	5.00S	136	2240kg/1000kPa	A5
7.00R15	25KM/H	736	195	28	5.5	143	2725kg/1000kPa	A5
7.50R15	25KM/H	770	215	30	6.0	146	3000kg/1000kPa	A5
8.25R15	25KM/H	838	232	32	6.5	153	3250kg/1000kPa	A5
225/75R15	25KM/H	706	230	25	7.0	149	3650kg/1000kPa	A5
250/70R15	25KM/H	736	252	26.5	7.0	153	3650kg/1000kPa	A5
315/70R15	25KM/H	835	312	36	8.0	165	5150kg/1000kPa	A5
10.00R20	25KM/H	1062	294	35	7.5	166	5300kg/1000kPa	A5
12.00R20	25KM/H	1136	320	41	8.5	176	7100kg/1000kPa	A5
12.00R24	25KM/H	1232	322	39	8.5	178	7500kg/1000kPa	A5
14.00R24	25KM/H	1416	390	64	10.0	193	11500kg/1000kPa	A5
18.00R25	25KM/H	1656	522	63.5	13.00/2.5	207	17500kg/1000kPa	A5



REM-17

REM-17

FEATURES AND BENEFITS:



**AIRCRAFT
TOW
TRACTOR**

Flat, wide tread face provides optimum performance and wear

- Special tread compounds fight rapid wear and scrub
- Exceptional stability with reduced lateral movement in a wide variety of applications including port applications

TYRE SIZE	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	SPEED SYMBOL
16.00R25	25KM/H	1495	424	56	11.25/2.0	200	14000kg/1000kPa	A5



REM-26

REM-26

FEATURES AND BENEFITS:



**(IND)
INDUSTRIAL
LUG**

New designed industrial tyre pattern has excellent adaptability for roads in ports and airports

- Deep tyre pattern and wide tread design extend service life
- The design of the hill reinforcement and anti-stone structure give the tyre more resistance of puncture.
- Tortuous grooves provide greater traction and grip

TYRE SIZE	SPEED	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	RIM	LOAD INDEX	SINGLE MAX LOAD PRESSURE	SPEED SYMBOL
315/70R15	25KM/H	828	316	31	8.0	165	5150kg/1000kPa	A5
12.00R20	25KM/H	1122	320	36	8.5	176	7100kg/1000kPa	A5