



Effective: 01-01-26

Red Pine Pole Specs

<u>Length</u>	<u>Rate Per Pole</u>	
30	POR	
	<i>Minimum circumference at 6' mark: 33" (11" dbh)</i>	
35	POR	
	<i>Minimum circumference at 6' mark: 38" (12" dbh)</i>	
40	POR	
	<i>Minimum circumference at 6' mark: 40" (13" dbh)</i>	
45	POR	
	<i>Minimum circumference at 6' mark: 46" (14" dbh)</i>	
50	POR	
	<i>Minimum circumference at 6' mark: 48" (15" dbh)</i>	
55	POR	
	<i>Minimum circumference at 6' mark: 50" (17" dbh)</i>	
60	POR	
	<i>Minimum circumference at 6' mark: 52" (18" dbh)</i>	
65	POR	
	<i>Minimum circumference at 6' mark: 54" (20" dbh)</i>	

Pole Specifications

- Trim Allowance of a minimum 1.5-2 ft in excess of the lengths above is required.
- Deep side scars or surface pitch pockets are not acceptable.
- Excessive crook or sweep is not accepted. The pole must stay within center line.
- No double sweep.
- No sheared butts.
- Excessive quantities of knots or excessively large knots that decrease the strength of the pole are not acceptable. Limbs in excess of 4" are not acceptable

Pay Schedule and Receiving

Anything received by Wednesday 3pm is processed on same Friday.
Hours of Operation: 7-3:30
Unloading outside of operating hours need to be arranged prior to Delivery.