



# FLEXX FLOW BELTING

## 1/8" PITCH X .050" WIRE

FLEXX FLOW BELTING is ideal for breading, cooking, battering, coating, or almost any processing application from freezing up to +500F. It has a wide range of uses in processing meat, poultry, seafood, baked goods, cereal, candy, and electronic P.C. board cleaning.

FLEXX FLOW BELTING is manufactured in Lancaster, PA, according to standard industry specifications and can be spliced directly into existing belts of this type.

FLEXX FLOW BELTING is easy to clean. The flow through design allows for unrestricted wash down and inspection.

FLEXX FLOW BELTING is light weight, easy to handle, and quick to install. Belt may be made endless without seams.

FLEXX FLOW BELTING is sprocket driven, providing positive drive and consistent tracking. Sprockets are available in various sizes to meet your needs.

FLEXX FLOW BELTING is designed to articulate around small diameter drive and tail rolls for tight transfers. This ensures gentle handling and constant positioning of the product.

---


### LUMSDEN FLEXX FLOW INC.

P.O. BOX 4647 • LANCASTER, PENNSYLVANIA 17604 • (717) 394-6871 FAX (717) 394-1640  
**1-800-367-3664**

# FLEXX FLOW

## 1/8" PITCH X .050" WIRE

↓ SPACE BETWEEN WIRES .117



WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH
3"	1	2.624	26"	9	2.847	47 5/8"	17	2.779
8"	3	2.541	28"	11	2.511	48"	17	2.801
10"	3	3.208	30"	11	2.693	50"	19	2.612
12"	5	2.325	32"	11	2.875	54"	19	2.822
14"	5	2.725	34"	13	2.586	58"	19	3.033
18"	7	2.518	36"	13	2.740	60"	21	2.839
20"	7	2.803	38"	13	2.894	63"	21	2.982
22"	7	3.089	40"	15	2.642	72"	29	2.470
24"	9	2.625	42"	15	2.775			

All other widths, not listed here, are also available and can be ordered by width, specification or belt number.

**BELT WIDTH:** 3" to 14'

**WIDTH TOLERANCE:** +,-1/16 to 36"  
 +,-3/32 for 36" to 60"  
 +,-3/8 for 60" up

**MATERIALS:** 302 Stainless Steel  
 High Tensile Strength Wire.  
 .050" Diameter.

**BELT WEIGHT:** Approximately .50 lbs.  
 per sq. ft.

**BELT LENGTH:** Unlimited, except by  
 strength requirements.

**WIRES:** 70 to 72 Wires per linear foot

**SPEED:** 30 FPM recommended max. speed.

**SPROCKETS:** See sprocket literature for  
 sizes and dimensions.

