



# FLEXX FLOW BELTING

## 1/2" PITCH X .072" WIRE

FLEXX FLOW BELTING is ideal for breading, cooking, battering, coating, or almost any processing application from freezing up to +500F. It has a wide range of uses in processing meat, poultry, seafood, baked goods, cereal, candy, and electronic P.C. board cleaning.

FLEXX FLOW BELTING is manufactured in Lancaster, PA, according to standard industry specifications and can be spliced directly into existing belts of this type.

FLEXX FLOW BELTING is easy to clean. The flow through design allows for unrestricted wash down and inspection.

FLEXX FLOW BELTING is light weight, easy to handle, and quick to install. Belt may be made endless without seams.

FLEXX FLOW BELTING is sprocket driven, providing positive drive and consistent tracking. Sprockets are available in various sizes to meet your needs.

FLEXX FLOW BELTING is designed to articulate around small diameter drive and tail rolls for tight transfers. This ensures gentle handling and constant positioning of the product.

---

**LUMSDEN FLEXX FLOW INC.**

P.O. BOX 4647 • LANCASTER, PENNSYLVANIA 17604 • (717) 394-6871 FAX (717) 394-1640  
**1-800-367-3664**

# FLEXX FLOW

## 1/2" PITCH X .072" WIRE

ACTUAL SIZE

SPACE BETWEEN WIRES .428

11  
32"

SPACE WIDTH

SPACE WIDTH

SPACE WIDTH

11  
32"

BELT WIDTH

WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH
2"	1	1.312	20"	9	2.146	40"	15	2.621
2 1/2"	1	1.812	21"	7	2.902	40"	19	2.069
3"	1	2.312	22"	9	2.368	42"	13	3.178
4"	1	3.312	24"	7	3.330	42"	15	2.754
4"	3	1.104	24"	9	2.590	42"	19	2.174
5"	1	4.312	24"	11	2.119	44"	17	2.548
5"	3	1.437	24"	13	1.793	46"	17	2.665
6"	3	1.771	25"	9	2.701	46"	21	2.158
6 1/2"	3	1.937	26"	9	2.812	48"	15	3.154
7"	3	2.104	26"	11	2.301	48"	17	2.783
8"	3	2.437	27"	9	2.924	48"	23	2.057
8"	5	1.462	28"	9	3.035	48"	25	1.892
9"	5	1.662	28"	11	2.483	50"	17	2.901
10"	3	3.104	30"	11	2.665	52"	23	2.231
10"	5	1.862	30"	13	2.255	54"	19	2.806
10 1/2"	5	1.962	30"	15	1.954	54"	21	2.539
11"	5	2.062	30"	17	1.724	54"	27	1.975
12"	5	2.262	32"	11	2.846	58"	21	2.729
13"	5	2.462	32"	13	2.409	60"	21	2.824
14"	5	2.662	32"	17	1.842	60"	29	2.045
14 1/2"	7	1.973	34"	13	2.562	62"	23	2.666
15"	5	2.862	35"	13	2.639	64"	21	3.015
15"	7	2.045	36"	13	2.716	66"	23	2.840
16"	7	2.187	36"	15	2.354	68"	21	3.205
17"	7	2.330	36"	17	2.077	70"	29	2.390
18"	7	3.473	36"	21	1.681	72"	25	2.852
18"	9	1.924	38"	15	2.487	80"	35	2.266
20"	7	2.759	38"	17	2.195	92"	29	3.149

All other widths, not listed here, are also available and can be ordered by width, specification or belt number.

**BELT WIDTH:** 2" to 14'

**WIDTH TOLERANCE:** +,-1/16 to 36"  
+,-3/32 for 36" to 60"  
+,-3/8 for 60" up

**MATERIALS:** 302 Stainless Steel  
High Tensile Strength Wire.  
.072" Diameter.

**BELT WEIGHT:** Approximately .48 lbs.  
per sq. ft.

**BELT LENGTH:** Unlimited, except by  
strength requirements.

**WIRES:** 24 Wires per linear foot

**SPEED:** 60 FPM recommended max. speed.

**SPROCKETS:** See sprocket literature for  
sizes and dimensions.

