



FLEXX FLOW BELTING

3/8" PITCH X .050" WIRE

FLEXX FLOW BELTING is ideal for breading, cooking, battering, coating, or almost any processing application from freezing up to +500F. It has a wide range of uses in processing meat, poultry, seafood, baked goods, cereal, candy, and electronic P.C. board cleaning.

FLEXX FLOW BELTING is manufactured in Lancaster, PA, according to standard industry specifications and can be spliced directly into existing belts of this type.

FLEXX FLOW BELTING is easy to clean. The flow through design allows for unrestricted wash down and inspection.

FLEXX FLOW BELTING is light weight, easy to handle, and quick to install. Belt may be made endless without seams.

FLEXX FLOW BELTING is sprocket driven, providing positive drive and consistent tracking. Sprockets are available in various sizes to meet your needs.

FLEXX FLOW BELTING is designed to articulate around small diameter drive and tail rolls for tight transfers. This ensures gentle handling and constant positioning of the product.


LUMSDEN FLEXX FLOW INC.

P.O. BOX 4647 • LANCASTER, PENNSYLVANIA 17604 • (717) 394-6871 FAX (717) 394-1640
1-800-367-3664

FLEXX FLOW

3/8" PITCH X .050" WIRE

↑ SPACE BETWEEN WIRES .236" ↓



WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH
2"	1	1.438	24"	11	2.130	40"	21	1.878
3"	1	2.438	26"	13	1.957	42"	15	2.763
5"	3	1.479	27"	11	2.403	42"	21	1.973
6"	3	1.813	28"	11	2.494	44"	21	2.068
8"	3	2.479	29"	11	2.585	45"	21	2.116
8"	5	1.488	29"	15	1.895	46"	23	1.976
9"	3	2.813	30"	11	2.676	48"	21	2.259
9"	5	1.688	30"	13	2.264	50"	21	2.354
10"	3	3.146	30"	15	1.962	50"	25	1.978
10"	5	1.888	30-1/2"	11	2.722	52"	23	2.236
11"	5	2.088	31"	13	2.341	52"	27	1.905
12"	5	2.288	31"	15	2.029	54"	21	2.545
12"	7	1.634	32"	11	2.858	57"	19	2.970
14"	5	2.688	32"	13	2.418	58"	25	2.298
15"	7	2.062	32"	15	2.096	58"	27	2.127
16"	7	2.205	33"	13	2.495	60"	25	2.378
16-1/2"	7	2.277	34"	13	2.572	60"	33	1.801
17"	7	2.348	34"	17	1.967	70"	27	2.572
18"	7	2.491	35"	17	2.026	72"	29	2.463
18"	9	1.937	36"	13	2.726	72"	33	2.165
19-1/2"	9	2.104	36"	15	2.362	76"	29	2.601
20"	7	2.777	36"	17	2.084	84"	33	2.528
20"	9	2.160	38"	15	2.496	96"	27	3.535
21"	9	2.271	38"	17	2.202	114"	47	2.414
22"	9	2.382	39"	15	2.562	120"	49	2.438
23"	9	2.493	39-1/2"	19	2.049	128"	49	2.601
24"	7	3.348	40"	15	2.629	144"	59	2.431
24"	9	2.604	40"	17	2.320	144"	57	2.516

All other widths, not listed here, are also available and can be ordered by width, specification or belt number.

BELT WIDTH: 2" to 14'

WIDTH TOLERANCE: +, -1/16 to 36",
 +, -3/32 for 36" to 60"
 +, -1/8 for 60" up

MATERIALS: 302 Stainless Steel High
 Tensile Strength Wire.
 .050" Diameter

BELT WEIGHT: Approximately .35 lbs.
 per sq. ft.

BELT LENGTH: Unlimited, except by
 strength requirements.

WIRES: 42 Wires per linear foot

SPEED: 30 FPM recommended max. speed.

SPROCKETS: See sprocket literature for
 sizes and dimensions.