



# **FLEXX FLOW BELTING**

## **3/8" PITCH X .062" WIRE**

FLEXX FLOW BELTING is ideal for breading, cooking, battering, coating, or almost any processing application from freezing up to +500F. It has a wide range of uses in processing meat, poultry, seafood, baked goods, cereal, candy, and electronic P.C. board cleaning.

FLEXX FLOW BELTING is manufactured in Lancaster, PA, according to standard industry specifications and can be spliced directly into existing belts of this type.

FLEXX FLOW BELTING is easy to clean. The flow through design allows for unrestricted wash down and inspection.

FLEXX FLOW BELTING is light weight, easy to handle, and quick to install. Belt may be made endless without seams.

FLEXX FLOW BELTING is sprocket driven, providing positive drive and consistent tracking. Sprockets are available in various sizes to meet your needs.

FLEXX FLOW BELTING is designed to articulate around small diameter drive and tail rolls for tight transfers. This ensures gentle handling and constant positioning of the product.

---

**LUMSDEN FLEXX FLOW INC.**


P.O. BOX 4647 • LANCASTER, PENNSYLVANIA 17604 • (717) 394-6871 FAX (717) 394-1640  
**1-800-367-3664**

# FLEXX FLOW

## 3/8" PITCH X .062" WIRE

ACTUAL SIZE

SPACE BETWEEN WIRES .224"



WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH
2	1	1.437	16	7	2.205	30	13	2.264
2-1/8	1	1.563	17	5	3.729	32	11	2.858
2-3/8	1	1.812	17-5/8	7	2.437	32	13	2.418
3	1	2.437	18	7	2.491	32-7/8	13	2.486
3-7/8	1	3.312	18-1/8	9	1.951	33	13	2.495
4	1	3.437	18-1/2	7	2.562	33-1/4	13	2.514
5-1/2	3	1.646	19	7	2.634	33-5/8	13	2.543
6	3	1.812	20	7	2.777	34	13	2.572
6-5/16	3	1.916	20-1/4	7	2.813	34-5/8	13	2.620
7-1/4	3	2.229	21	7	2.920	35	13	2.649
7-3/8	3	2.271	21-1/8	7	2.795	36	13	2.726
7-1/2	3	2.312	21-7/8	7	3.044	36-1/4	13	2.745
8	3	2.479	22	7	3.062	38	13	2.880
8-1/4	3	2.562	22	9	2.382	38	15	2.496
9	3	2.812	22-1/2	9	2.437	40	15	2.629
9-1/2	3	2.979	22-5/8	7	3.152	40-7/8	17	2.371
10	3	3.146	23	7	3.205	41	15	2.696
10-1/4	3	3.229	23-1/2	9	2.549	42	15	2.762
11	5	2.088	24	9	2.604	42	17	2.437
11-1/2	5	2.188	24-1/8	9	2.618	48	17	2.790
12	5	2.288	24-1/2	9	2.660	50	19	2.602
13	5	2.488	26	9	2.826	54	17	3.143
14	5	2.688	26	11	2.312	54	21	2.545
14-1/4	5	2.738	27	11	2.403	60	21	2.830
14-3/8	5	2.763	27-1/2	11	2.449	63	21	2.973
14-3/4	5	2.838	28	11	2.494	72	23	3.106
15	5	2.888	29	11	2.585	99-7/8	39	2.546
16	5	3.088	30	11	2.676	105	41	2.547

All other widths, not listed here, are also available and can be ordered by width, specification or belt number.

**BELT WIDTH:** 2" to 14'

**WIDTH TOLERANCE:** +, -1/16 to 36"  
 +, -3/32 for 36" to 60"  
 +, -3/8 for 60" up

**MATERIALS:** 302 Stainless Steel  
 High Tensile Strength Wire.  
 .062" Diameter.

**BELT WEIGHT:** Approximately .56 lbs.  
 per sq. ft.

**BELT LENGTH:** Unlimited, except by  
 strength requirements.

**WIRES:** 42 Wires per linear foot

**SPEED:** 50 FPM recommended max. speed.

**SPROCKETS:** See sprocket literature for  
 sizes and dimensions.

