



3/8" PITCH X .082" WIRE

FLEXX FLOW BELTING is ideal for breaching, cooking, battering, coating, or almost any processing application from freezing up to +500F. It has a wide range of uses in processing meat, poultry, seafood, baked goods, cereal, candy, and electronic P.C. board cleaning.

FLEXX FLOW BELTING is manufactured in Lancaster, PA, according to standard industry specifications and can be spliced directly into existing belts of this type.

FLEXX FLOW BELTING is easy to clean. The flow through design allows for unrestricted wash down and inspection.

FLEXX FLOW BELTING is light weight, easy to handle, and quick to install. Belt may be made endless without seams.

FLEXX FLOW BELTING is sprocket driven, providing positive drive and consistent tracking. Sprockets are available in various sizes to meet your needs.

FLEXX FLOW BELTING is designed to articulate around small diameter drive and tail rolls for tight transfers. This ensures gentle handling and constant positioning of the product.

LUMSDEN FLEXX FLOW INC.

P.O. BOX 4647 • LANCASTER, PENNSYLVANIA 17604 • (717) 394-6871 FAX (717) 394-1640
1-800-367-3664

FLEXX FLOW

3/8" PITCH X .082" WIRE

ACTUAL SIZE

SPACE BETWEEN WIRES
.293/.299"



WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH	WIDTH INCHES	NO. OF SPACES	NOMINAL SPACE WIDTH
4"	1	3.375	19"	5	3.675	34"	11	3.034
6"	1	5.375	20"	7	2.767	34"	13	2.567
8"	3	2.458	21"	7	2.910	35 ¹ / ₄ "	13	2.663
9"	3	2.791	21"	5	4.075	35 ¹ / ₂ "	11	3.170
10"	3	3.125	22"	7	3.053	36"	13	2.721
11"	3	3.458	23 ¹ / ₂ "	7	3.267	39 ⁹ / ₁₆ "	13	2.995
12"	3	3.791	23 ⁵ / ₈ "	9	2.555	40"	15	2.625
12"	5	2.275	24"	7	3.339	40"	13	3.028
13"	3	4.125	25"	7	3.482	40 ⁵ / ₈ "	15	2.666
13"	5	2.475	28"	9	3.041	42"	13	3.182
14"	5	2.675	28"	11	2.488	48"	15	3.158
16"	5	3.075	29"	9	3.152	54"	17	3.139
16 ¹ / ₂ "	5	3.175	32"	9	3.486	64"	21	3.017
18"	5	3.475	33 ⁹ / ₁₆ "	11	2.994			

All other widths, not listed here, are also available and can be ordered by width, specification or belt number.

BELT WIDTH: 3" to 14'

WIDTH TOLERANCE: +, -1/16 to 36"
+, -3/32 for 36" to 60"
+, -3/8 for 60" up

MATERIALS: 302 Stainless Steel
High Tensile Strength Wire.
.082" Diameter.

BELT WEIGHT: Approximately .75 lbs.
per sq. ft.

BELT LENGTH: Unlimited, except by
strength requirements.

WIRES: 31¹/₂ to 32 Wires per linear foot

SPEED: 75 FPM recommended max. speed.

SPROCKETS: See sprocket literature for
sizes and dimensions.

