

Hydraulic Unit

The Makefast USA

Hydraulic rotary actuator is a versatile, compact, highly finished operating system ideal for use in powered Bimini systems, anchor handlers, bathing, or swim platforms and more.

Manufactured from highly polished 316 marine-grade stainless steel, it is supplied with a compact hydraulic powerpack which can be hidden within the boat's structure. These powerful units operate at the simple push of a button and are available in three sizes.



Contact Us

Makefast USA

3725 Payne Road, Preston,
Maryland 21655, United
States

sales@makefast-usa.com

[202 507 9011](tel:2025079011)



HYDRAULIC
UNIT



 MAKEFAST
USA

TECH SPECS

- + Manufactured from high-quality marine grade 316 Stainless Steel with a mirror polished finish.
- + Rotary movement up to 190 degrees.
- + All units are supplied with colour-coded hoses for ease of installation. These hoses can be supplied to the correct lengths to suit the customers application.
- + All hydraulic fittings and connections supplied.
- + Discreet & compact 12 or 24 volt hydraulic pump supplied enclosed in IP65 rated control box containing a safety override valve, manual release and operating audible warning sounder.
- + All systems are supplied fully built and cycle tested prior to despatch.
- + 2 year warranty period from date of dispatch (full details available on request)
- + Optional 3 year extended warranty available.



APPLICATIONS

BIMINI HYDRAULIC UNIT

Perfect for effortless opening and closing of large Bimini frames.
Available in three sizes to suit 1 ¼", 1 ½", and 2" tube.
Side mounted socket and inline yoke fitting available in all tube diameters.
Range of mounting options and accompanying hardware available.



ANCHOR HANDLER UNIT

The anchor and bow-roller mechanism mounts below deck in the anchor locker and effortlessly extends beyond the bow at the touch of a button. The anchor handler can be integrated easily into a fully automated anchor system.
The robust design can accommodate many different anchor types, the standard design is suitable for a 20KG Delta anchor.
The anchor is retained with a manually applied locking pin for user-safety



THESE POWERFUL UNITS OPERATE AT THE SIMPLE PUSH OF A BUTTON

BATHING/SWIM PLATFORM UNIT



Ideal for both aft bathing platforms and for smaller side swim doors. A locking solenoid pin is used to keep the platform or door secure in the vertical position when closed.

