


Airspace Class	Entry Requirement	Pilot Certificate or Rating	Two-Way Communication	Altitude Decoding Transponder	VFR Min. Visibility Below 10,000 MSL	VFR Min. Visibility 10,000 MSL and Above	VFR Cloud Clearance Below 10,000 MSL	VFR Cloud Clearance 10,000 MSL and Above
A	ATC Clearance	Instrument	Yes	Yes	N/A	N/A	N/A	N/A
B	ATC Clearance	Private Certificate or student with endorsement	Yes	Yes within 30 nm of the class B primary airport ¹	3 miles	3 miles	Clear of Clouds	Clear of Clouds
C	VFR: Radio Contact IFR: Clearance	Student Certificate	Yes	Yes within C space and above lateral limits of C space ¹	3 miles	3 miles	500 below 1,000 above 2,000 horizontal	500 below 1,000 above 2,000 horizontal
D	VFR: Radio Contact IFR: Clearance	Student Certificate	Yes	No unless required by other airspace	3 miles	3 miles	500 below 1,000 above 2,000 horizontal	500 below 1,000 above 2,000 horizontal
E	VFR: None IFR: Clearance	Student Certificate	IFR only	No unless required by other airspace	3 miles	5 miles	500 below 1,000 above 2,000 horizontal	1,000 below 1,000 above 1 mile horizontal
G	None	Student Certificate	No	No unless required by other airspace	Day: 1 mile Night: 3 miles	5 miles ²	500 below 1,000 above 2,000 horizontal } ²	1,000 below 1,000 above 1 mile horizontal } ²

¹ An altitude decoding transponder is required above 10,000 MSL.

² When flying 1,200 AGL or below: DAY: 1 mile visibility clear of clouds; NIGHT: 3 miles visibility, 500 below, 1,000 above, 2,000 horizontal.

U.S. Airspace Classes at a Glance



AGL - above ground level
FL - flight level
MSL - mean sea level

14 CFR Part 91.155

www.FAASafety.gov
Your Aviation Safety Web Site



U.S. Department of Transportation
Federal Aviation Administration