



- + Liquid cooling
- + Slim, compact, and stylish design
- + Reduced install cost
- + Increased reliability
- + Durable UV resistant exterior
- + Low maintenance
- + OCPP integration

RT50/50kW Specifications

OUR INNOVATION • YOUR FUTURE



SPECIFICATIONS

CONNECTORS	CHAdeMO and CCS (Type 1 or 2)
POWER	Up to 50kW
SUPPLY INPUT	380 - 480 V AC 3ø
SUPPLY FREQUENCY	50-60Hz
IP RATING	IP65
EFFICIENCY	>92%
POWER FACTOR	0.99
MAXIMUM OPERATING ALTITUDE	2000m (6560')
OPERATING TEMPERATURE	-35°C to 50°C (-31°F to 122°F)
STORAGE TEMPERATURE	-55°C to 80°C (-67°F to 176°F)
NETWORK CONNECTION	4G and Gigabit Ethernet
RFID	MIFARE ISO/IEC14443A/B, ISO/IEC15693, ISO/IEC18000-3, FeliCa, NFC, EMV 2.0
CREDIT CARD READER	Optional
COMMUNICATION PROTOCOL	OCPP 1.5 and 1.6J
WEIGHT	165kg (364 lb)
ELECTRICAL PROTECTION	Short circuit; Over voltage: RCD
DIMENSIONS	2000 (6'7") (H) x 750 (2'6") (W) x 330 (1'1") (D) mm
FREIGHT	24 units per 20' container
CERTIFICATION	CE, UL, CHAdeMO, RCM, FCC, IC



A U S T R A L I A • U S A • E U R O P E

tritium.com.au • enquiries@tritium.com.au

Worldwide +61 7 3147 8500 • 48 Miller Street, Murarrie, QLD 4172, Australia

USA +1 310 961 5299 • 20000 Vermont Avenue, Torrance, CA 90503, United States

Europe +31 202 250 100 • Luchtvaartstraat 3B, 1059 CA Amsterdam, Netherlands

Veefil® is a registered trademark of Tritium Pty Ltd. © 2020 Tritium Pty Ltd