

SIEMENS

Ingenuity for life



Energizing the
evolution of eMobility

VersiCharge AC series

[siemens.com/versicharge](https://www.siemens.com/versicharge)


No application left behind

VersiCharge is the perfect fit for wherever you need charging

The VersiCharge AC charger is perfect for various applications including workplaces, retail, parking garages, multi-residential, all public charging, and home charging.

No matter where you need charging, you'll enjoy many benefits and features, such as an easy-to-use mobile app, smart building integration, flexible communication connections, faster charging, smart load management OCPP and Modbus communication and much more.

Siemens VersiCharge AC chargers can be mounted to a wall or on a pedestal. The various accessories help you easily integrate it into any parking location.




Flexibility for the future

Smart building integration

VersiCharge AC chargers offer various communication interfaces for seamless integration to local and remote networks. An extensive Modbus implementation allows for direct communication with building management systems, such as Siemens Desigo for benefits like dynamic load management.





Modbus
Wi-Fi
Ethernet



Modular system configuration

Whether you are using the VersiCharge parent units just as a communications gateway or to execute more extensive local networking and control functions, the parent-child configuration options will help reduce investment and operational costs.

Flexible and elegant posts



Easy cloud integration



Wi-Fi, Ethernet, 4G, and UMTS



easy to use mobile app



Simple ID card identification

Setting the stage

Benefits designed for you



Smart building integration

- Monitoring and control through Siemens Designo and third-party systems
- Modbus TCP and RTU communication
- Smart load management and monitoring



Flexibility

- Modular and extend-able site configurations
- Various communication possibilities
- Wall or pole mounted



Robust and reliable

- Indoor and outdoor capable (IP56)
- Industry-leading safety features



State-of-the-art and Future-proof

- Tested EV interoperability
- Remote upgrade-ability
- Integrated MID metering



Intuitive design

- Smart interface and easy usability
- Quick setup using the mobile app for iPhone and Android
- Integrated upstream electrical protection



Integrity

- Cost-effective
- 3rd generation Versicharge AC Wallbox
- Quality made by Siemens



Making a difference

Key features

Compatibility with all common electric vehicles and applicable charging standards plus ease of use and comfort functions, such as delayed and planned charging, ensure a high degree of customer convenience.

Rugged housing suitable for outdoor applications (IP56 and IK10)

Status bar for information on identification, charging, and time delay

Integrated MID metering*

Status LEDs indicate system power, vehicle connection status, charging power, and fault indication

User authentication via RFID (Mifare classic, local whitelist and synching via OCPP)

Integrated 6 mA DC RCD protection provides installation cost savings

Amperage adjustment switch for five different current limit setting

Integrated high-performing dual band Wi-Fi

UMTS LTE / 4G connectivity for mobile network communication (parent units)

Status LEDs indicating connectivity, locked panel, and use of remote control

CE-certified for safety and interoperability

Touch-sensitive button for desired time delay and power level

Protective cover

Available with either a type 2 socket or a 7-m cable with a type 2 plug

RS485 Modbus RTU and Modbus TCP connections to building management system, for instance

*ERK compliant metering in development

More than charging

Experience the peace of mind

Siemens Versicharge Chargers have been standing for superior quality, ruggedness, and proven technology for more than a decade and have reliably provided millions of charges to electric vehicles (EVs). The new third-generation Versicharge AC series continues this tradition with numerous groundbreaking enhancements and is further supported by Siemens local and remote services.



Service Packages

We offer world-class services and support throughout the entire lifetime of your charging infrastructure, in this way assuring maximum uptime and the highest availability of your vehicles. Our cloud-based service packages Care and Care Plus look after your chargers using the dedicated Siemens service backend.

Care

The basic Care package is included during the warranty period and can be extended by subscription.

It ensures that firmware updates keep your chargers up to date as eMobility continues to evolve. Remote analyses and diagnostics are performed by our support center on demand.

Care Plus *

Enjoy all Care digital services and even more with our Care Plus package. Your charger will be pro-actively monitored and analyzed by our operation center. Firmware updates will be delivered with priority.

* coming soon

VersiCharge AC wallbox – technical data

| Features and functions | |
|-----------------------------|---|
| Charging mode | Mode 3 |
| Vehicle connection | Type 2 socket, 32 A or 7-m cable with type 2/32 A plug |
| AC power output | Single phase: up to 7.4 kW or three-phase: up to 22 kW |
| Environment | Indoor and outdoor |
| Mounting options | Wall- and pole-mounting |
| Touch button | Time delay, return to max. power level |
| Charging status LEDs | Powered up, time delay, charging state, reduced power level, authentication |
| Communication / status LEDs | Connected / not connected during operation / signal strength during commissioning |
| Parent / child | Up to 9 child units per parent unit for combined communication to back-end |
| Load management | via OCPP or Modbus independently |
| Communication | |
| Interfaces | Ethernet, Wi-Fi, Modbus RS-485, Modbus TCP/IP, for parent units additionally GSM, LTE, 4G |
| User authentication | RFID card (local white-list, MiFare) |
| Configuration | via VersiCharge mobile app or VersiCharge PC Tool |
| Backend protocol | OCPP 1.6, upgradeable to OCPP 2.0.1 (available in 2022) |
| Software upgrade | Remote update possible |
| Electrical design | |
| Power supply voltage | Single phase: 230 V / 7,2 kW, three-phase: 400 V / 22 kW; 50/60 Hz. |
| Rated current settings | 10 / 13 / 16 / 20 / 32 A |
| Cross wire section | Single phase: 10 mm ² , three-phase: up to 10 mm ² |
| Network Type | TT / TN, for single phase units additionally IT |
| Energy metering | integrated MID metering |
| AC ground fault detection | 30 mA AC |
| DC leakage detection | ≤6 mA DC |
| RCCB/ FI | not integrated |
| Voltage protection | integrated |
| Over-current protection | Current +10% above configured threshold, min. +2 A / 5 seconds |
| Operating altitude | 2,000 m |
| General design | |
| IP and IK rating | IP 56, IK10 |
| Dimensions (HxWxD) | 446 mm x 180 mm x 158 mm |
| Weight | cable: 1~ 5,3kg; 3~ 7.2kg / socket: 1~ 2.9kg; 3~ 5.0kg |
| Ambient conditions | Operating temperature: -30°C - +50°C, storage temp.: -40°C - +60°C, 98% non condensing |
| Colors | Silver metallic (Pantone 10077), Black |
| Certificates and standards | |
| Certifications | CE |
| Standards | EN IEC 61851-1, EN IEC 61851-21-2, EN IEC 60068-2-52, EN IEC 61000-6-1, EN 61000-6-3, EN IEC 61000-6-4, EN 330 330, EN 300 328, EN 301 511, EN 301 893, IEC 62955 |

| IEC variants | | | Parent | Child |
|--------------|--------|------------------|--------------------|--------------------|
| Single phase | Cable | without SIM card | 8EM1310-2EJ04-3GA1 | 8EM1310-2EJ04-0GA0 |
| | | with SIM card | 8EM1310-2EJ04-3GA2 | |
| | Socket | without SIM card | 8EM1310-2EH04-3GA1 | 8EM1310-2EH04-0GA0 |
| | | with SIM card | 8EM1310-2EH04-3GA2 | |
| Three-phase | Cable | without SIM card | 8EM1310-3EJ04-3GA1 | 8EM1310-3EJ04-0GA0 |
| | | with SIM card | 8EM1310-3EJ04-3GA2 | |
| | Socket | without SIM card | 8EM1310-3EH04-3GA1 | 8EM1310-3EH04-0GA0 |
| | | with SIM card | 8EM1310-3EH04-3GA2 | |

Published by
Siemens AG
Smart Infrastructure
Distribution Systems
Mozartstrasse 31C
91052 Erlangen, Germany

For the U.S. published by
Siemens Industry Inc.
100 Technology Drive
Alpharetta, GA 30005, United States

For more information, please contact
our Customer Support Center.
Phone: +49 180 524 70 00
Fax: +49 180 524 24 71
(Charges depending on provider)
E-mail: support.energy@siemens.com

Article No. SIDS-B10056-00-7600
Dispo 06200
fb 8780 WS 1220

© Siemens 2020

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

