
45mm Roller Shutter (Residential)







TECHNICAL SPECIFICATIONS

PU	Polyurethane (Dow)	
Max. Surface Area	7M ²	
Weight/M²	2.8Kg	
Number of Slats/M ²	22	
Axle Types	60mm Octagonal Steel or Aluminium	
Bottom Bar Dimensions	55mm x 8.5mm	
Guide Dimensions	53mm x 22mm	
	(68mm x 22mm x 14mm Guide Upgrade available at additional cost)	
Maximum Width	3200mm	
Maximum Height	2600mm	



SUITABLE APPLICATIONS

- * Domestic Windows & Door ways
- * Counter Tops

FEATURES

- * High quality aluminium alloy construction.
- * Foam filled slat for additional strength and silent operation.
- * High quality painted finish.
- * Smooth and curved face slat.
- * Roll tight design.
- * High quality internal sealed bearings.
- * Suitable for widths up to 3200mm.
- * Can be manually operated or motorised.
- * Made In Australia.

COLOURS OPTIONS

Colour	Name Of Colour
	Cream
	Clear Beige
	White
	Shale Grey
	Black
	Monument
	Green
	Red
	Brown
	Woodland Grey



45mm Roller Shutter (Residential)

PELMET SIZES & MAXIMUM SHUTTER HEIGHT

Pelmet Box Size	Max. No. of Slats	Max. Shutter Height	Axle Size
150mm	27	1300mm	60mm
165mm	36	1700mm	60mm
180mm	47	2200mm	60mm
205mm	69	3200mm	60mm
230mm	92	4200mm	60mm
250mm	116	5300mm	60mm
300mm	176	8000mm	60mm

CONTROL OPTIONS

Manual Options



Strap Winder (Up To 15Kg)



Cord Winder (Up To 15Kg)



Steel Cable Winder (Up To 50Kg)



Strap Coiler (Up To 10Kg)



Cord Coiler (Up To 10Kg)



Spring Loaded With Key Lock

Motorised Options



Wall Switch With 240V Electric Motor



Remote Control Hand Held or Key Ring



DC 12V Battery Controller With 12V Motor



DC 24V UPS Power Bank Controller With 24V Motor



Key Switch With 240V Electric Motor



Crank Handle With 240V Electric Manual Override Motor



