50mm PC CRYSTALVIEW SHUTTERS®





TECHNICAL SPECIFICATIONS

Max. Surface Area	10M²	
Weight/M²	5.2Kg	
Number of Slats/M ²	14.3 (combined aluminium & Polycarbonate slats)	
Axle Types	70mm Octagonal Steel or	
	90mm, 101 Steel Round Tube and	
	(130mm with adaptor)	
Bottom Bar Dimensions	55mm x 8.5mm	
Guide Dimensions	68mm x 25mm x 14mm	
	(Heavy Duty Guide)	
Profile Extruded Slat	33mm x 9.3mm (Aluminium)	
Maximum Width	4400mm	
Maximum Height	3000mm	

SUITABLE APPLICATIONS

- * Restaurants & Cafes.
- * Counter Tops.
- * Garage Doors.
- * Alfresco and Patio Enclosures.
- * Commercial Shop Fronts, Pubs, Clubs and Hotels

FEATURES

- * High quality aluminium alloy and polycarbonate Construction.
- * Commercial grade double wall extruded profile for heavy duty strength.
- * High quality painted finish.
- * UV resistant 50mm polycarbonate profile.
- * Roll tight design.
- * Heavy duty steel axle with high quality sealed Bearing.
- * Suitable for widths up to 5800mm.
- * Can be manually operated or motorised.
- * Made In Australia.

COLOURS OPTIONS

Colour	Name Of Colour
	Cream
	Clear Beige
	White
	Shale Grey
	Black
	Monument
	Woodland Grey





50mm PC CRYSTALVIEW SHUTTERS®

PELMET SIZES & MAXIMUM SHUTTER HEIGHT

Pelmet Box Size	Max. No. of Slats	Max. Shutter Height	Axle Size
150mm	15	1110mm	70mm
165mm	21	1530mm	70mm
180mm	27	1950mm	70mm
205mm	39	2790mm	70mm
230mm	52	3700mm	70mm
250mm	65	4610mm	70mm
300mm	97	6850mm	70mm

Pelmet Box Size	Max. No. of Slats	Max. Shutter Height	Axle Size
230 mm	47	3350mm	90mm
250mm	56	3980mm	90mm
300mm	90	6360mm	90mm


Pelmet Box Size	Max. No. of Slats	Max. Shutter Height	Axle Size
230 mm	44	3140mm	101mm
250mm	60	4260mm	101mm
300mm	93	6570mm	101mm

Pelmet Box Max. Shutter **Axle Size** Height 230 mm 38 2720mm 130mm 250mm 49 3510mm 130mm 300mm 82 5800mm 130mm

CONTROL OPTIONS

Manual Options







Spring Loaded With Key Lock

Motorised Options



Wall Switch With 240V Electric Motor



Remote Control Hand Held or Key Ring



DC 12V Battery Controller With 12V Motor



DC 24V UPS Power Bank Controller With 24V Motor



Key Switch With 240V Electric Motor



Crank Handle With 240V Electric Manual Override Motor



