



LADDERS

Integrated Water Services, Inc.
(the Company)



Purpose

The purpose of the program is to prescribe rules and establish minimum requirements for the construction, care, and use of the common types of ladders.

Scope

This program is applicable to all employees of the Company.

When work is performed by a subcontractor on a company site, the contractor's written safety program shall take precedence for their employees. However, subcontractors may adopt this procedure for their use.

Definitions

Ladder: an appliance usually consisting of two side rails joined at regular intervals by cross- pieces called steps, rungs, or cleats, on which a person may step in ascending or descending.

Stepladder: a self-supporting portable ladder, nonadjustable in length, having flat steps and a hinged back. Its size is designated by the overall length of the ladder measured along the front edge of the side rails.

Single ladder: a non-self-supporting portable ladder, nonadjustable in length, consisting of only one section. The overall length of the side rail designates its size.

Extension ladder: a non-self-supporting portable ladder adjustable in length. It consists of two or more sections traveling in guides or brackets so arranged as to permit length adjustment. Its size is designated by the sum of the lengths of the sections measured along the side rails.

Fixed ladder: a ladder permanently attached to a structure, building, or equipment.

Individual-rung ladder: a fixed ladder each rung of which is individually attached to a structure, building, or equipment.

Cage: a guard that may be referred to as a cage or basket guard, which is an enclosure that is fastened to the side rails of the fixed ladder or to the structure to encircle the climbing space of the ladder for the safety of the person who must climb the ladder.

Key Responsibilities

Managers and Supervisors

- Superintendents are responsible for ensuring that all employees have been trained in the use and inspection of ladders in accordance with the manufacture's guidelines.
- Superintendents are responsible for ensuring that all employees and subcontractors are aware that if an inspection discovers a defect, the ladder shall be taken out of service and repaired or discarded.



Employees and Subcontractors

- Employees and sub subcontractors shall inspect ladders prior to each use to ensure the proper safe working condition of the ladder.
- Employees and subcontractors are responsible for following this program and reporting any damage or repairs that may be needed to their supervisor.

Procedure

Inspection, Care and Safe Work Practices of Ladders

Inspection

- Ladders shall be inspected for visible defects on a periodic basis and after any occurrence that could affect their safe use.
- Ladders used by Integrated Water Services employees and/or subcontractors must meet OSHA/ANSI specifications.
- Ladder rungs, cleats, and steps shall be parallel, level, and uniformly spaced when the ladder is in position for use.
- Portable and fixed ladders with structural defects such as but not limited to broken or missing rungs, cleats, or steps, broken or split rails, corroded components, or other faulty or defective components shall either be immediately marked in a manner that readily identifies them as defective or be tagged with "Do Not Use" or similar language, or they shall be withdrawn from service and discarded or repaired.
- If a ladder is tipped over, it shall be inspected by a competent person for side rail dents or bends, or excessively dented rungs- check all rung to side rail connections, check hardware connections and check rivets for shears.
- All wood parts shall be free from sharp edges and splinters and not painted.

Care

- Ladders shall always be maintained in good condition, the joint between the steps and side rails shall be tight, all hardware and fittings shall be securely attached, and the movable parts shall operate freely without binding or undue play.
- Metal bearings of locks, wheels, pulleys, etc., shall be frequently lubricated.
- Frayed or badly worn rope shall be replaced. Safety feet and other auxiliary equipment shall be kept in good condition to ensure proper performance.
- Rungs shall be kept free of grease and oil.

How to Safely Use Ladders

- Ladders shall be used only for the intended purpose for which they were designed. Never use ladder in a horizontal position or as scaffolding and do not place ladders on top of boxes, barrels, crates, etc.
- The ladder shall be secured at the top or held by another person at the base.
- The footing of the ladder shall be placed on a stable and level surface.
- Extension ladders should be placed against the top support at a 4:1 incline. Ladders shall be used at an angle such that the horizontal distance from the top support to the foot of the ladder is approximately one-quarter of the working length of the ladder. (The distance along the ladder between the foot and the top support.)



- When ladders are not able to be extended, the ladder shall be secured at its top to a rigid support that will not deflect.
- Ladders shall not be used in a horizontal position as platforms, runways, or scaffolds.
- Ladders shall not be used by more than one person at a time.
- Ladders shall not be placed in front of doors opening toward the ladder unless the door is blocked open, locked, or guarded.
- If a ladder is used in a high traffic area, barricades shall be placed to avoid accidental displacement due to collisions.
- Do not stand on the top two rungs of a vertical ladder.
- Always follow manufacturer instructions.

On two-section extension ladders the minimum overlap for the two sections in use shall be as follows:

Size of Ladder (feet)	Overlap (feet)
Up to and including 36'	3
Over 36 up to and including 48'	4
Over 48 up to and including 60'	5

- The upper supports of ladders used to access elevated work areas must extend a minimum of 3 feet above the elevated surface. When ladders are not able to be extended then the ladder shall be secured at its top to a rigid support that will not deflect.
- The ladder side rails shall extend at least 3 feet (.9m) above the upper landing surface. When ladders are not able to be extended then the ladder shall be secured at its top to a rigid support that will not deflect.
- The employee or subcontractors shall always maintain a three (3)-point grip on the ladder and carry tools/equipment on a belt or hoist up. Workers traversing ladders should not carry anything in their hands that could cause injury in case of fall.
- The employee or subcontractors shall face the ladder while ascending or descending.
- The bracing on the back legs of step ladders is designed solely for increasing stability and not for climbing.
- The ladder shall not be moved while occupied.

Portable Ladders

Stepladders shall not be longer than 20 feet. Single ladders shall not be longer than 30 feet. Two-section extension ladders shall not be longer than 60 feet. All ladders of this type shall consist of two sections, one to fit within the side rails of the other and arranged in such a manner that the upper section can be raised and lowered.

Keep all ladders at least ten (10) feet away from power lines.

Ladders shall not be loaded beyond the maximum intended load for which they were built, nor beyond the manufacturer's rated capacity.

Weight includes the combined weight of the climber and his tools and equipment. Ladders are rated as the following:

- I (holds 250 lbs)
- I-A (holds 300 lbs)
- II (holds 225 lbs)
- III (holds 200 lbs)

**Fixed Metal Ladders**

Ladders shall be constructed to withstand a minimum of 200 pounds.

All metal rungs shall have a minimum diameter of $\frac{3}{4}$ inches and wooden rungs shall have a minimum diameter of $1\frac{1}{8}$ inches.

Rungs shall not be more than 12 inches apart and shall be uniform throughout the length of the ladder.

Rungs shall be a minimum length of 16 inches and provide protection that prevents the climber's foot from slipping off the end.

Rungs shall have a minimum of 7 inches between themselves and the structure behind it.

A fall restraint system must be provided for all fixed ladders greater than six feet in height.

- A Cage is required when the fixed ladder is twenty feet or greater.
- Cages on fixed ladders shall not begin at a point less than 7 feet nor greater than 8 feet from the walking surface below the cage.
- Cages shall provide a clear width of 15 inches in each direction of the rung's centerline.
- Cages shall not extend less than 27 inches, but not greater than 28 inches from the centerline of the rung.
- A climbing fall restraint system may be substituted for a ladder cage.