



Hot Work Permit

Date:	Time:
Location:	Job #
Issuing Supt:	Issued to:

Procedures

Flammable material removed? Yes or No	Lockout/Tagout Required? Yes or No or N/A
De-Pressurized? Yes or No	Will this work produce a toxic gas? Yes or No
Confined Space Permit Required? Yes or No	Ventilation required? Yes or No
Electrical hot work required? Yes or No	Water, liquids, or gases removed? Yes or No or N/A

Atmospheric Monitoring Information

Gas Monitor Make:	Serial Number:
Calibrated date:	Person testing:

Gas monitor readings must remain at or below these levels:

Oxygen 19.5% to 23.5%	LEL 0 to less than 10%
Carbon Monoxide 0 to less than 35% PPM	H ₂ S 0 to less than 10 PPM
California Carbon Monoxide to less than 25% PPM	

Monitor readings to be recorded initially and updated every 2 hours after.

Time	Oxygen	LEL	CO	H ₂ S	Other

Safety Equipment Required.

ABC Fire extinguisher 20 or 30 lbs.	Fire Watch required
Face Shield	Welding Hood
Leather Welding Gloves/Sleeves	Cutting Goggles
Arc Flash Protection (Electrical Hot Work)	Proper PPE

Employee or Sub-Contractor Employee Names.

Fire Watch:	Fire Watch:

Fire watch must remain in place, may be relieved by another trained fire watchman for breaks, or lunch but fire watch must be always maintained when hot work is going on. Fire watch required until 30 minutes after the last hot work is completed.

Was work completed? Yes or No	Was work STOPPED? Yes or No
Why?	Was it resolved?
Issuing Supt.	End Time:

This permit is void if the atmosphere is not safe for Hot Work. Valid for 1 shift only.