



Revision Date: 11/06/2006 Issue date: 11/06/2006

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: 56531 Product type: Anaerobic Sealant Region: **United States**

Company address: **Contact Information:** Henkel Corporation Telephone: 860.571.5100 1001 Trout Brook Crossing

Emergency telephone: 860.571.5100

Rocky Hill, Connecticut 06067 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Polyglycol dimethacrylate 25852-47-5	<u>%</u> 30-60	ACGIH TLV None	OSHA PEL None	OTHER None
Cellulose ester 9004-36-8	10-30	None	None	None
Poly(tetrafluoroethylene) 9002-84-0	5-10	None	None	AEL (DuPont): 10 mg/m³, 8 Hr TWA, total dust; 5mg/m³, 8 hr. TWA respirable dust
Titanium dioxide 13463-67-7	1-5	10 mg/m ³ TWA	15 mg/m³ TWA total dust	•
Treated fumed silica 67762-90-7	1-5	10mg/m³ Inhalable fraction, 3mg/m³ Respirable fraction, TWA	5mg/m³ Respirable dust, 15mg/m³ Total dust	None
Saccharin 81-07-2	1-5	None None	None	None
Cumene hydroperoxide 80-15-9	1-5	None	None	1 ppm (6 mg/m³) Skin (WEEL), 1ppm, skin TWA, (WEEL)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: **HEALTH:** 2* Paste Color: White FLAMMABILITY: 1 Odor: Mild PHYSICAL HAZARD: Personal Protection: See Section 8

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

May cause skin irritation. May cause allergic skin reaction. Skin contact:

Eye contact: Contact with eyes will cause irritation.

Item No. : Product name: 565 Thread Sealant PST® Pipe Sealant with PTFE **Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Toxic fluorine compounds. Irritating organic

vapors.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing.

Storage: For safe storage, store at or below 38°C (100°F).

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be required if concentrations

exceed occupational exposure limts.

Item No. : 56531 Product name: 565 Thread Sealant PST® Pipe Sealant with PTFE

Respiratory protection: Use a NIOSH approved air purifying respirator with an organic vapor cartridge if the potential to exceed

established exposure limits exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene,

Butyl-rubber, or nitrile-rubber gloves.

Eye/face protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: White
Odor: Mild

Vapor pressure: Less than 5 mm Hg at 27°C (80°F)

pH: Not applicable

Boiling point/range: Greater than 149°C (300°F)

Melting point/range:Not availableSpecific gravity:1.1Vapor density:Not availableEvaporation rate:Not available

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available
Not available

VOC content: 0.111%; 1.0595 grams/liter

10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Toxic fluorine compounds. Irritating organic

vapors.

Incompatability: Strong oxidizers.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatability" (Section 10).

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Acute oral LD50 greater than 5000mg/kg (rat)(estimated). Acute dermal LD50 greater than 2000 mg/kg

(rabbit) (estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dimethacrylate 25852-47-5	No	No	No
Cellulose ester 9004-36-8	No	No	No
Poly(tetrafluoroethylene) 9002-84-0	No	No	No
Titanium dioxide 13463-67-7	No	Group 2B	Yes
Treated fumed silica 67762-90-7	No	No	No
Saccharin 81-07-2	No	No	No
Cumene hydroperoxide 80-15-9	No	No	No

Literature Referenced Target Organ & Other Health Effects

Item No.: 56531 Product name: 565 Thread Sealant PST® Pipe Sealant with PTFE

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate 25852-47-5	Allergen, Irritant
Cellulose ester 9004-36-8	No Target Organs
Poly(tetrafluoroethylene) 9002-84-0	No Target Organs
Titanium dioxide 13463-67-7	Irritant, Respiratory
Treated fumed silica 67762-90-7	Irritant
Saccharin 81-07-2	No Target Organs
Cumene hydroperoxide 80-15-9	Allergen, Central nervous system, Corrosive, Irritant, Mutagen

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: 4-Methoxyphenol (150-76-5).

CERCLA/SARA Section 302 EHS: None above reporting de minimus.

CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313

of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene

hydroperoxide (CAS# 80-15-9) .

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or

other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 8

Prepared by: Kyra Kozak Woods, Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.