



# Material Safety Data Sheet

Sikadur® 32 Hi-Mod - Part A

## 1. Product and company identification

**Product name** : Sikadur® 32 Hi-Mod - Part A  
**Supplier** : Sika Corporation, Construction  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikausa.com  
**Telephone no.** : (201) 933 - 8800  
**Fax no.** : (201) 804 - 1076  
**In case of emergency** : CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887  
**Manufacturer** : Sika Corporation, Operations  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikausa.com  
**Telephone no.** : (201) 933 - 8800  
**Validation date** : **5. November 2012.**  
**Print date** : 5. November 2012.  
**Product type** : Liquid.

## 2. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Aromatic Hydrocarbon Blend	Trade Secret	
Modified Epoxy Resin	Trade Secret	
Nonyl Phenol	84852-15-3	

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 3. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Potential acute health effects

**Inhalation** : May cause respiratory tract irritation.  
**Ingestion** : Maybe Harmful if swallowed.  
**Skin** : May cause skin irritation. May cause sensitization by skin contact.  
**Eyes** : Irritating to eyes.

See toxicological information (Section 11)

## 4. First aid measures

**Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. Check for and remove any contact lenses. Get medical attention.  
**Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

## 4 . First aid measures

- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Maintain an open airway. In the event of any complaints or symptoms, avoid further exposure.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Never give anything by mouth to an unconscious person.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: >104.4°C (>219.9°F)
- Color** : Straw.
- Odor** : Aromatic.
- Density** : ~1.14 g/cm<sup>3</sup>
- VOC** : 35 g/l (A+B Combined)

## 10 . Stability and reactivity

- Stability** : The product is stable.
- Conditions to avoid** : Avoid exposure - obtain special instructions before use. Do not swallow.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Hazardous polymerization may occur under certain conditions of storage or use. Exotherm when curing in mass

## 11 . Toxicological information

### Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure.
- Acute toxicity**
- Conclusion/Summary** : Not available.

## 12 . Ecological information

- Environmental effects** : No known significant effects or critical hazards.

## 13 . Disposal considerations

- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Additional information
<b>DOT Classification</b>	Not regulated.		-	-	-
<b>TDG Classification</b>	Not regulated.		-	-	-
<b>ADR/RID Class</b>	Not regulated.		-	-	-
<b>IMDG Class</b>	Not regulated.		-	-	-

## 14 . Transport information

<b>IATA-DGR Class</b>	Not regulated.	-	-	-
-----------------------	----------------	---	---	---

PG\* : Packing group

## 15 . Regulatory information

- U.S. Federal regulations** : **United States inventory (TSCA 8b)**: All components are listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances**: No products were found.  
**SARA 302/304 emergency planning and notification**: No products were found.  
**SARA 302/304/311/312 hazardous chemicals**: nonylphenol  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification**:  
nonylphenol: Immediate (acute) health hazard  
**Clean Water Act (CWA) 307**: phenol; solvent naphtha (petroleum), heavy arom.; naphthalene  
**Clean Water Act (CWA) 311**: phenol; solvent naphtha (petroleum), heavy arom.; naphthalene  
**Clean Air Act (CAA) 112 accidental release prevention**: epichlorhydrin  
**Clean Air Act (CAA) 112 regulated flammable substances**: No products were found.  
**Clean Air Act (CAA) 112 regulated toxic substances**: epichlorhydrin

### SARA 313

#### Form R - Reporting requirements

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

- |   | <u>Product name</u> | <u>CAS number</u> | <u>Concentration</u>  |
|---|---------------------|-------------------|---|
| <b>State regulations</b>                      |                     |                   |   |
| <b>Massachusetts Substances:</b>              |                     |                   | The following components are listed:<br>NONYLPHENOL                 |
| <b>New Jersey Hazardous Substances:</b>       |                     |                   | The following components are listed:<br>ALKYL PHENOL, n.o.s.        |
| <b>New York Acutely Hazardous Substances:</b> |                     |                   | The following components are listed:<br>Naphthalene                 |
| <b>Pennsylvania RTK Hazardous Substances:</b> |                     |                   | The following components are listed:<br>PHENOL, NONYL-; NAPHTHALENE |

- United States inventory (TSCA 8b)** : All components are listed or exempted.

## 16 . Other information

### Hazardous Material Information System (U.S.A.) :

Health	2
Flammability	1
Physical hazards	0
Personal Protection Equipment	C

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

## 16 . Other information

The customer is responsible for determining the PPE code for this material.

**Date of printing** : 05.11.2012.

**Date of issue** : 05.11.2012.

**Date of previous issue** : 05.11.2012.

**Version** : 1.05

✔ Indicates information that has changed from previously issued version.

### Notice to reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.



# Material Safety Data Sheet

Sikadur 32 Hi Mod - Part B

## 1. Product and company identification

**Product name** : Sikadur 32 Hi Mod - Part B  
**Supplier** : Sika Corporation, Construction  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikausa.com  
**Telephone no.** : (201) 933 - 8800  
**Fax no.** : (201) 804 - 1076  
**In case of emergency** : CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887  
**Manufacturer** : Sika Corporation, Operations  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikausa.com  
**Telephone no.** : (201) 933 - 8800  
**Validation date** : **5. November 2012.**  
**Print date** : 5. November 2012.  
**Product type** : Liquid.

## 2. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Aromatic Hydrocarbon Blend	Mixture	
Benzyl Alcohol	100-51-6	
Nonylphenol	84852-15-3	
Proprietary blend of aliphatic and cycloaliphatic amines	Trade Secret	
Silica, quartz	14808-60-7	

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 3. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Potential acute health effects

**Inhalation** : Irritating to respiratory system.  
**Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.  
**Skin** : Corrosive to the skin. May cause sensitization by skin contact.  
**Eyes** : Corrosive to eyes. Causes irreversible damage to eyes.

See toxicological information (Section 11)

## 4. First aid measures

**Eye contact** : Get medical attention immediately. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician. Immediately flush eyes with plenty of water for at least 15 minutes.

**Skin contact** : Get medical attention immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

## 4 . First aid measures

- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## 5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.



## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### Product name

Quartz (SiO<sub>2</sub>)

### Exposure limits

**OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO<sub>2</sub>+2)**

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Respirable

**OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO<sub>2</sub>+5)**

TWA: 250 mppcf 8 hour(s). Form: Respirable

**OSHA PEL 1989 (United States, 3/1989). Notes: as quartz**

TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hour(s). Form: Respirable dust

**ACGIH TLV (United States, 1/2011).**

TWA: 0.025 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction

**NIOSH REL (United States, 6/2009).**

TWA: 0.05 mg/m<sup>3</sup> 10 hour(s). Form: respirable dust

**OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO<sub>2</sub>+2)**

TWA: 30 mg/m<sup>3</sup> 8 hour(s). Form: Total dust.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## 8 . Exposure controls/personal protection

- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: >104.4°C (>219.9°F)
- Color** : Gray.
- Odor** : Amine-like.
- Density** : ~1.7 g/cm<sup>3</sup> [20°C (68°F)]
- VOC** : 35 g/l (A+B Combined)

## 10 . Stability and reactivity

- Stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11 . Toxicological information

### Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
- Developmental effects** : Contains material which can cause developmental abnormalities.
- Fertility effects** : Contains material which may impair female fertility, based on animal data.

### Acute toxicity

- Conclusion/Summary** : Not available.

### Carcinogenicity

### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Quartz (SiO <sub>2</sub> )	-		-	+	Proven.	-

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Additional information
<b>DOT Classification</b>	UN3267	Corrosive liquid, basic, organic, n.o.s. (aliphatic and cycloaliphatic amines)	8	III	-
<b>TDG Classification</b>	UN3267	Corrosive liquid, basic, organic, n.o.s. (aliphatic and cycloaliphatic amines)	8	III	-
<b>ADR/RID Class</b>	UN3267	Corrosive liquid, basic, organic, n.o.s. (aliphatic and cycloaliphatic amines)	8	III	-
<b>IMDG Class</b>	UN3267	Corrosive liquid, basic, organic, n.o.s. (aliphatic and cycloaliphatic amines)	8	III	<b>Emergency schedules (EmS)</b> F-A, S-B
<b>IATA-DGR Class</b>	UN3267	Corrosive liquid, basic, organic, n.o.s. (aliphatic and cycloaliphatic amines)	8	III	-

PG\* : Packing group

## 15 . Regulatory information

**U.S. Federal regulations** : **United States inventory (TSCA 8b)**: All components are listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances**: No products were found.  
**SARA 302/304 emergency planning and notification**: No products were found.  
**SARA 302/304/311/312 hazardous chemicals**: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 4-tert-butylphenol; benzyl alcohol; calcium carbonate; Quartz (SiO<sub>2</sub>)  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification**: Immediate (acute) health hazard Delayed (chronic) health hazard  
**Clean Water Act (CWA) 307**: 2-methylnaphthalene; 1-methylnaphthalene; naphthalene  
**Clean Water Act (CWA) 311**: naphthalene  
**Clean Air Act (CAA) 112 accidental release prevention**: No products were found.

## 15 . Regulatory information

<b>State regulations</b>	<b>: Massachusetts Substances:</b>	The following components are listed: BENZYL ALCOHOL
	<b>New Jersey Hazardous Substances:</b>	The following components are listed: SILICA, QUARTZ; QUARTZ (SiO <sub>2</sub> ); TITANIUM DIOXIDE; TITANIUM OXIDE (TiO <sub>2</sub> ); 2-METHYL NAPHTHALENE; NAPHTHALENE, 2- METHYL-; NAPHTHALENE; MOTH FLAKES; ISOPHORONEDIAMINE; CYCLOHEXANEMETHANAMINE, 5- AMINO-1,3,3-TRIMETHYL-
	<b>New York Acutely Hazardous Substances:</b>	The following components are listed: Naphthalene
	<b>Pennsylvania RTK Hazardous Substances:</b>	The following components are listed: QUARTZ (SiO <sub>2</sub> ); TITANIUM OXIDE (TiO <sub>2</sub> ); BENZENEMETHANOL; PARTICULATE POLYCYCLIC AROMATIC HYDROCARBONS; NAPHTHALENE

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

## 16 . Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	3
Flammability		1
Physical hazards		0
Personal Protection Equipment		D

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**Date of printing** : 05.11.2012.  
**Date of issue** : 05.11.2012.  
**Date of previous issue** : No previous validation.  
**Version** : 1

✓ Indicates information that has changed from previously issued version.

Notice to reader

## **16 . Other information**

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.