



STRIPE UPRIGHT MARKING PAINT

Fast drying overhead marking paint that is permanent, lead free, and VOC compliant. The can may be sprayed by hand without removing the cap, or you could use it with the Z-606 Marking Wand or the Z-605 Marking Gun.

Suggested Uses:

Mines
Construction sites
Mark pipes
Mark ductwork

Packaging:

| | |
|--------------------------|--------------------------------------|
| Cans per case | 12 |
| Shipping weight per case | 20 lbs. |
| Container | 20 fluid ounce can |
| Label weight | 17 ounces (469 grams) |
| Shipping Classification | Consumer Commodity ORM-D, UN 1950 |
| Hazard Class | 2.1 |

Properties:

| | |
|-------------------------|----------------------------|
| Flammability | "Flammable" |
| Flash point | -4F |
| Specific Gravity | 0.83 |
| Solids Content | ~27% |
| VOC content | ~49%, cannot exceed 60% |
| MIR value | ~0.62, cannot exceed 1.20 |
| HAPs content | 0 |
| Storage Temperature | 40-100F |
| Application Temperature | 50-90F |
| Durability | Good |
| Abrasion Resistance | Good |
| Resin System | V.T. Alkyd |
| Shelf life | Guaranteed for 2 years |
| Freeze/Thaw | Up to 7 times without harm |

Dry Time*:

To touch 15 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60° gloss meter

Available Colors:

| Part # | Description | UPC Code |
|---------|----------------------|---------------|
| 20-1752 | White | 043281005418 |
| 20-1754 | Fluorescent Red | 043281005425 |
| 20-1757 | Fluorescent Orange | 043281001250 |
| 20-1767 | Hi Visibility Yellow | 04328100_____ |
| 20-1768 | Fluorescent Green | 043281005432 |