



## **2020 - Mud Cat MC 115D Hydraulic Dredge**

*186 hours still within the break in period.*

*Call For Pricing*

*(651)755-6542*

Positioning boom w/ 15 ft. (4.6 M) Digging depth Heavy duty steel hull

**SolidsMaster®:** Hydraulic sand & silt cutterhead w/replaceable teeth

8 in. (203mm) hydraulically driven, submersible dredge pump constructed of HARDOX steel closed face impeller 125 HP (93 Kw) John Deere diesel / hydraulic power unit with top shroud,

Hydraulic windlass cable system, Hydraulic oil for start-up, Operator's chair with oversized analog gauges mounted in an IP 55 outdoor enclosure, Digital depth gauge

**Dual 25HP Yamaha Outboards** w/throttle control Self-Propulsion System electric start & Trim

**Safety Package:** 1 life vests, 1 life ring, 1 fire extinguisher

**Manuals Package:** 1 Operations & Maintenance manuals and 1 engine manuals

Hand tool kit and tool box, Pump Defender™ (patent pending) self-cleaning debris guard for up to 80% downtime reduction Canopy for operator's station

Tattle Tale Sample Line w/ Pinch Valve for Quick Slurry Thickness Observation

**Additional Equipment** (855 feet of hose)

2 – 12 x 14 Work Flats with electric spud poles. More 5h3 600 feet of 3/8 cable, danforth anchor back up system.

14 = 8 in. x 20 ft. (280 feet) sections of 32.5 SDR HDPE pipe w/ quick disconnect fittings and ringlocks.

12 = 8 in. x 39 ft. (480 feet) sections of 32.5 SDR HDPE pipe w/ quick disconnect fittings and ringlocks.

10 = 8 in. x 5 ft. (50 feet) sections of T253 layflat hose w/ quick disconnect fittings and ringlocks.

23 = IMS Saddle type pipe/hose floats

1 = 8 in. x 20 ft. sections of roll flat discharge hose w/quick disconnect fittings and ringlocks

1 = 8 in. x 25 ft. sections of roll flat discharge hose w/quick disconnect fittings and ringlocks

2-Point Rigging System 3/8 in. Travel Cable

Broadcaster discharge attachment for sidecasting slurry discharge.





