12 MONTH REPLACEMENT WARRANTY

Rimskins are warranted to be free of manufacturing defects for a period of 12 months from date of purchase. If found to be defective, if possible please take a photo and email (orders@rimskins.com.au) describing the nature of the defect. When advised please return (with proof of purchase) for immediate like for like replacement. (Please note: we will ONLY supply the same colour under warranty.)

This warranty is limited to the replacement of the defective product only and does not extend to any consequential costs that may be incurred should the product fail. Warranty does not cover costs of returning defective product. However, Rimskins will bear the cost of postage of the replacement product(s) to the claimant. It is a strict condition of the replacement warranty that original proof of purchase is provided at time of claim.

If your Rimskins are defective please return the defective product along with proof of purchase to the address below and a replacement product will be sent to you.

AVAILABLE COLORS



STE GOLOGS		
	CURRENT COLORS	
	Original	
	Black	
rim	Blue	
0	Red	
P	White	
	Yellow	









DURABLE PROTECTION FOR YOUR RIMS

PREVENT AND COVER WHEEL DAMAGE





RIMSKINS_COM_AU A great Australian invention

rim(sk)ins

For instructions on how to use Rimskins, visit www.rimskins.com.au. Click on the Fitting page to see a video showing how to apply Rimskins.

Rimskins will cover most gutter rash; however, if your rims are chipped or cracked, they may be dangerous and you should seek the advice of a wheel specialist before fitting Rimskins. For rims with existing damage, make sure any rough edges are smoothed or sanded first. The better you prepare your rims, the better Rimskins will work.

NOTE:

- **a.** Rimskins requires 12C to cure correctly. If you are in cold temperatures use a heat gun or a hairdryer on the Rimskins once they are installed.
- **b.** The adhesive used on Rimskins is a two staged tape, the first stage is only slightly tacky and is designed to assist in the fitting process allowing you to peel/lift it up several times if needed.

The second stage starts to cure to a very high bond over the next 24h from fitting. This stage requires temperatures 12 degrees and higher to bond to full strength, if need be use a heat gun or hairdryer/heater to help cure to a strong bond.

c. There is a current trend towards Matt and Satin finishes on many wheels. These finishes tend to be harder to clean/prepare and retain oil or silicone based wheel shine. To insure the glue works best, go over these wheels more than once with a suitable cleaner.

WARNING

Rimskins are only designed to protect wheel rims against kerb damage incurred at low speed while parking. Rimskins are not designed to protect wheel rims against kerb damage incurred at normal driving speeds. Rimskins may not be suitable for all wheel rim designs.

The adhesive will not stick to surfaces that have been recently treated with a Teflon- or silicone-based preservative/dressing treatment. These treatments can be applied after the installation of Rimskins.

PLEASE READ

It is **IMPERATIVE** that you clean your rims **FIRST** with a solvent or Acetone (eg.Diggers from Bunning's) as per our fitting instructions. The wipes we provide are **ONLY** for removing excess solvent after you have cleaned the rims. All tyre shines, mag wheel cleaners (Armourall, Maguiars etc) use silicon, which can be hard to see or remove and it

will stop the skins sticking properly to your wheels or may result in them coming off after a short time. This is why you **HAVE** to use solvent first. Whether they are new wheels, freshly painted, detailed and cleaned or a new car etc. there are no exceptions to this rule!

Due to Australia's dangerous goods laws, we are unable to send solvent or acetone based product through the mail. For the best results please follow every step of the instructions.

FITTING INSTRUCTIONS





5. Apply Rimskins from the top of the wheel rim and proceed in a clockwise or anti clockwise direction, removing the backing strip as



DO NOT stretch or pull the RimSkin, allow it to follow the rim without force.





- **6.** When application is complete, use scissors or a sharp blade to trim Rimskins to the correct length.
- 7. Firmly press Rimskins onto the rim.
- **8.** To clean, wipe over with wax and grease remover and cloth.

2. The performance of this product is directly related to how well you prepare the wheel rim before application. Use a quality

solvent/acetone (not supplied) and cloth to thoroughly clean the wheel rim. Wait 5 minutes for wheels to dry.

1. Read instructions before use.

Now and only now use the Rimskins wipes provided to remove any excess solvent. Wipe with a clean rag and make sure it is completely dry.

- **3.** Ensure the ends of the Rimskins have been cut off squarely.
- **4.** Peel 10cm of orange backing strip from adhesive strip.







