

**FREE  
PATTERN**

**Freshly Made** to bring your ideas to life.

EMMA & MILA

## Diaper Changing Pad (D-034) by Emma & Mila

Difficulty Level: Intermediate  
Finished Size: 20" W x 30" L



### Fabric requirements



Accent: 214-0001  
1/4 yard



Main: 21185501 03  
1 yard



Binding: 214-0093  
1/4 yard



Exclusive Project Design by Eugene Textiles Inc.  
The direction of the fabrics in the digital imagery may not be accurate to the final product.  
© Eugene Textiles Inc. All Rights Reserved.

## OTHER TOOLS & SUPPLIES

- 2/3 yd of quilt batting (58" wide)
- 24" straight edge ruler
- basic sewing supplies
  - sewing machine
  - quilting foot (optional, but recommended)
  - iron & pressing surface
  - fabric shears
  - measuring tape
  - pencil/fabric marker
  - straight pins
  - coordinating thread

## NOTES

- Please wash, dry & iron your fabric before beginning, and trim selvages.
- Unless otherwise directed, sew all seams with a 1/2" seam allowance.
- RST = right sides together.
- WOF = width of fabric.

## CUTTING

1. Cut (1) 21" x 5" rectangle from your Accent fabric.
2. Cut (3) 2-1/2" x WOF strips from your Binding fabric.
3. From your Osnaburg, cut:
  - (1) 30" x 21" rectangle for the Backing,
  - (1) 22" x 21" rectangle for the large front panel,
  - (1) 6" x 21" rectangle for the small front panel.
4. From the batting, cut (1) 36" x 24" rectangle.

## PIECING THE TOP

1. Sew the Accent rectangle to the larger front panel along their 21" edges, RST.
2. Sew the smaller front panel to the Accent rectangle along their 21" edge, RST.
3. Press both seams toward Accent.



## BINDING

1. Join the Binding strips end-to-end, RST, and press the seams open.
2. Fold & press your Binding strip in half lengthwise, Wrong Sides facing, and unfold.



3. Fold & press each long edge to the center crease.



4. Fold the strip in half lengthwise and press.



5. We suggest wrapping your Binding around a piece of cardboard and securing the end with a pin, to keep it tidy.

## ASSEMBLY

1. On a large work surface (we like the floor), make a "sandwich" of your Backing, batting & pieced top, with the fabrics' Right Sides facing outward and their edges aligned.
2. Pin or baste all layers together, over the entire surface of the mat. Trim the excess batting.
3. Install your quilting foot (if you're using one) according to your sewing machine manual's directions, and quilt the mat as desired. We sewed out quilting lines at a 45° to the fabrics' grain, making up shapes as we went.
4. Trim any uneven edges, and finish the edges with your Binding.