


MODEL SDFL90
SUCTION DIFFUSER FLEX WITH 150# PLATE FLANGES AND A LR ELBOW



QTY	PART NUMBER	PIPE SIZE		A	B	PRESSURE RATING (PSI)*	WEIGHT (LBS)	PROJECT INFORMATION
		INCH	MM					
	SDFL900200	2"	50	11-1/2"	3-1/4"	516	13	
	SDFL900250	2-1/2"	65	12-1/4"	4"	387	19	
	SDFL900300	3"	80	13"	4-3/4"	316	22	
	SDFL900400	4"	100	14-1/2"	6-1/4"	232	31	
	SDFL900500	5"	125	18"	7-3/4"	191	43	
	SDFL900600	6"	150	19-1/2"	9-1/4"	165	56	
	SDFL900800	8"	200	23-1/4"	12-1/4"	234	104	
	SDFL901000	10"	250	27-1/4"	15-1/4"	230	163	
	SDFL901200	12"	300	31-1/4"	18-1/4"	161	233	
	SDFL901400	14"	350	34-1/4"	21-1/4"	150	275	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	.91
300	.85
400	.78
500	.77
600	.76

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
 MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____


ENGINEER: _____

REV.	1	TEMP FACTOR UPDATED	DATE 1/4/2017
		epiphene.com info@epiphene.com +1-559-288-2392	
ENERGY SAVING PUMP PROTECTION SOLUTIONS			

MODEL SDFL90	
SDF WITH 150# PLATE FLANGES AND A LR ELBOW	
DRAWN BY: DKISH	DATE: 11/22/2013
APPROVED: JC	DATE: 11/22/2013
SCALE: N/A	DRAWING NUMBER: SDFL90-1

MODEL SDFS90

SUCTION DIFFUSER FLEX WITH 150# PLATE FLANGES AND A SR ELBOW



QTY	PART NUMBER	PIPE SIZE		A	B	PRESSURE RATING (PSI)*	WEIGHT (LBS)	PROJECT INFORMATION
		INCH	MM					
	SDFS900200	2"	50	10-1/2"	2-1/4"	516	12	
	SDFS900250	2-1/2"	65	11"	2-3/4"	387	18	
	SDFS900300	3"	80	11-1/2"	3-1/4"	316	20	
	SDFS900400	4"	100	12-1/2"	4-1/4"	232	28	
	SDFS900500	5"	125	15-1/2"	5-1/4"	191	38	
	SDFS900600	6"	150	16-1/2"	6-1/4"	165	49	
	SDFS900800	8"	200	19-1/4"	8-1/4"	234	89	
	SDFS901000	10"	250	22-1/4"	10-1/4"	230	136	
	SDFS901200	12"	300	25-1/4"	12-1/4"	161	190	
	SDFS901400	14"	350	27-1/4"	14-1/4"	150	224	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	.91
300	.85
400	.78
500	.77
600	.76

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8"
MAX PERMANENT OFFSET FROM CENTERLINE 3/8"


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	1	TEMP FACTOR UPDATED	DATE 1/4/2017
		epiphene.com info@epiphene.com +1-559-288-2392	
MODEL SDFS90 SDF WITH 150# PLATE FLANGES AND A SR ELBOW			
DRAWN BY: DKISH		DATE: 11/22/2013	
APPROVED: JC		DATE: 11/22/2013	
SCALE: N/A	DRAWING NUMBER: SDFS90-1		