



Drapery Databook

Glydea® ULTRA and Irismo™

somfy®

Table of Contents

Why Somfy?	2	Product Dimensional Specifications	
		Carrier Arm Dimensions	22
Drapery Motor Range	3-4	Wall Bracket Dimensions	22-23
		Ceiling Bracket Dimensions	23
Drapery Systems at a Glance	5-6	Track Configurations	24-25
Motor Features and Main Characteristics		Track Specification Charts	26-27
Features Overview Comparison Chart	7-8	Drapery Fabricated Track Options	28
Glydea® ULTRA 35	9	Custom Track Options	29
Glydea® ULTRA 60	10	Drapery Order Form & Resources	
Irismo™ 35 Mini DC	11	Drapery Order Form & Resources	30-31
Irismo™ 45 WireFree RTS	12	Bent Drapery Track Measurement Form	32
		Directions for Creating a Template for Drapery Curves	33
Drapery Motor Wiring Examples	13-14	DecoFlex Zigbee Engraving Form	34
		DecoFlex Wirefree™ Surface 5 Channel Button Engraving Form	35
Glydea® ULTRA and Irismo™ 35 Mini DC Drapery Motors, Integration and Power		DecoFlex Keypad Button Engraving Form	36
Glydea® ULTRA	15	Smoove® Wireless Wall Switches Custom Engraving Form	37-40
Glydea ULTRA DCT Control Modules	15		
Irismo™ 35	15		
Integration Control Modules for Irismo™ 35 only	15		
Irismo™ 45 Drapery Motor, Integration and Power			
Irismo™ 45	16		
Power Accessories for Irismo™ 45	16		
Somfy Digital Network™ (SDN) RS485	16		
Drapery Controls and Accessories			
Zigbee® Technology	17		
Radio Technology Somfy® (RTS)	17-18		
Somfy Digital Network™ (SDN)	19		
Wired Technology	19		
Dry Contact Technology (DCT)	19		
Drapery Components			
Common Track Components	20		
Ripplefold® & Accordia® Track Components	20		
Pinch Pleat Track Components	21		
Brackets	21		

Why Somfy?



Somfy® is the leading global manufacturer of strong, quiet motors with electronic and app controls for interior window coverings and exterior solar protections. Over 270 million users worldwide enjoy the more than 170 million motors produced by Somfy. During the past 50 years, Somfy engineers have designed products for both the commercial and residential markets to motorize window coverings such as interior shades, wood blinds, draperies, awnings, rolling shutters, exterior solar screens, and projection screens. Somfy motorization systems are easily integrated with security, HVAC, and lighting systems provide total home or building automation.

- Somfy has a production capacity of more than 70,000 motors per day.
- Somfy motors have over 600 approved standards worldwide.
- Somfy has certified over 100 patents since the year 2000.
- Every Somfy motor goes through an extensive quality assurance process that includes testing for extreme environmental conditions, electrostatic discharge, mechanical shock, and high life cycle.
- Somfy has a network of 15,000 trained professional installers throughout the world.

Somfy operates in 60 countries, with 76 subsidiaries and 60 agencies spread across 5 continents. With 8 production centers, Somfy is an efficient and reactive industry leader. Thanks to its strict quality standards, Somfy is able to satisfy the needs of over 270 million users worldwide.

Somfy has a committed customer support team comprised of Somfy motor and control specialists available for assistance:

Somfy Corporate Headquarters
800-22-SOMFY (76639)

General Customer Service
877-210-5327
customerservice_us@somfy.com

Standard Purchase Order
ordering_us@somfy.com

Rush Purchase Order
expeditedshippingorders_us@somfy.com

Accounting Inquiries
accountsreceivable@somfy.com

Technical Support
877-233-0019
technicalsupport_us@somfy.com

Warranty Claim Requests
us_return@somfy.com



Somfy understands that training and support are critical to success. Somfy's Expert Program has been developed to provide a platform for those who want to enhance their expertise of motorization and control solutions. Visit www.somfypro.com to learn more and sign up for training.

Drapery Motor Range

This document presents the technical information and related accessories for Somfy's Glydea® ULTRA and Irismo™ motor ranges designed specifically for draperies. It provides detailed information to facilitate the specification of these motor solutions and presents information regarding options for specialty applications, including bent and curved tracks. Information for Somfy's entire product range, including motors, power sources, control interfaces, etc. can be accessed at www.somfypro.com.

Innovative


These sophisticated motors are the result of industry experience and expertise. Reliable motor solutions offer a superior user experience as well as a wide array of features, while exemplifying Somfy's continued commitment to quality.

Adaptable


Designed for residential, commercial, and hospitality markets, these ranges provide a convenient solution for glare reduction and privacy while also reducing energy costs and protecting interiors from damaging UV rays.

Flexible


Glydea® ULTRA and Irismo™ are available for all drapery types, including Pinch Pleat, Ripplefold®, and Accordia®. Additionally, they have been designed to easily adapt to various control technologies, including infrared, Dry Contact, Radio Technology Somfy® (RTS), RS485, and Zigbee®.



Pinch Pleat



Ripplefold®



Accordia®

Compatible with various technologies:



Aesthetic

- Clean, premium motor design with built-in control modules.
- Easy to conceal behind drapery fabric.
- Adjustable limit setting provides precise alignment of drapery fabric.
- Advanced track design and swivel ceiling brackets minimize light gaps.
- Soft start and soft stop drapery motion.
- Improved hardware design provides greater overlap and even stack back.

Easy Installation

- Spring loaded one-touch hardware (wall and ceiling mount).
- Motor can be installed to the right or left side of the drapery track.
- Automatic or adjustable limit setting.
- Inverse (top mount) option allows the motor to be installed above the track.

Flexible

- Patented versatile master carrier reduces friction and is adaptable to various drapery types.
- Multiple built-in control options allow seamless integration with third-party systems.
- Adjustable drapery speed control.

Ultra Quiet

- Motor design and advanced high-performance belt drive system provide quiet operation (<38dBA).




Somfy
DESIGNED FOR
SILENCE

Efficient

- Touch motion feature allows the user to activate the motorized drapery simply by pulling on the fabric.
- Manual override permits the drapery to be adjusted manually, which is ideal for power outages and also protects the fabric from damage.
- The “my” function allows user to set a preferred drapery opening which provides enhanced convenience.

Flexible


Includes 5 years international warranty.
International certifications.




Drapery Systems at a Glance

The difference is in the details.






Any style, any technology



Pinch Pleat



Ripplefold®



Accordia®

Built-in RTS, DCT, and Wired technologies



Radio Technology Somfy®



Optional modules extend control to Zigbee and RS485



Features Overview Comparison Chart

	Line Voltage 120V DC			
	Glydea® ULTRA 35		Glydea® ULTRA 60	
	DCT	RTS	DCT	RTS
Motor unit main features				
Soft start	✓	✓	✓	✓
Manual operation	✓	✓	✓	✓
Automatic limits on end stop	✓	✓	✓	✓
Soft stop	✓	✓	✓	✓
Intermediate position	✓	✓	✓	✓
Touch motion with 2 sensitivity settings	✓	✓	✓	✓
Adjustable limits	✓	✓	✓	✓
Speed control & adjustment	✓	✓	✓	✓
Control options				
Dry Contact input via RJ12 Connector	✓	✓	✓	✓
Dry Contact individual, group and master control	✓	✓	✓	✓
Radio Technology Somfy® RTS		✓		✓
SDN RS485 digital technology (two-way communication)	✓	✓	✓	✓
Zigbee® module (two-way communication)	✓		✓	
Tandem alternative	✓	✓	✓	✓
Timer control	✓	✓	✓	✓
Installation and setting features				
Programming with buttons on motor unit	✓	✓	✓	✓
Programming with DCT Setting Tool (preferred)	✓		✓	
LED indicators	✓	✓	✓	✓
Motor unit direction change	✓	✓	✓	✓
Factory reset	✓	✓	✓	✓
Inverse (top mount) mounting	✓	✓	✓	✓
Audible sound Indicator				
Tracks/Drapery Types				
One-way opening	✓	✓	✓	✓
Center opening	✓	✓	✓	✓
Asymmetric	✓	✓	✓	✓
Multiple	✓	✓	✓	✓
Pinch pleat	✓	✓	✓	✓
Ripplefold® with overlap arm	✓	✓	✓	✓
Ripplefold® with butt arm	✓	✓	✓	✓
Accordia®	✓	✓	✓	✓

	Low Voltage 24V DC		WireFree 25.9V DC (Li-ion Rechargeable)
	Irismo™ 35 RTS	Irismo™ 35 DCT	Irismo™ 45 WireFree RTS
Motor unit main features			
Soft start	✓	✓	✓
Manual operation	✓	✓	✓
Automatic limits on end stop	✓	✓	✓
Soft stop	✓	✓	✓
Intermediate position	✓	✓	✓
Touch motion with 2 sensitivity settings	✓	✓	✓
Adjustable limits	✓	✓	✓
Speed control & adjustment	✓	✓	✓
Control options			
Dry Contact input via RJ12 Connector	✓	✓	
Dry Contact individual, group and master control	✓	✓	
Radio Technology Somfy® RTS	✓		✓
SDN RS485 digital technology (one-way communication)	✓	✓	
Tandem alternative	✓	✓	✓
Timer control	✓	✓	✓
Installation and setting features			
Programming with buttons on motor unit	✓		
Programming with DCT Setting Tool (preferred)		✓	
LED indicators	✓	✓	✓
Motor unit direction change	✓	✓	✓
Factory reset	✓	✓	✓
Inverse (top mount) mounting	✓	✓	✓
Audible sound Indicator			✓
Tracks/Drapery Types			
One-way opening	✓	✓	✓
Center opening	✓	✓	✓
Asymmetric	✓	✓	✓
Multiple	✓	✓	
Pinch pleat	✓	✓	✓
Ripplefold® with overlap arm	✓	✓	✓
Ripplefold® with butt arm	✓	✓	✓
Accordia®	✓	✓	✓

Glydea® ULTRA 35

Technical Specifications

Motor part numbers

Glydea® ULTRA 35 RTS motor (with 10' cable and molded NEMA plug)	Part# 1246116
Glydea® ULTRA 35 DCT motor (with 10' cable and molded NEMA plug)	Part# 1246115
Glydea® ULTRA 35 Wired motor (5' long without plug)	Part# 1003153


Features overview

Glydea® ULTRA 35	
Motor unit main features	
Soft start	✓
Manual operation	✓
Automatic limits on end stop	✓
Soft stop	✓
Intermediate position	✓
Touch motion with 2 sensitivity settings	✓
Adjustable limits	✓
Speed control & adjustment	✓
Control options	
Dry Contact input via RJ12 Connector	✓
Dry Contact individual, group and master control	✓
Radio Technology Somfy® RTS	✓
SDN RS485 digital technology (two-way communication)	✓
Zigbee® (two-way communication) (DCT only)	✓
Tandem alternative	✓
Sun control	✓
Timer control	✓
Installation and setting features	
Programming with buttons on motor unit	✓
Programming with DCT Setting Tool (preferred)	✓
LED indicators	✓
Motor unit direction change	✓
Factory reset	✓
Inverse (top mount) mounting	✓
Tracks/Drapery Types	
One-way opening	✓
Center opening	✓
Asymmetric	✓
Multiple	✓
Pinch pleat	✓
Ripplefold® with overlap arm	✓
Ripplefold® with butt arm	✓
Accordia®	✓

Motorized track main characteristics

Glydea® ULTRA 35	
Power Supply	120V AC 50/60 HZ
Amperage	0.8 A
Average linear speed	Silent Mode: 2.95 in./s (7.5 cm/s) Standard Mode: 4.95 in./s - 7.86 in./s (12.5 cm/s - 20 cm/s)
Power consumption	96W (standby <1W)
Power cable type	3-wire cable with molded NEMA plug 4-wire cable (wired version only)
Control connector type (Dry Contact)	RJ12
DCT control circuit voltage	3.3V DC
Motor sound level	<38 dBA at silent mode
Certifications	c TUV us, CE
Track maximum length	32 ft. (9.7 m)
Maximum number of splices	2
Minimum bending radius	11.8 in. (30 cm)
Minimum curving radius	118 in. (300 cm)
Side opening max weight	77 lbs. 35 kg.
Center opening max weight	77 lbs. 35 kg.
Tandem alternative (see pages 23, 24, 26)	154 lbs./ 70 kgs. 64 ft./ 19.4 m

Motor dimensions



Glydea® ULTRA 60

Technical Specifications

Motor part numbers

Glydea® ULTRA 60 RTS motor (with 10' cable and molded NEMA plug)	Part# 1246118
Glydea® ULTRA 60 DCT motor (with 10' cable and molded NEMA plug)	Part# 1246117
Glydea® ULTRA 60 Wired motor (5' long without plug)	Part# 1003160


Features overview

Glydea® ULTRA 60	
Motor unit main features	
Soft start	✓
Manual operation	✓
Automatic limits on end stop	✓
Soft stop	✓
Intermediate position	✓
Touch motion with 2 sensitivity settings	✓
Adjustable limits	✓
Speed control & adjustment	✓
Control options	
Dry Contact input via RJ12 Connector	✓
Dry Contact individual, group and master control	✓
Radio Technology Somfy® RTS	✓
SDN RS485 digital technology (two-way communication)	✓
Zigbee® (two-way communication) (DCT only)	✓
Tandem alternative	✓
Sun control	✓
Timer control	✓
Installation and setting features	
Programming with buttons on motor unit	✓
Programming with DCT Setting Tool (preferred)	✓
LED indicators	✓
Motor unit direction change	✓
Factory reset	✓
Inverse (top mount) mounting	✓
Tracks/Drapery Types	
One-way opening	✓
Center opening	✓
Asymmetric	✓
Multiple	✓
Pinch pleat	✓
Ripplefold® with overlap arm	✓
Ripplefold® with butt arm	✓
Accordia®	✓

Motorized track main characteristics

Glydea® ULTRA 60	
Power Supply	120V AC 50/60 HZ
Amperage	0.8 A
Average linear speed	Silent Mode: 2.95 in./s (7.5 cm/s) Standard Mode: 4.95 in./s - 7.86 in./s (12.5 cm/s - 20 cm/s)
Power consumption	96W (standby <1W)
Power cable type	3-wire cable with molded NEMA plug 4-wire cable (wired version only)
Control connector type (Dry Contact)	RJ12
DCT control circuit voltage	3.3V DC
Motor sound level	<38 dBA at silent mode
Certifications	c TUV us, CE
Track maximum length	36 ft. (10.9 m)
Maximum number of splices	2
Minimum bending radius	11.8 in. (30 cm)
Minimum curving radius	118 in. (300 cm)
Side opening max weight	132 lbs. 60 kg.
Center opening max weight	132 lbs. 60 kg.
Tandem alternative (see pages 23, 24, 26)	264 lbs. / 120 kgs. 72 ft. / 21.8 m

Motor dimensions



Irismo™ 35 Mini DC

Technical Specifications

Motor part numbers

Irismo™ 35 Mini DC RTS Part# 1003004

Irismo™ 35 Mini DC DCT Part# 1003003


Features overview

	Irismo™ 35 RTS	Irismo™ 35 DCT
Motor unit main features		
Soft start	✓	✓
Soft stop	✓	✓
Manual operation	✓	✓
Automatic limits on end stop	✓	✓
Intermediate position	✓	✓
Touch motion with 2 sensitivity settings	✓	✓
Adjustable limits	✓	✓
Speed control & adjustment	✓	✓
Control options		
Dry Contact input via RJ12 connector	✓	✓
Radio Technology Somfy® RTS	✓	
Tandem alternative	✓	✓
SDN RS485 digital technology (one-way communication)	✓	✓
Zigbee® (one-way communication)	✓	✓
Timer control	✓	✓
Installation and setting features		
Programming with DCT Setting Tool (preferred)	✓	✓
LED indicators	✓	✓
Motor unit direction change	✓	✓
Factory reset	✓	✓
Inverse mounting (top mount)	✓	✓
Tracks/Drapery Types		
One-way opening	✓	✓
Center opening	✓	✓
Asymmetric	✓	✓
Multiple	✓	✓
Pinch pleat	✓	✓
Ripplefold® with overlap arm	✓	✓
Ripplefold® with butt arm	✓	✓
Accordia®	✓	✓

Motorized track main characteristics

	Irismo™ 35 RTS	Irismo™ 35 DCT
Power Supply	24V DC	
Power adaptor amperage	2 A	
Average linear speed	4.9 in./s - 7.86 in./s 12.5 cm/s - 20 cm/s	
Power consumption	<3W (standby)	
Power adaptor cable length	13.2 ft. (4 m)	
Control connector type	RJ12	
DCT control circuit voltage	5V DC	
Motor sound level	<44 dBA	
Certifications	CE	
Track maximum length	32 ft. (9.7 m)	
Maximum number of splices	2	
Minimum bending radius	11.8 in. (30 cm)	
Minimum curving radius	118 in. (300 cm)	
Side opening max weight	77 lbs. (35 kg)	
Center opening max weight	77 lbs. (35 kg)	
Tandem alternative (see pages 23, 24, 26)	154 lbs. (70 kg)	

Motor dimensions



Irismo™ 45 WireFree RTS

Technical Specifications

Motor part numbers

Irismo™ 45 WireFree RTS

Part# 1002353

Features overview

Irismo™ 45 WireFree RTS


Motor unit main features	
Soft start	✓
Soft stop	✓
Manual operation	✓
Intermediate position	✓
Touch motion with 2 sensitivity settings	✓
Adjustable limits	✓
Speed control & adjustment	✓
Control options	
Radio Technology Somfy® RTS	✓
Tandem alternative	✓
Timer control	✓
Installation and setting features	
LED indicators	✓
Audible sound Indicator	✓
Motor unit direction change	✓
Factory reset/programming button	✓
Inverse mounting (top mount)	✓
Tracks/Drapery Types	
One-way opening	✓
Center opening	✓
Asymmetric	✓
Pinch pleat	✓
Ripplefold® with overlap arm	✓
Ripplefold® with butt arm	✓
Accordia®	✓

Motorized track main characteristics

Irismo™ 45 WireFree RTS


Power Supply	25.9V DC
Average linear speed	4.9 in./s - 7.86 in./s 12.5 cm/s - 20 cm/s
Rechargeable (Li-ion) battery capacity	3200 mAh
Motor sound level	<44 dBA
Certifications	CE
Track maximum length	33 ft. (10 m)
Maximum number of splices	2
Minimum bending radius	11.8 in. (30 cm)
Minimum curving radius	118 in. (300 cm)
Side opening max weight	99 lbs. (45 kg)
Center opening max weight	99 lbs. (45 kg)
Tandem alternative (see pages 23, 24, 26)	198 lbs. (90 kg)

Motor dimensions




Drapery Motor Wiring Examples

Zigbee® Control



Radio Technology Somfy® (RTS) Control




Dry Contact Technology (DCT) Control

DRY CONTACT

The Dry Contact Control can be done through devices with 2 normally open contacts (open, close) or 3 normally open contacts (open, stop, close). For devices using 2 contacts, the stop command is achieved by closing the open and close contacts. For 3 devices, the stop can also be achieved with a specific stop button.

Number of DCT Drapery Motors and Length of Control Limitations

Wire Cross-Section	Maximum Length of Cable	Maximum Number of Motors
Cat5 or Equal	328 ft. (100 m)	10
0.75 mm ²	656 ft. (200 m)	20




NOTE: Examples are for illustrative purposes. Additional components may be needed depending on your installation.
Applies to Glydea ULTRA range only.

Drapery Motor Wiring Examples

Wired Control




Individual control



Brown	Dir1
Black	Dir2
Blue	Neutral
Green/Yellow	Ground


Group control




Somfy Digital Network™ (SDN) Wiring Examples




Plug-in:



Power Panel:



Power over Ethernet (PoE):



NOTE: Contact Somfy for additional details.

NOTE: Examples are for illustrative purposes. Additional components may be needed depending on your installation. Does not apply to Irismo™ 45 WireFree. Not compatible with TaHoma.

Glydea® ULTRA and Irismo™ 35 Mini DC Drapery Motors, Integration and Power

Glydea® ULTRA

Glydea® ULTRA 35 and Glydea® ULTRA 60



Glydea® ULTRA 35

RTS with 10' Plug 1246116
DCT with 10' Plug 1246115
Wired w/o Plug 1003153

Glydea® ULTRA 60

RTS with 10' Plug 1246118
DCT with 10' Plug 1246117
Wired w/o Plug 1003160

Glydea® ULTRA Control Modules

Zigbee®



Plug-in module integrates with Zigbee systems
 9000043

SDN RS485



RS485 Two-way Module for Glydea® ULTRA Motors
 1871412

Irismo™ 35

Irismo™ 35 Mini DC



RTS 1003004
DCT 1003003

(24V DC power supply included)
 (Optional power panels available)

Please see pages 13 and 14 for wiring examples.

DC Control Card Enclosure




DC Control Card Enclosure
 9021132

Enclosure/Control Kits

SDN Irismo™ 35 24V Mini DC Control Enclosure Kit (includes cable for SDN & PoE)
 1870282

Irismo™ 35 Control Modules

SDN RS485




RS485 plug-in module integrates with Somfy Digital Network™ systems

1811129



Irismo™ 35 Power Panels

Surface-mount Power Panel



SDN PowerConnect™ Surface-Mount Panel

Adds 10 isolated motor ports and two isolated device ports to an SDN bus segment.

1871026

Rack-mount Power Panel



SDN PowerConnect™ Rack-Mount Panel

Adds eight isolated motor ports and two isolated device ports to an SDN bus segment per panel.

Single Kit: 1871027
 Dual Kit: 1871312



Irismo™ 45 Drapery Motor, Integration and Power

Irismo™ 45

Irismo™ 45 WireFree RTS



1002353

Rechargeable Lithium-ion
battery pack included

Power Accessories for Irismo™ 45



Plug-in Battery Charger for Irismo™ 45
with 5 ft. cable - 20 AWG

1003080



Replacement 25.9V Rechargeable
Li-ion Battery for Irismo™ 45

9026476

Drapery Controls and Accessories

Zigbee® Technology

TaHoma® switch



TaHoma® switch
1871037

TaHoma® switch
(with ethernet adaptor)
1871038



TaHoma® switch
Ethernet Adaptor
9028054

Glydea® ULTRA Control Module



Zigbee (2-Way) Module for
Glydea® ULTRA Motors
9000043



Ysia®



Ysia® 1 Zigbee
1871153



Ysia® 5 Zigbee
1871154



Ysia® 5 Variation Zigbee
1871281

DecoFlex WireFree™ Wall Switches



DecoFlex WireFree™ Zigbee,
White 2 Channel
Surface-mount
1871577
In-wall
1871573



DecoFlex WireFree™ Zigbee,
White 4 Channel
Surface-mount
1871576
In-wall
1871572

Radio Technology Somfy® (RTS)

Situo & Telis Collections



Situo® 1 RTS
Pure Single
Channel Remote
1870571



Situo® 5 RTS
Pure Five
Channel Remote
1870575



Situo® 1 RTS
Iron Single
Channel Remote
1870572



Situo® 5 RTS
Iron Five
Channel Remote
1870576



Situo® 1 RTS
Natural Single
Channel Remote
1870573



Situo® 5 RTS
Natural Five
Channel Remote
1870577



Situo® 1 RTS
Arctic Single
Channel Remote
1870574



Situo® 5 RTS
Arctic Five
Channel Remote
1870578



Situo® 5 RTS
Soliris Five
Channel Remote
1870579



Situo® 5 RTS
Variation Five
Channel Remote
1811612



Telis 1 RTS Patio
Single Channel
Remote
1810643



Telis 4 RTS Patio
Five Channel
Remote
1810645



Telis 16 Channel RTS
Pure Remote with
On-screen display
1811081



Telis 16 Channel RTS
Silver Remote with
On-screen display
1811082



Telis 1 Chronis RTS
Pure Timer with
On-screen display
1805237

NOTE: For additional information regarding Zigbee® or RTS controls, contact Somfy Systems, Inc.

Drapery Controls and Accessories

Radio Technology Somfy® (RTS)



DecoFlex WireFree™ Wall Switches



DecoFlex 1
Channel RTS
WireFree™ Wall Switch
White
1810897
Black
1810899



DecoFlex 2
Channel RTS
WireFree™ Wall Switch
White
1811068
Black
1811067



DecoFlex 3
Channel RTS
WireFree™ Wall Switch
White
1811071
Black
1811070



DecoFlex 4
Channel RTS
WireFree™ Wall Switch
White
1811074
Black
1811073



DecoFlex 5
Channel RTS
WireFree™ Wall Switch
White
1810813
Black
1810830



DecoFlex WireFree™
3-Button
White
1870908



DecoFlex WireFree™
Surface 5 Channel
White
1871025

- Wall Switches shown in white. Black finish is also available.
- Switches are shown assembled with printed channel buttons.
- Custom engraved buttons are also available.



Black

- Wall Switches are only available in white.

Table Top Accessories



DecoFlex WireFree™
RTS Table Top
Accessory
Black
1811051*



DecoFlex WireFree™
RTS Table Top
Accessory
Silver
1810972*



DecoFlex WireFree™
RTS Table Top
Accessory
White
1811185*



Smoove® 1 RTS Pure II
181361



Smoove® 4 RTS Pure II
181381

- Battery-operated convenience
- Surface mounts with ease
- Frames available in 3 colors



Pure



Silver Matte



Black

*DecoFlex Switch is sold separately from Table Top Accessory.

TaHoma® switch



TaHoma® switch
1871037



TaHoma® switch
(with ethernet adaptor)
1871038

16 Channel RTS Interface



Universal RTS Interface 16-Channel
(converts IR, RS232, RS485 to RTS)
1810872

RTS Repeater



RTS Repeater
(extends RTS range)
1810791

NOTE: For additional information regarding Zigbee® or RTS controls, contact Somfy Systems, Inc.

Drapery Controls and Accessories

Somfy Digital Network™ (SDN)



Control4® to Digital Motor Interface

Interfaces



Receives Zigbee transmissions and converts them to motor control commands

1870533



Somfy Connect Universal Automation Interface (UAI) Plus

Commission and integrate Somfy-powered SDN solutions over IP

1870272




Somfy Connect BMS Interface V2

Provides communication between building management systems and SDN motorized shading systems

1871168

SDN RS485 Control Modules



RS485 Module for Irismo™ Motors (Irismo DCT to RS485 Upgrade)

Converts SDN signals to control commands to operate Irismo™ 35 motors

1811129



RS485 (2-Way) Module for Glydea® ULTRA Motors

Converts SDN signals to control commands to operate Glydea® ULTRA motors

1871412

Wired Technology



Dry Contact Technology (DCT)

DRY CONTACT

Decorator Paddle Switches

Dry Contact Switches

Limit Setting Tool



Maintained White
1800374

Double Pole,
Double Throw
1800375



Maintained Ivory
1800373

Double Pole,
Double Throw
1800376



White
1800219



Ivory
1800220



9014599*

8 ft. Cable with RJ12 Plug (required)
9015443

*For use with Glydea ULTRA wired motors only.

Drapery Components

Common Track Components

Small Drive Pulley (white & bronze)



1782318



1782861

Drive Pulley (white & bronze)



1780945



1782873

Pulley Cover (white & bronze)



1780898



1782868

Straight Rail Joint



1782316

Heavy Duty Master Carrier



1781344

Silent Master Carrier*
1782922

High Performance 10mm Belt



198' per roll
1782084

Track (white & bronze)



96' per carton (6 pcs. x 16')
1780899 per ft.



228' per carton (12 pcs x 19')
9025133 per ft.

*Must be used with Fixing holder 9027657

Ripplefold® & Accordia® Track Components

Straight Arm Kit



1782321
For use with center
opening draperies

Overlap Arm Kit



1782320
For use with one way and
center opening draperies

One Way Overlap Arm Kit



1780947
For use with tandem
alternative straight arm

Ripplefold® Butt Master Arms Kit



1780953
For use with center
opening draperies only

One Way Ripplefold® Butt Arm Kit



1782319
For use with Ripplefold one
way opening and double
track tandem alternative

Straight Arm Kit



1782662
For use with tandem butted
tracks alternative draperies
(to be used together)

Fixing Holder for Ripplefold Runner



9027657
For use with Ripplefold carriers,
attaches to the master carrier
and first Ripplefold carrier

90 Degree Drapery Motor Adaptor Plate



9027179
For use with Ripplefold
draperies to provide more
aesthetic look

Adjustable Ripplefold Arm Kit



9027045
For use with Ripplefold
draperies to provide more
aesthetic look

Ripplefold® and Accordia® Type Carriers



80% Fullness (White)
Carrier Spacing: 2 3/8"
Qty. per roll: 500
1780903



100% Fullness (White)
Carrier Spacing: 2 1/8"
Qty. per roll: 500
1780902



120% Fullness (White)
Carrier Spacing: 1 7/8"
Qty. per roll: 500
1780901



Ripplefold Silent
Runners 80% (White)
Carrier Spacing: 2 3/8"
Qty. per roll: 250
9027592



Ripplefold Silent
Runners 100% (White)
Carrier Spacing: 2 1/8"
Qty. per roll: 250
9027593



Ripplefold Silent
Runners 120% (White)
Carrier Spacing: 1 7/8"
Qty. per roll: 250
9027594



80% Fullness (Bronze)
Carrier Spacing: 2 3/8"
Qty. per roll: 500
1782782



100% Fullness (Bronze)
Carrier Spacing: 2 1/8"
Qty. per roll: 500
1782871



120% Fullness (Bronze)
Carrier Spacing: 1 7/8"
Qty. per roll: 500
1782870



Ripple Pendant Only
White
1780948



Ripple Return Snap
100 yd. roll: 1782301
Per yd.: 1782542



Ripple Return Snap
White 1780905
Bronze 1782863

NOTE: Recommended for use with Somfy Ripple Snap Tape (ordered separately), but also adaptable to Kirsch and Graber snap tape.
Accordia® type carrier consists of Pinch Pleat carrier and Ripplefold® pendant.

Drapery Components

Pinch Pleat Track Components

Straight Arm Kit



1782321
For use with center opening draperies

Overlap Arm Kit



1782320
For use with one way and center opening draperies

Pinch Pleat Return Hook



White
1780895



Bronze
1782862

Carrier



White
1781415



Bronze
1782862

Silent Carrier
(white only)
1782921

One Way Overlap Arm Kit



1780947
For use with tandem alternative straight arm

Straight Arm Kit



1782662
For use with tandem butted tracks alternative draperies
(to be used together)

Brackets

One Touch Ceiling Bracket



1780907

Adjustable Wall Mount Bracket



Projection 4.5" - 6"
1780909

Double Adjustable Wall Mount Bracket



Projection 8.75" - 10.25"
1780910

Swivel Ceiling Bracket



1780906



Bronze
1782865



Bronze
Projection 4.5" - 6"
1782866




Bronze
Projection 8.75" - 10.25"
1782867




Bronze
1782864

Adjustable Wall/Ceiling Mount Bracket Kit



Projection 4.5" - 6"
1782054

Double Adjustable Wall/Ceiling Mount Bracket Kit




Projection 8.75" - 10.25"
1782053


Product Dimensional Specifications

Carrier Arm Dimensions


Overlap Arm - #1782320




Overlap Arm - #1780947



Straight Arm* - #1782321




Straight Arm - #1782662




*For use with one-way opening with standard drive pulley.


One Way Butt Arm - #1782319




Adjustable Ripplefold Arm kit - #9027045



Butt Master Arm Center Opening - #1780953




Fixing Holder for Ripplefold Runner - #9027657




Wall Bracket Dimensions

Adjustable Wall Mount Bracket - #1780909 & 1782866




Double Adjustable Wall Mount Bracket - #1780910 & 1782867




Product Dimensional Specifications

Track Profile




Ceiling Bracket Dimensions


One Touch Ceiling Bracket - #1780907 & 1782865




Swivel Ceiling Bracket - #1780906 & 1782864 (recommended for curved tracks)




90 Degree Motor Plate - #9027179



Carriers




Carriers



Track Configurations


Ripplefold® One Way Stacked




Required Arms (1)





Required Arms (2)



Bottom-up view of track and drape assembly



Center Opening




Required Arms (1 each)




Straight Arm Kit - #1782321
&
Overlap Arm Kit - #1782320

Bottom-up view of track and drape assembly



*Motor can be mounted on either side of track.

Center Opening with Butt Master Arms




Required Arms (2)



Butt Master Arms - #1780953


Bottom-up view of track and drape assembly



*Motor can be mounted on either side of track.


Track Configurations

Pinch Pleat One Way Stacked





Required Arms (1)

One Way Overlap Arm Kit - #1782320




Center Opening




Required Arms (1 each)

Straight Arm Kit - #1782321




Overlap Arm Kit - #1782320



*Motor can be mounted on either side of track.

Pinch Pleat and Ripplefold® Two One Way Butted Tracks (tandem alternative)



Required Arms (2)

One Way Butt Arm Kit - #1782319




Required Arms (2)

Straight Arm Kit - #1782662







Overlap Arm Kit - #1780947



Track Specification Charts

Selection Charts




		Glydea® 35e & Irismo™ 35 Mini DC		Irismo™ 45 WireFree RTS		Glydea® 60e		
Track Type		UP TO 10 FT.	UP TO 20 FT.	UP TO 32 FT.	UP TO 33 FT.	UP TO 10 FT.	UP TO 32 FT.	UP TO 36 FT.
A	One Way	77 Lbs.			99 Lbs.	132 Lbs.		
								
B	Center Opening	77 Lbs.			99 Lbs.	132 Lbs.		
								
C	Asymetrical	77 Lbs.			99 Lbs.	132 Lbs.		
								
D	One Way w/Bend	77 Lbs.	55 Lbs.	44 Lbs.	NA	100 Lbs.	100 Lbs.	77 Lbs.
 R = 30 cm max (11.8")								
E	Center Opening w/Bend	77 Lbs.	55 Lbs.	44 Lbs.	NA	100 Lbs.	100 Lbs.	77 Lbs.
 R = 30 cm max (11.8")								
F	One Way w/2 Bends	33 Lbs.	22 Lbs.	-	NA	77 Lbs.	55 Lbs.	-
 R = 30 cm max (11.8")								
G	Center Opening w/2 Bends	33 Lbs.	22 Lbs.	-	NA	77 Lbs.	55 Lbs.	-
 R = 30 cm max (11.8")								
H	One Way w/Continuous Curve	77 Lbs.	33 Lbs.	-	NA	132 Lbs.	55 Lbs.	-
 R = 300 cm (118")								
I	Center Opening w/Continuous Curve	66 Lbs.	22 Lbs.	-	NA	113 Lbs.	38 Lbs.	-
 R = 300 cm (118")								

Stacking Chart* - for reference only


TRACK SIZES	RIPPLEFOLD® - inches carrier count - ()					
	ONE WAY 80%	ONE WAY 100%	ONE WAY 120%	CENTER OPENING 80%	CENTER OPENING 100%	CENTER OPENING 120%
	Butt Arm	Butt Arm	Butt Arm	Butt Arm	Butt Arm	Butt Arm
Up to 4 ft.	19.5 (20)	21.5 (24)	23.5 (28)	12.25 (20)	13.25 (24)	14.25 (28)
5 ft.	22 (25)	24.5 (30)	27 (35)	13.75 (26)	14.75 (30)	16.25 (36)
6 ft.	24.5 (30)	27.5 (36)	30.5 (42)	14.75 (30)	16.25 (36)	17.75 (42)
7 ft.	27 (35)	30.5 (42)	34 (49)	16.25 (36)	17.75 (42)	19.75 (50)
8 ft.	29.5 (40)	33.5 (48)	37.5 (56)	17.25 (40)	19.25 (48)	21.25 (56)
9 ft.	32 (45)	36.5 (54)	41 (63)	18.75 (46)	20.75 (54)	23.25 (64)
10 ft.	34.5 (50)	39.5 (60)	44.5 (70)	19.75 (50)	22.25 (60)	24.75 (70)
11 ft.	37 (55)	42.5 (66)	48 (77)	21.25 (56)	23.75 (66)	26.75 (78)
12 ft.	39.5 (60)	45.5 (72)	51.5 (84)	22.25 (60)	25.25 (72)	28.25 (84)
13 ft.	42 (65)	48.5 (78)	55 (91)	23.75 (66)	26.75 (78)	30.25 (92)
14 ft.	44.5 (70)	51.5 (84)	58.5 (98)	24.75 (70)	28.25 (84)	31.75 (98)
15 ft.	47 (75)	54.5 (90)	62 (105)	26.25 (76)	29.75 (90)	33.75 (106)
16 ft.	49.5 (80)	57.5 (96)	65.5 (112)	27.25 (80)	31.25 (96)	35.25 (112)
17 ft.	52 (85)	60.5 (102)	69 (119)	28.75 (86)	32.75 (102)	37.25 (120)
18 ft.	54.5 (90)	63.5 (108)	72.5 (126)	29.75 (90)	34.25 (108)	38.75 (126)
19 ft.	57 (95)	66.5 (114)	76 (133)	31.25 (96)	35.75 (114)	40.75 (134)
20 ft.	59.5 (100)	69.5 (120)	79.5 (140)	32.25 (100)	37.25 (120)	42.25 (140)
21 ft.	62 (105)	72.5 (126)	83 (147)	33.75 (106)	38.75 (126)	44.25 (148)
22 ft.	64.5 (110)	75.5 (132)	86.5 (154)	34.75 (110)	40.25 (132)	45.75 (154)
23 ft.	67 (115)	78.5 (138)	90 (161)	36.25 (116)	41.75 (138)	47.75 (162)
24 ft.	69.5 (120)	81.5 (144)	93.5 (168)	37.25 (120)	43.25 (144)	49.25 (168)
25 ft.	72 (125)	84.5 (150)	97 (175)	38.75 (126)	44.75 (150)	51.25 (176)
26 ft.	74.5 (130)	87.5 (156)	100.5 (182)	39.75 (130)	46.25 (156)	52.75 (182)
27 ft.	77 (135)	90.5 (162)	104 (189)	41.25 (136)	47.75 (162)	54.75 (190)
28 ft.	79.5 (140)	93.5 (168)	107.5 (196)	42.25 (140)	49.25 (168)	56.25 (196)
29 ft.	82 (145)	96.5 (174)	111 (203)	43.75 (146)	50.75 (174)	58.25 (204)
30 ft.	84.5 (150)	99.5 (180)	114.5 (210)	44.75 (150)	52.25 (180)	59.75 (210)
31 ft.	87 (155)	102.5 (186)	118 (217)	46.25 (156)	53.75 (186)	61.75 (218)
32 ft.	89.5 (160)	105.5 (192)	121.5 (224)	47.25 (160)	55.25 (192)	63.25 (224)
33 ft.	92 (165)	108.5 (198)	125 (231)	48.75 (166)	56.75 (198)	65.25 (232)
34 ft.	94.5 (170)	111.5 (204)	128.5 (238)	49.75 (170)	58.25 (204)	66.75 (238)
35 ft.	97 (175)	114.5 (210)	132 (245)	51.25 (176)	59.75 (210)	68.75 (246)
36 ft.	99.5 (180)	117.5 (216)	135.5 (252)	52.25 (180)	61.25 (216)	70.25 (252)

Dual Motor Tandem Alternative

(2 one way tracks)

Track Type		Irismo™ 45 WireFree RTS	Glydea® 60e			Glydea® 35e & Irismo™ 35 Mini DC		
2 One Way Butted Tracks		UP TO 33 FT.	UP TO 10 FT.	UP TO 32 FT.	UP TO 36 FT.	UP TO 10 FT.	UP TO 20 FT.	UP TO 32 FT.
J Center opening w/2 Straight 	(1) Straight	99 Lbs.	132 Lbs.			77 Lbs.		
	(1) Straight	99 Lbs.	132 Lbs.			77 Lbs.		
K Center opening w/1 Bend  R = 30 cm max (11.8")	(1) 90° Bend	NA	100 Lbs.	77 Lbs.	77 Lbs.	55 Lbs.	44 Lbs.	
	(1) Straight	NA	132 Lbs.			77 Lbs.		
L Center opening w/2 Bends  R = 30 cm max (11.8")	(1) 90° Bend	NA	100 Lbs.	77 Lbs.	77 Lbs.	55 Lbs.	44 Lbs.	
	(1) 90° Bend	NA	100 Lbs.	77 Lbs.	77 Lbs.	55 Lbs.	44 Lbs.	
M Center opening w/2 Curves  R = 300 cm (118")	(1) Curve	NA	132 Lbs.	55 Lbs.	-	77 Lbs.	33 Lbs.	-
	(1) Curve	NA	132 Lbs.	55 Lbs.	-	77 Lbs.	33 Lbs.	-

*Measurements do not consider drapery fabric and are calculated from end of pulley to front of master arm (shown here).



Track Specification Charts

Stacking Chart cont'd* - for reference only

TRACK SIZES	RIPPLEFOLD® - inches carrier count - ()									PINCH PLEAT - inches carrier count - ()		
	ONE WAY 80%	ONE WAY 100%	ONE WAY 120%	CENTER OPENING 80%		CENTER OPENING 100%		CENTER OPENING 120%		ONE WAY	CENTER OPENING	
	Overlap Arm	Overlap Arm	Overlap Arm	Overlap Arm	Straight Arm	Overlap Arm	Straight Arm	Overlap Arm	Straight Arm	Overlap Arm	Overlap Arm	Straight Arm
Up to 4 ft.	19.25 (20)	21.25 (24)	23.25 (28)	14 (10)	13.75 (10)	15 (12)	14.75 (12)	16.25 (14)	16 (14)	15.25 (12)	11.75 (6)	11.5 (6)
5 ft.	21.75 (25)	24.25 (30)	26.75 (35)	15.5 (13)	15.25 (13)	16.5 (15)	16.25 (15)	18.25 (18)	18 (18)	16.75 (15)	12.75 (8)	12.5 (8)
6 ft.	24.25 (30)	27.25 (36)	30.25 (42)	16.5 (15)	16.25 (15)	18 (18)	17.75 (18)	19.75 (21)	19.5 (21)	18.25 (18)	13.25 (9)	13 (9)
7 ft.	26.75 (35)	30.25 (42)	33.75 (49)	18 (18)	17.75 (18)	19.5 (21)	19.25 (21)	21.75 (25)	21.5 (25)	19.75 (21)	14.25 (11)	14 (11)
8 ft.	29.25 (40)	33.25 (48)	37.25 (56)	19 (20)	18.75 (20)	21 (24)	20.75 (24)	23.25 (28)	23 (28)	21.25 (24)	14.75 (12)	14.5 (12)
9 ft.	31.75 (45)	36.25 (54)	40.75 (63)	20.5 (23)	20.25 (23)	22.5 (26)	22.25 (26)	25.25 (32)	25 (32)	22.75 (27)	15.75 (14)	15.5 (14)
10 ft.	34.25 (50)	39.25 (60)	44.25 (70)	21.5 (25)	21.25 (25)	24 (30)	23.75 (30)	26.75 (35)	26.5 (35)	24.25 (30)	16.25 (15)	16 (15)
11 ft.	36.75 (55)	42.25 (66)	47.75 (77)	23 (28)	22.75 (28)	25.5 (33)	25.25 (33)	28.75 (39)	28.5 (39)	25.75 (33)	17.25 (17)	17 (17)
12 ft.	39.25 (60)	45.25 (72)	51.25 (84)	24 (30)	23.75 (30)	27 (36)	26.75 (36)	30.25 (42)	30 (42)	27.25 (36)	17.75 (18)	17.5 (18)
13 ft.	41.75 (65)	48.25 (78)	54.75 (91)	25.5 (33)	25.25 (33)	28.5 (39)	28.25 (39)	32.25 (46)	32 (46)	28.75 (39)	18.75 (20)	18.5 (20)
14 ft.	44.25 (70)	51.25 (84)	58.25 (98)	26.5 (35)	26.25 (35)	30 (42)	29.75 (42)	33.75 (49)	33.5 (49)	30.25 (42)	19.25 (21)	19 (21)
15 ft.	46.75 (75)	54.25 (90)	61.75 (105)	28 (38)	27.75 (38)	31.5 (45)	31.25 (45)	35.75 (53)	35.5 (53)	31.75 (45)	20.25 (23)	20 (23)
16 ft.	49.25 (80)	57.25 (96)	65.25 (112)	29 (40)	28.75 (40)	33 (48)	32.75 (48)	37.25 (56)	37 (56)	33.25 (48)	20.75 (24)	20.5 (24)
17 ft.	51.75 (85)	60.25 (102)	68.75 (119)	30.5 (43)	30.25 (43)	34.5 (51)	34.25 (51)	39.25 (60)	39 (60)	34.75 (51)	21.75 (26)	21.5 (26)
18 ft.	54.25 (90)	63.25 (108)	72.25 (126)	31.5 (45)	31.25 (45)	36 (54)	35.75 (54)	40.75 (63)	40.5 (63)	36.25 (54)	22.25 (27)	22 (27)
19 ft.	56.75 (95)	66.25 (114)	75.75 (133)	33 (48)	32.75 (48)	37.5 (57)	37.25 (57)	42.75 (67)	42.5 (67)	37.75 (57)	23.25 (29)	23 (29)
20 ft.	59.25 (100)	69.25 (120)	79.24 (140)	34 (50)	33.75 (50)	39 (60)	38.75 (60)	44.25 (70)	44 (70)	39.25 (60)	23.75 (30)	23.5 (30)
21 ft.	61.75 (105)	72.25 (126)	82.75 (147)	35.5 (53)	35.25 (53)	40.5 (63)	40.25 (63)	46.25 (74)	46 (74)	40.75 (63)	24.75 (32)	24.5 (32)
22 ft.	64.25 (110)	75.25 (132)	86.25 (154)	36.5 (55)	36.25 (55)	42 (66)	41.75 (66)	47.75 (77)	47.5 (77)	42.25 (66)	25.25 (33)	25 (33)
23 ft.	66.75 (115)	78.25 (138)	89.75 (161)	38 (58)	37.75 (58)	43.5 (69)	43.25 (69)	49.75 (81)	49.5 (81)	43.75 (69)	26.25 (35)	26 (35)
24 ft.	69.25 (120)	81.25 (144)	93.25 (168)	39 (60)	38.75 (60)	45 (72)	44.75 (72)	51.25 (84)	52 (84)	45.25 (72)	26.75 (36)	26.5 (36)
25 ft.	71.75 (125)	84.25 (150)	96.75 (175)	40.5 (63)	40.25 (63)	46.5 (75)	46.25 (75)	53.25 (88)	53 (88)	46.75 (75)	27.75 (38)	27.5 (38)
26 ft.	74.25 (130)	87.25 (156)	100.25 (182)	41.5 (65)	41.25 (65)	48 (78)	47.75 (78)	54.75 (91)	54.5 (91)	48.25 (78)	28.25 (39)	28 (39)
27 ft.	76.75 (135)	90.25 (162)	103.75 (189)	43 (68)	42.75 (68)	49.5 (81)	49.25 (81)	56.75 (95)	56.5 (95)	49.75 (81)	29.25 (41)	29 (41)
28 ft.	79.25 (140)	93.25 (168)	107.25 (196)	44 (70)	43.75 (70)	51 (84)	50.75 (84)	58.25 (98)	58 (98)	51.25 (84)	29.75 (42)	29.5 (42)
29 ft.	81.75 (145)	96.25 (174)	110.75 (203)	45.5 (73)	45.25 (73)	52.5 (87)	52.25 (87)	60.25 (102)	60 (102)	52.75 (87)	30.75 (44)	30.5 (44)
30 ft.	84.25 (150)	99.25 (180)	114.25 (210)	46.5 (75)	46.25 (75)	54 (90)	53.75 (90)	61.75 (105)	61.5 (105)	54.25 (90)	31.25 (45)	31 (45)
31 ft.	86.75 (155)	102.3 (186)	117.75 (217)	48 (78)	47.75 (78)	55.5 (93)	55.25 (93)	63.75 (108)	63.5 (108)	55.75 (93)	32.25 (47)	32 (47)
32 ft.	89.25 (160)	105.3 (192)	121.25 (224)	49 (80)	48.75 (80)	57 (96)	56.75 (96)	65.25 (112)	65 (112)	57.25 (96)	32.75 (48)	32.5 (48)
33 ft.	91.75 (165)	108.3 (198)	124.75 (231)	50.5 (83)	50.25 (83)	58.5 (99)	58.25 (99)	67.25 (116)	67 (116)	58.75 (99)	33.75 (50)	33.5 (50)
34 ft.	94.25 (170)	111.3 (204)	128.25 (238)	51.5 (85)	51.25 (85)	60 (102)	59.75 (102)	68.75 (118)	68.5 (118)	60.25 (102)	34.25 (51)	34 (51)
35 ft.	96.75 (175)	114.3 (210)	131.75 (245)	53 (86)	52.75 (86)	61.5 (105)	61.25 (105)	70.75 (123)	70.5 (123)	61.75 (105)	35.25 (53)	35 (53)
36 ft.	99.25 (180)	117.3 (216)	135.25 (252)	54 (90)	53.75 (90)	63 (108)	62.75 (108)	72.25 (126)	72 (126)	63.25 (108)	35.75 (54)	35.5 (54)

Drapery Fabricated Track Options*

*Fabricated tracks are available upon request. For more information, please contact Somfy sales.

Available Carrier Arms

Carrier arms are included with fabricated motorized drapery tracks per the opening type.

One Way Opening

Overlap Arm - For use with one way opening Pinch Pleat, one way Ripplefold®, and Accordia® draperies.
Qty 1 per drapery track.



One Way Overlap Arm Kit
1782320

Center Opening

Overlap Arm - For use with center opening Pinch Pleat, Ripplefold®, and Accordia® draperies.
Qty 1 Overlap Arm per drapery track.
Qty 1 Straight Arm per drapery track.



Overlap Arm Kit
1782320

Straight Arm Kit
1782321

Center Opening Butt Master

Butt Master Arm - For use with Ripplefold® and Accordia® center opening draperies only.
Qty 2 per drapery track required.



Butt Master Arms
1780953

One Way Opening or Two Motor Tandem


One Way Butt Arm - For use with Ripplefold® one way draperies and 2 motor tandem alternative.
Qty 1 per drapery track required.



One Way Butt Arm Kit
1782319

Two Motor Tandem Alternative

Overlap Arm/Straight Arm - For use with Pinch Pleat and 2 motor tandem alternative.
Qty 1 per drapery track required.



Straight Arm Kit
1782662

Overlap Arm Kit
1780947

Available Carriers

Standard Carriers are included with fabricated motorized drapery tracks.

Pinch Pleat Draperies

Pinch Pleat Carriers**: Somfy includes a quantity of 3 carriers per foot.
Additional carriers can be ordered if necessary.



Carrier
1781415
Bronze
1782869



**See page 27 for carrier counts.

Pinch Pleat Return Hook

Qty 2 for One Way Draw (included)
Qty 4 for Center Opening (included)



Return Hook
1780895
Bronze
1782862



Ripplefold Silent Runners

Ripplefold Silent Runners 80%
Qty per roll: 250



White
9027592

Ripplefold Silent Runners 100%
Qty per roll: 250



White
9027593

Ripplefold Silent Runners 120%
Qty per roll: 250



White
9027594

Ripple Pendant
Only



1780948

Ripplefold®/Accordia® Draperies

Somfy Standard Ripplefold/Accordia Type Carriers***: The quantity of carriers needed depends on the desired fullness. Reference the chart below to determine the needed quantity and standard spacing. Each carrier comes complete with pendant. See page 26-27 for carrier counts.

Item# (white)	Item# (bronze)	Fullness	***Carrier Spacing
1780903	1782872	80%	2 3/8" / 5 per ft. (included)
1780902	1782871	100%	2 1/8" / 6 per ft. (included)
1780901	1782870	120%	1 7/8" / 7 per ft. (included)



Carrier and Pendant

*****NOTE: Quantity per ft. is included with each fabricated track. Fullness must be specified when order is placed.**

Recommended for use with Somfy Ripple Snap Tape (ordered separately), but also adaptable to Kirsch and Graber snap tape.

Ripple Snap Tape:



100 yd. roll: 1782301
Per yd.: 1782542

Return Snap:

Qty 2 for One Way Draw (included)
Qty 4 for Center Opening (included)



Return Snap
1780905
Bronze
1782863




Custom Track Options

Tandem Alternative

Tandem alternative RTS motorized systems utilize two drapery motors and are for draperies that exceed the maximum single motor capacity. Tandem systems are also available with Dry Contact control technologies and require additional accessories.


See pages 24 & 25 for track configurations and specification details



Top Mount

Drapery motors can be installed above the drapery track depending on the project needs. This option provides the ability to conceal the motor in a drop ceiling or under a valance and requires an additional kit.

Top Mount Kit
#1780908



Glystro® Conversion Kit

The Glystro® conversion kit is designed to allow adaptation to allow Somfy's current drapery motors to adapt to previous Glystro® drapery tracks and associated hardware.




#1782106

Bends

Tracks with bends are ideal for bay and corner windows. Track bends are available at a fixed radius of 11.8 in. For more information on how to measure for a bend, please see page 30.


Bent Drapery Track Measurement Form required for all orders.



Bends


Custom curves are ideal for bow windows and other special applications. For additional information on how to measure for a curve, and how to make a template, please see *Directions for Creating a Template for Drapery Curves* page 31.

Templates are required for accuracy for all orders.



Bracket Mounting Recommendations (Top View of Track)

Somfy recommends 1 bracket by each pulley and 1 bracket every 24 in. Also, 1 bracket should be placed on each side of a splice if used.





DRAPERY ORDER FORM & RESOURCES

Date of Order: _____

Account # _____

P/O #: _____ Sidemark: _____

Special Shipping Directions: _____

SHIPPING

Sold To:

Business Name: _____

Address: _____

City: _____ State: ____ Zip: _____

Phone: _____ Fax #: _____

Email: _____

Ordered By: _____

Signature: _____

Ship To:

Business Name: _____

Address: _____

City: _____ State: ____ Zip: _____

Contact Name: _____

Phone: _____ Fax #: _____

Email: _____

ORDER DETAIL: Please see next page for glossary and definition of terms.

Item #	Room	QTY.	1	2	3	4	5	6	7	8	9	10		11	12
			Motor Part#	Width (in.)	Tandem	Motor Side	Track Type*	Track Color	Stack (L/R/S)	If Bent**: # of bends	Carrier Type	Bracket		Butt Master	Splice
												Part #	QTY.		
ex.	Living Room	1	1246116	144	Y/N	L	F	WHT/BRZ	S	2	RF80	1780907	7	NO	X
1															
2															
3															
4															
5															
6															

*For curved tracks, Somfy requires a template. Please see *Directions for Creating a Template for Drapery Curves*.

**For bent tracks, Somfy does not require a template. Please include the *Bent Drapery Tracks Measurement Form* for exact measurements per angle and return.

NOTE: Somfy includes a center splice every 16' of track. Please indicate in the "SPECIAL INSTRUCTIONS" section if your requirements differ from Somfy's standard.

CONTROLS: In the space provided below, please list the part number(s) for the control(s) you desire.

Given the nature of custom motorization products, control options and compatibility vary dramatically. If you would like further assistance with control options, simply note it in the field below, and one of our customer service specialists will contact you upon the submission of your order.

SPECIAL INSTRUCTIONS





1	Motor	Part Number
	Glydea® ULTRA 35 Motor RTS with 10' Plug	1246116
	Glydea® ULTRA 35 Motor DCT with 10' Plug	1246115
	Glydea® ULTRA 60 Motor RTS with 10' Plug	1246118
	Glydea® ULTRA 60 Motor DCT with 10' Plug	1246117
	Glydea® ULTRA 35 Wired Motor with 10' Plug	1003153
	Glydea® ULTRA 60 Wired Motor with 10' Plug	1003160
	Irismo™ 35 (Mini DC) RTS	1003004
	Irismo™ 35 (Mini DC) DCT	1003003
	Irismo™ 45 WireFree RTS	1002353

2	Width (Inches)
	Motorized drapery tracks are custom built according to the specified width. Please note that the finished track width is measured pulley end to pulley end. For bent and curved tracks, please provide the total of all wall measurements. When fabricating your drapery, please add 1.5" to your return.


3	Tandem Y=Yes N=No
	Tandem motorized systems utilize two drapery motors. Items needed for tandem systems should be noted in the Special Instructions Section of the order form.
	Tandem alternative = 2 one way tracks Requires Glydea ULTRA DCT or IRISMO 35 DCT motors.

4	Motor Side
	L=Left Side R=Right Side Choose the motor side best suited for your installation.

5	Track Type
	A-I See below O=Other NOTE: Somfy requires a template for all curved tracks. Add an "S" after Track Type for Silent Master Carrier option (e.g., "A-S"). Please see Directions for Creating a Template for Drapery Curves for necessary information.

A	One way	D	One way w/Bend	G	Center Opening w/2 Bends
					
B	Center Opening	E	Center Opening w/Bend	H	One Way w/Continuous Curve
					
C	Asymmetrical	F	One way w/2 Bends	I	Center Opening w/Continuous Curve
					

6	Track Color - White or Bronze
---	-------------------------------



8	If Bent: # of Bends
	1=1 Bend, 2=2 Bends, 3=3 Bends, etc. NOTE: Somfy requires exact angle measurements for all bent tracks. Please submit completed and signed Bent Drapery Track Measurement Form with all bent track orders.

9	Carrier/Runner Type
	1=1 Bend, 2=2 Bends, 3=3 Bends, etc. SPP=Silent Pinch Pleat (QTY of 3 per foot included) PP=Pinch Pleat (QTY of 3 per foot included) RF80 = RippleFold® 80% fullness (QTY of 5 per foot spaced every 2 3/8" included) RF100 = RippleFold® 100% fullness (QTY of 6 per foot spaced every 2 1/8" included) RF120 = RippleFold® 120% fullness (QTY of 7 per foot spaced every 1 7/8" included)

10

Brackets

NOTE: Brackets are not included and must be ordered separately

Part Numbers	White	Bronze
One Touch Ceiling Bracket (not recommended for curved tracks)	# 1780907	# 1782865
4.5"-6" Wall Mount Bracket	# 1782054	# 9025621
8.75"-10.25" Double Wall Mount Bracket	# 1782053	# 9025622
Swivel Ceiling Bracket (strongly recommended for curved tracks)	# 1780906	# 1782864

Somfy recommends one (1) bracket by each pulley and one (1) bracket every 24". Additionally, one (1) bracket should be placed on each side of a splice if used.

11	Butt Master
	Y=Yes N=No Only available for RippleFold® center opening systems. Quantity 2 required; please note item #1780953 in Special Instructions Section of the order form.

12	Splice
	X=Special splice instructions Somfy includes a center splice every 16ft of track. Please indicate in the Special Instructions Section if your requirements differ from Somfy's standard.




BENT DRAPERY TRACK MEASUREMENT FORM


1. Choose the design that best fits your room setup.
2. Measure the wall and degrees of all angles as in the examples shown below.
 - Make sure to provide the return measurement "R" (distance from wall to front of drapery track as shown in red). The bent track measurement form represents wall measurements; therefore, the "R" dimension **MUST BE** specified for accurate track fabrication. If "R" dimension **IS NOT** specified, drapery track will be fabricated according to dimensions (A, B, C, D, etc.) provided.
 - Return dimensions will not be considered, and measurements will be calculated from center of each bend.
 - When fabricating drapery, please add an additional 1.5 inches of drapery fabric to the anticipated return size.
3. Provide all measurements by filling out order form and submitting to Somfy.

NOTE: The following dimensions are shown from top view of the track and show various wall designs.


STYLE 1 MEASUREMENT




STYLE 2 MEASUREMENT




STYLE 3 MEASUREMENT



STYLE 4 MEASUREMENT



STYLE 5 MEASUREMENT*



TRACK 1

"R" Dimension _____
Style _____ Degree of
A _____ Bend _____
B _____ AB _____
C _____ BC _____
D _____ CD _____
E _____ DE _____
AC _____
AE _____

TRACK 2

"R" Dimension _____
Style _____ Degree of
A _____ Bend _____
B _____ AB _____
C _____ BC _____
D _____ CD _____
E _____ DE _____
AC _____
AE _____

*Splices are required for this style.

NOTE: Iriso™ 45 WireFree RTS is not compatible with bends and curves.



DIRECTIONS FOR CREATING A TEMPLATE FOR DRAPERY CURVES

What you need: • Large piece of construction paper • Tape Measure • Marker • Tape

- 1 Start with a large piece of construction paper that exceeds the depth and length of the curve.
- 2 Place the paper on the floor or ceiling depending on the orientation of the curve.
- 3 Secure the paper with tape.
- 4 Clearly define the stacking side, motor placement, pocket depth and center line of track with the marker.
- 5 Mark the radius of the curve.
- 6 Please provide as much detail as possible, and all templates must include the following:
 - Indicate "room side"
 - Note how the template was created
 - Template created on the floor facing up (See Figure 1)
 - preferred method*
 - Template created on the ceiling facing down (See Figure 2)
 - Purchase order number
 - Customer name
 - Company name and account number
- 7 Note the distance from the wall or the window to the center of the track.
NOTE: be sure to clear all possible obstructions such as handles, sills etc.
- 8 Identify the following measurement points:
 - Placement of motor
 - Exact stopping point of track on template
 - Total measurement of curve (See Figure 4-"C")

Please call Somfy for specialty curving applications.
Depending on your particular application, your
project may require special attention.

FIGURE 1: TEMPLATE ON THE FLOOR FACING UP




FIGURE 2: TEMPLATE ON CEILING FACING DOWN




FIGURE 3: CRITICAL DIMENSIONS OF A CURVED TRACK





FIGURE 4: TOTAL MEASUREMENT OF CURVE



Template Submission Instructions

- Attach a copy of the purchase order to the template.
- Roll up template and place in a mailing tube.

DO NOT FOLD TEMPLATE

NOTE: When mailing, be sure to:

- Get a tracking number
- Include your return address
- Include your purchase order number on the label

Mail to:

Somfy Systems, Inc.
121 Herrod Blvd.
Dayton, NJ 08810
Attn: Drapery Department

Acceptable materials for making templates:

- Kraft Paper • Butcher Paper • Construction Paper

Somfy will not accept template made from the following materials:

- Newspaper • Plastic • Wax Paper • Fabric • Tissue Paper
- Roofing Paper • Existing Arch Shades • Wrapping Paper

NOTE: If the material used to make a template stretches, tears easily, will not lay flat, or will mark the fabric - IT WILL NOT BE USED.

NOTE: Irisimo™ 45 WireFree RTS is not compatible with bends and curves.



DECOFLEX ZIGBEE ENGRAVING FORM

<https://www.somfypro.com/DecoFlex-custom-button>

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: ____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

Keypad Configuration (choose one)

☐ 2 Channel Surface-mount #1871577 ☐ 2 Channel In-wall #1871573 ☐ 4 Channel Surface-mount #1871576 ☐ 4 Channel In-wall #1871572

Engraving Options - Default option will be used if nothing is selected.

Character Types: (choose one)

☐ Text only - Centered only (Sentence case) ☐ Icon only Centered only ☐ Text and icon Icon centered, text below (Sentence case)
☐ 1-line ☐ 2-line

Buttons (A-D)


9 Characters Maximum (including spaces)

QTY.

A1										
A2										
B1										
B2										
C1										
C2										
D1										
D2										

Button A
Custom
Engraving
#1871604

Button B
Custom
Engraving
#1871605




2 Channel

Button A
Custom
Engraving
#1871601

Button B & C
Custom
Engraving
#1871602

Button D
Custom
Engraving
#1871603



4 Channel

ENGRAVING OPTIONS

Pictogram Options

Buttons (A-D)

Use numeric code

QTY.

A				
B				
C				
D				

01



Roller shades

02



Horizontal shades

03



Cellular shades

04



Layered shades

05



Draperies

06



Top-down
Bottom-up

07



Awnings

08



Rolling
shutters

09



Insect
screens

10



Lamps

11



Light
bulbs

12



On/Off

13



Plug

14



Kitchen

15



Patio

16



Living room

17



Dining
room

18



Bedroom

19



Bathroom

20



Entryway/
Mud room

21



Lanai

22



Sunroom

23



Bar

24



Theater

25



Family
room

Payment terms of your account will apply. All engraved wall plates are custom made and are non-cancellable. Please send form to: Fax # (609) 495-8117 or e-mail Ordering_us@somfy.com

Somfy Systems, Inc.
T: (800) 22-SOMFY
www.somfypro.com

New Jersey
121 Herrod Blvd.
Dayton, NJ 08810
T: (609) 395-1300
F: (609) 395-1776

Florida
1200 SW 35th Ave.
Boynton Beach, FL 33426
T: (561) 995-0335
F: (561) 995-7502

California
15301 Barranca Pkwy.
Irvine, CA 92618-2201
T: (949) 727-3510
F: (949) 727-3775

Somfy ULC
T: (800) 66-SOMFY
www.somfypro.ca

Canada
6411 Edwards Blvd.
Mississauga, ON L5T 2P7
T: (905) 564-6446
F: (905) 238-1491



DECOFLEX WIREFREE™ SURFACE 5 CHANNEL BUTTON ENGRAVING FORM

<https://www.somfypro.com/DecoFlex-custom-button>

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

F button by default is labeled **STOP** on the DecoFlex range of keypads.

G and *H* buttons by default are labeled as follows:


- *G* = down icon
- *H* = up icon

ENGRAVING OPTIONS

Buttons (A-E)
9 Characters Maximum (including spaces) QTY.

A									
B									
C									
D									
E									

DecoFlex WireFree™ Surface 5 Channel #1871025



Engraving Options - Default option will be used if nothing is selected.

Character Types: ☐ ALL LETTERS CAPITALIZED (Default) ☐ First Letters Capitalized ☐ As written in above section (choose one)

Payment terms of your account will apply. All engraved wall plates are custom made and are non-cancellable. Please send form to: Fax # (609) 495-8117 or e-mail Ordering_us@somfy.com

New Jersey
121 Herrod Blvd.
Dayton, NJ 08810
T: (609) 395-1300
F: (609) 395-1776

Somfy Systems, Inc.
T: (800) 22-SOMFY
www.somfypro.com
Florida
1200 SW 35th Ave.
Boynton Beach, FL 33426
T: (561) 995-0335
F: (561) 995-7502

California
15301 Barranca Pkwy.
Irvine, CA 92618-2201
T: (949) 727-3510
F: (949) 727-3775

Somfy ULC
T: (800) 66-SOMFY
www.somfypro.ca
Canada
6411 Edwards Blvd.
Mississauga, ON L5T 2P7
T: (905) 564-6446
F: (905) 238-1491



DECOFLEX KEYPAD BUTTON ENGRAVING FORM

<https://www.somfypro.com/DecoFlex-custom-button>

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

STYLE

Button Color:

☐ White #9018259 ☐ Black #9018261

Switch Type:

☐ RTS ☐ Somfy Digital Network (SDN) RS485
Including the SDN Group Keypad. Available in White only.
☐ Dry Contact
Available in White only.

ENGRAVING OPTIONS

Buttons (A-F) 9 Characters Maximum (including spaces) QTY.

A									
B									
C									
D									
E									
F									
G									
H									

F button by default is labeled STOP on the DecoFlex Range of keypads.


G and *H* buttons by default are labeled as follows:

(*G* = down icon) WHITE - #9018263 BLACK - #9018265


(*H* = up icon) WHITE - #9018267 BLACK - #9018269

These button labels can be substituted with an associated command NAME (UP, DOWN, LOWER, etc.) up to 5 characters.


DecoFlex RTS



DecoFlex SDN (Standalone or Group)



DecoFlex Dry Contact



Engraving Options - Default option will be used if nothing is selected.

Character Types: ☐ ALL LETTERS CAPITALIZED (Default) ☐ First Letters Capitalized ☐ As written in above section (choose one)

Payment terms of your account will apply. All engraved wall plates are custom made and are non-cancellable. Please send form to: Fax # (609) 495-8117 or e-mail Ordering_us@somfy.com

Somfy Systems, Inc.
T: (800) 22-SOMFY
www.somfypro.com

Florida
1200 SW 35th Ave.
Boynton Beach, FL 33426
T: (561) 995-0335
F: (561) 995-7502

California
15301 Barranca Pkwy.
Irvine, CA 92618-2201
T: (949) 727-3510
F: (949) 727-3775

Somfy ULC
T: (800) 66-SOMFY
www.somfypro.ca
Canada
6411 Edwards Blvd.
Mississauga, ON L5T 2P7
T: (905) 564-6446
F: (905) 238-1491

New Jersey
121 Herrod Blvd.
Dayton, NJ 08810
T: (609) 395-1300
F: (609) 395-1776



SMOOVE® WIRELESS WALL SWITCHES

Custom Engraving Order Form

Available for Pure frames only

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

SINGLE GANG ENGRAVING OPTIONS

OPTION 1: Smoove® 1 RTS II

Complete section for the desired option

The diagram shows a rectangular switch plate with a central square cutout. Above and below the cutout are rows of 12 small squares each, intended for engraving. Two checkboxes labeled "Use Logo Instead**" are positioned above and below the central cutout.

***Logo specs: Maximum dimension: 1.97 in. (5cm) wide x .39 in. (1cm) high
File format (type): .dxf files only*

STYLE OPTIONS

Choose only 1

☐ Smoove Frame, Pure
#9027376 (Frame Only)

Quantity:

☐ Smoove® 1 RTS Pure II
#1871361 (Switch + Frame)

Quantity:

Example:



Engraving Options - Default option will be used if nothing is selected.

Character Types: (choose one)

☐ ALL LETTERS CAPITALIZED (Default) ☐ First Letters Capitalized ☐ As written in above section



SMOOVE® WIRELESS WALL SWITCHES

Custom Engraving Order Form

Available for Pure frames only

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

SINGLE GANG ENGRAVING OPTIONS

OPTION 2: Smoove® 4 RTS II

Complete section for the desired option

☐ Use Logo Instead**

TEXT

TEXT

TEXT

TEXT

☐ Use Logo Instead**

***Logo specs: Maximum dimension: 1.97 in. (5cm) wide x .39 in. (1cm) high
File format (type): .dxf files only*

STYLE OPTIONS

Choose only 1

☐ Smoove Frame, Pure
#9027376 (Frame Only)

Quantity:

☐ Smoove® 4 RTS Pure II
#1871381 (Switch + Frame)

Quantity:

Example:



Engraving Options - Default option will be used if nothing is selected.

Character Types: (choose one)

☐ ALL LETTERS CAPITALIZED (Default) ☐ First Letters Capitalized ☐ As written in above section



SMOOVE® WIRELESS WALL SWITCHES

Custom Engraving Order Form

Available for Pure frames only

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

OPTION 3: Dual Gang Vertical

Complete section for the desired option

☐ Use Logo Instead**

TEXT

TEXT

TEXT

TEXT

☐ Use Logo Instead**

☐ Use Logo Instead**

TEXT

TEXT

TEXT

TEXT

☐ Use Logo Instead**


***Logo specs: Maximum dimension: 1.97 in. (5cm) wide x .39 in. (1cm) high
File format (type): .dxf files only*

STYLE OPTIONS

☐ Smoove Double Frame, Pure
#9027377 (Frame Only)

Quantity:

Examples:



Engraving Options - Default option will be used if nothing is selected.

Character Types: (choose one)

- ☐ ALL LETTERS CAPITALIZED (Default)
- ☐ First Letters Capitalized
- ☐ As written in above section



SMOOVE® WIRELESS WALL SWITCHES

Custom Engraving Order Form

Available for Pure frames only

Customer Name: _____ Customer #: _____

SHIPPING

Shipping Information

Ship to: Default Shipping Address ☐ Drop Ship ☐
Name: _____
Address: _____
City: _____ State: _____ Zip: _____
Phone: _____

Project Information

Project Name: _____
Installer Name/Company: _____
P/O #: _____ Order #: _____
Area: _____
Room: _____

DUAL GANG ENGRAVING OPTIONS



OPTION 4: Dual Gang Horizontal

Complete section for the desired option

☐ Use Logo Instead**										☐ Use Logo Instead**									
TEXT						TEXT													
TEXT						TEXT													
TEXT						TEXT													
TEXT						TEXT													
☐ Use Logo Instead**										☐ Use Logo Instead**									

**Logo specs: Maximum dimension: 1.97 in. (5cm) wide x .39 in. (1cm) high. File format (type): .dxf files only

Examples:



STYLE OPTIONS

☐ Smoove Double Frame, Pure
#9027377 (Frame Only)

Quantity:

Engraving Options - Default option will be used if nothing is selected.

Character Types: ☐ ALL LETTERS CAPITALIZED (Default) ☐ First Letters Capitalized ☐ As written in above section
(choose one)

Payment terms of your account will apply. All engraved frames are custom made and are non-cancellable. Please send form to: Fax # (609) 495-8117 or e-mail Ordering_us@somfy.com

New Jersey
121 Herrod Blvd.
Dayton, NJ 08810
T: (609) 395-1300
F: (609) 395-1776

Somfy Systems, Inc.
T: (800) 22-SOMFY
www.somfypro.com
Florida
1200 SW 35th Ave.
Boynton Beach, FL 33426
T: (561) 995-0335
F: (561) 995-7502

California
15301 Barranca Pkwy.
Irvine, CA 92618-2201
T: (949) 727-3510
F: (949) 727-3775

Somfy ULC
T: (800) 66-SOMFY
www.somfypro.ca
Canada
6411 Edwards Blvd.
Mississauga, ON L5T 2P7
T: (905) 564-6446
F: (905) 238-1491



Make the move

About Somfy®

For over 50 years, Somfy has been pioneering innovative motorization and automated solutions for window coverings and exterior shading products. With comfort, ease of use, security, and sustainability in mind, our seamless and connected solutions are designed to help people make the move to living spaces impactful for humans and with a reduced impact on nature.

A BRAND OF **SOMFY** GROUP

New Jersey
121 Herrod Blvd.
Dayton, NJ 08810
T: (609) 395-1300
F: (609) 395-1776

Somfy Systems, Inc.
T: (800) 22-SOMFY
www.somfypro.com

Florida
1200 SW 35th Ave.
Boynton Beach, FL 33426
T: (561) 995-0335
F: (561) 995-7502

California
15301 Barranca Pkwy.
Irvine, CA 92618-2201
T: (949) 727-3510
F: (949) 727-3775

Somfy ULC
T: (800) 66-SOMFY
www.somfypro.ca

Canada
6411 Edwards Blvd.
Mississauga, ON L5T 2P7
T: (905) 564-6446
F: (905) 238-1491