

# 

NOZZLE CLEANING STATIONS

### HIGH PERFORMANCE NOZZLE CLEANING STATIONS





wire-wizard.com

## | RELIABLE PERFORMANCE FOR | MAXIMUM WELDING PRODUCTIVITY

## TORCH WIZARD NOZZLE CLEANING STATIONS FEATURES & OPTIONS



#### **QUICK ACCESS MAINTENANCE PANEL**

Dual-hinged panel in rear of unit provides full accessibility for easy maintenance.



#### AUTOMATED SELF-CLEANING FOR EASY MAINTENANCE

Integrated air blast for automated cleaning of spatter and debris (optional).



#### **BLUE MAGIC® ANTI-SPATTER**

Extended two-year warranty with exclusive use of Blue Magic<sup>®</sup> or Blue Chill<sup>®</sup> Anti-spatter.

#### **OPTIONAL WIRE CUTTER**

Available wire cutter cleanly cuts wire, removing weld bead for smoother arc starts.

#### INTEGRATED STATUS LIGHT

Verifies proper functionality

#### **BUILT FOR RELIABILITY**

No complex circuit boards or belts for reliable, low maintenance operation.

#### TOOL CENTER POINT (TCP) MOUNT

Optional TCP mounts available for Fanuc® tool center points.



Contained wet/dry compartments prevent sludge buildup on blade and motor.

#### TITANIUM NITRIDE COATED BLADES

Strong alloy tool steel blades are TiN coated to maintain sharpness and resist breakage.

#### HIGH TORQUE MOTOR

High torque pneumatic motor prevents stalls and cleans effortlessly.



#### ETHERNET OR IO-LINK OPTION

Ethernet or IO-Link capability available for connectivity in modern weld cells.

## FULLY ENCLOSED OPERATING ENVIRONMENT

Sealed enclosure and button covers provide protection for internal components. Catch tray keeps the weld cell clean.

## | SELF-CLEANING ROBOTIC | NOZZLE CLEANING STATION

### THE SELF-CLEANING WORKHORSE

Torch Wizard® Automatic Robotic Nozzle Cleaning Stations assist in maintaining quality and productivity in MIG welding cells by quickly and efficiently removing spatter build-up in the gas nozzle. The SC models feature a self-cleaning air blast to clean spatter and other debris from the blade and air motor. Anti-spatter is applied evenly to the nozzle and tip through an isolated compartment, eliminating wet debris build-up on the reamer blade and motor. Two year warranty with exclusive use of Blue Magic®/Blue Chill® anti-spatter.


- Extends torch consumable life by removing spatter build-up
- ▶ **IO-Link or Ethernet option** for connectivity in modern robotic welding cells
- No circuit boards and fewer moving parts means
   more reliable operation and lower maintenance costs
- Integrated air blast option for automated cleaning of debris from the reamer motor, reducing downtime for maintenance
- Multi-station bulk anti-spatter dispensing ability standard on all models
- ▶ **High torque motor** prevents stalls, reducing downtime
- ▶ Enclosed operating environment keeps weld cell clean
- ► **Easy-open hinged covers** provide quick access to internal components
- ▶ **TiN coated reamer blades** offer efficiency and longevity
- Status light to verify proper functionality
- Automated self-diagnostics and maintenance mode
- Model for aluminum welding applications also available

**Note:** Each base unit requires a reamer blade (based on I.D. of gas nozzle being used) and power/control cable. Required FRL is available for purchase.




#### TOP VIEW

#### SIDE VIEW



#### FRONT VIEW without cover



## | TANDEM ARC | NOZZLE CLEANING STATION

Innovative design cleans tandem arc torches with ease!



The Torch Wizard® TA Tandem Arc Nozzle Cleaning Station is specially designed for removing spatter build-up in tandem arc torches. Models are available for cleaning Cloos®, Fronius® and Tregaskiss® tandem arc torches. Two year warranty with use of Blue Magic®/Blue Chill® anti-spatter.

- Quickly and effectively cleans tandem arc torch nozzles, requiring only a simple movement of the torch to ream each side
- Nozzle clamp (based on torch model) designed specifically for securing tandem arc torches
- ► Includes all the same features and uses the same reamer blades as the other Torch Wizard® Nozzle Cleaning Stations

Torch Wizard® Tandem Arc Nozzle Cleaning Station EL-NCS-A-TA-24-TR



## **CLEANING STATION OPTIONS & ACCESSORIES**

TITANIUM NITRIDE COATED
REAMER BLADES

Made from alloy tool steel and coated with titanium nitride (TiN) for enhanced durability, our reamer blades maintain their sharp cutting edge and resist breakage. Sizes for all standard nozzle IDs and lengths available.



Single Flute Double Flute Reamer Blades Reamer Blades

#### **TESTING & DIAGNOSTIC BOX**

The Torch Wizard® Reaming Station
Test Box is a recommended
maintenance peripheral for
periodically testing and fine tuning
your reaming station. Functions
include: Sink/Source, Motor Slide
Up/Down, Nozzle Clamp, Anti-spatter
Spray and Wire Cutter (if applicable).
Includes 110v AC unit and cable.
Available for all cleaning station models.





#### TORCH WIZARD° WIRE CUTTER

Features reversible hardened steel blade for long cutting life. Included with AC and ACE models. Standalone model also available.



#### **COBOT GUARDING KIT**

For Reamer and Wire Cutter



## **BLUE MAGIC® INDUSTRIAL ANTI-SPATTER**

## BLUE MAGIC® & TORCH WIZARD® STATIONS — A WINNING COMBINATION!

A cost effective, environmentally safe product, this new generation of anti-spatter provides superb performance even in high temperature applications. Biodegradable formula contains no harmful chemicals and is noncombustible. And, because it contains one of the lowest water contents available, you get protection, not water.

- Surfactants provide excellent wetting and lubricity in torches
- Protects against spatter build-up and char residue
- Keeps clean-ups to a minimum
- ► Contains no silicone easily painted over
- Neutral pH level inhibits multi-metal corrosion
- Will not evaporate, keeping lines and nozzles clog-free
- Contains biocide, providing longer shelf life in warm climates
- Available in concentrated form in 5 gallon buckets or 1 liter bottles
  - One 5 gallon bucket makes 55 gallons of anti-spatter ideal for overseas shipping





**5454K87 (not shown)** 1/4" NPT Bulkhead

Connector for through-wall installations

#### ANTI-SPATTER MULTI-STATION SETUP

▶ Lowers operating costs by allowing the use of bulk anti-spatter, reduces downtime for refilling

Spatter-Resistant Tubing

40021-04 1/4" Ball Valve

- ▶ Supplies anti-spatter to multiple stations with pneumatic pump (pumps up to 1.92 gallons per minute at 75 psi)
- Less space required due to one feeding source

Blue Magic® or Blue Chill® 55 gallon



Spatter-Resistant Tubing

**F** 2001008 1/4" x 1/4" NPT Push-in

### TORCH WIZARD® CLEANING STATIONS & ACCESSORIES

## TORCH WIZARD® ROBOTIC NOZZLE CLEANING STATIONS

Part No.	Description
EL-NCS-A-24	9-Pin Cleaning Station with Integrated Anti Spatter Spray
EL-NCS-A-24-SC	9-Pin Cleaning Station with Integrated Anti Spatter Spray and Self Cleaning
EL-NCS-AC-24	9-Pin Cleaning Station with Integrated Anti Spatter Spray and a Wire Cutter
EL-NCS-AC-24-SC	9-Pin Cleaning Station with Integrated Anti Spatter Spray, Self Cleaning, and a Wire Cutter
EL-NCS-24	9-Pin Cleaning Station for aluminum
EL-NCS-AIO-24	IO-Link Cleaning Station with Integrated Anti Spatter Spray
EL-NCS-AIO-24-SC	IO-Link Cleaning Station with Integrated Anti Spatter Spray and Self Cleaning
EL-NCS-ACIO-24	IO-Link Cleaning Station with Integrated Anti Spatter Spray and a Wire Cutter
EL-NCS-ACIO-24-SC	IO-Link Cleaning Station with Integrated Anti Spatter Spray, Self Cleaning, and a Wire Cutter
EL-NCS-AE-24	Ethernet Cleaning Station with Integrated Anti Spatter Spray
EL-NCS-AE-24-SC	Ethernet Cleaning Station with Integrated Anti Spatter Spray and Self Cleaning
EL-NCS-ACE-24	Ethernet Cleaning Station with Integrated Anti Spatter Spray and a Wire Cutter
EL-NCS-ACE-24-SC	Ethernet Cleaning Station with Integrated Anti Spatter Spray, Self Cleaning, and a Wire Cutter
EL-NCS-A-TA-24-CL	Cleaning Station with Integrated Anti-Spatter Spray for Tandem Arc Torches with Cloos® Nozzles
EL-NCS-A-TA-24-FR	Cleaning Station with Integrated Anti-Spatter Spray for Tandem Arc Torches with Fronius® Nozzles
EL-NCS-A-TA-24-TR	Cleaning Station with Integrated Anti-Spatter Spray for Tandem Arc Torches with Tregaskiss® Nozzles

#### **TORCH WIZARD® OPTIONAL ACCESSORIES**

Part No.	Description
EL-NCS-STAND-12	12" (305 mm) stand for EL-NCS models
EL-NCS-STAND-20	20" (508 mm) stand for EL-NCS models
EL-NCS-STAND	29.5" (749 mm) stand for EL-NCS models
EL-NCS-STAND-36	36" (914 mm) stand for EL-NCS models
EL-NCS-STAND-48	48" (1,219 mm) stand for EL-NCS models
EL-NCS-STAND-60	60" (1,524 mm) stand for EL-NCS models
EL-NCS-FRL-14	Filter/Regulator/Lubricator
EL-NCS-TB-20	Testing and Diagnostic Box
EL-NCS-TCP-F-R	Tool Center Point Mount (attaches to reaming station stand)
EL-NCS-WCS-12	Integrated Wire Cutter (included on AC models)
EL-NCS-WCS-SA-12	Stand Alone Wire Cutter
EL-NCS-CC9-20-3	9 Pin, 20 ft Power/Control Cable

Custom heights are available for Torch Wizard® stands

#### **TORCH WIZARD® REAMER BLADES**

Part No.	Description	Diameter	Flutes	Thread	Height
EL-NCS-13MM	Reamer Blade	13 mm	2	Female	2.558"
EL-NCS-TL-13MMF	Reamer Blade	13 mm	1	Female	2.687"
EL-NCS-15MM	Reamer Blade	15 mm	2	Female	2.558"
EL-NCS-TL-15MMF	Reamer Blade	15 mm	1	Female	2.697"
EL-NCS-17MM-L	Reamer Blade (ID: .402")	17 mm	2	Female	3.564"
EL-NCS-17MM-1-L	Reamer Blade (ID: .329")	17 mm	2	Female	3.564"
EL-NCS-500	Reamer Blade 🍎	1/2"	2	Female	2.558"
EL-NCS-TL-50F	Reamer Blade 🍎	1/2"	1	Female	2.687"
EL-NCS-TS-50F	Reamer Blade 🍎	1/2"	1	Female	2.433"
EL-NCS-625	Reamer Blade 🍎	5/8"	2	Female	2.558"
EL-NCS-TL-62F	Reamer Blade 🦸	5/8"	1	Female	2.687"
EL-NCS-TS-62F	Reamer Blade 🧳	5/8"	1	Female	2.433"
EL-NCS-750	Reamer Blade 🍎	3/4"	2	Female	2.558"

The reamer blade required is based on the I.D. of the gas nozzle being used.

Blades compatible with PowerBall® Torch Consumables

#### **BLUE MAGIC® ANTI-SPATTER**

Part No.	Description
EAS1000-C32	32 oz Spray Bottle
EAS1000-C1	1 gal Bottle
EAS1000-C5	5 gal Container
EAS1000-C	55 gal Drum
EAS1000-CT	275 gal Bulk Tote
EAS1000-C-CON-1L	1 l (33 oz) Concentrate
EAS1000-C-CON-5	5 gal Concentrate
EAS1000-DP	Manual Drum Pump (55 gal)

#### **BLUE MAGIC® HD HIGH DUTY CYCLE ANTI-SPATTER**

Specially formulated for extremely high temperature, long duty cycle applications

Part No.	Description
EAS1000-HDC32	32 oz Spray Bottle
EAS1000-HDC1	1 gal Bottle
EAS1000-HDC5	5 gal Container
EAS1000-HDC	55 gal Drum
EAS1000-BCT	275 gal Bulk Tote



