



### MAX

### SLOTTED



The ONLY Heavy Duty Welding Table with the modular, reversible plate design. This affordable modular Fixturing system gives you unlimited possibilities so you can improve current processes and take on new and complex projects to expand and grow your business.

#### Tabletop Size

3.0 × 1.5 M
2.4 × 1.2 M
2.0 × 1.0 M
1.5 × 1.0 M
1.2 × 1.2 M

Plate Thickness	25 ±0.06 mm
Tabletop Flatness	±0.064 mm per 600 mm area
Tabletop Height	200 mm
Hole Diameter	28 mm
Hole Spacing	100 mm
Tabletop Hardness	Top: HV750 Side: HV550



The Alpha 5-sided table systems are combined with our patent-exclusive, reversible, and replaceable tabletop plates. Each plate can be reconfigured to expand the width of the table to accommodate larger projects. Alpha tables allow you to increase quality, consistency, and productivity while also reducing scrap and setup times for repeating jobs.

#### Tabletop Size

120" × 60"
96" × 48"
72" × 48"
72" × 36"
48" × 48"

Plate Thickness	0.47" ±0.004
Tabletop Flatness	±0.005 per 24"
Tabletop Height	6 inches
Hole Diameter	0.625" ±0.002
Hole Spacing	2 inches
Tabletop Hardness	HV550



BuildPro MAX tables have a continuous tabletop surface design and feature 33% more CNC machined boreholes compared to a BuildPro Slotted table. You can set up large, heavy-duty, and complex fixtures or set up more than one fixture at a time. The additional boreholes allow for better clamping point options and offer improved versatility.

#### Tabletop Size

96" × 48"
72" × 48"
60" × 36"
48" × 48"

Plate Thickness	0.63" ±0.004
Tabletop Flatness	±0.005 per 24"
Tabletop Height	6¼ inches
Hole Diameter	0.625" ±0.002
Hole Spacing	2 inches



BuildPro Slotted table tops are constructed from 5/8" thick steel plates and feature a 1.7" slot between plates. Top plates are CNC machined with Ø5/8" boreholes that are equally spaced on a 2" grid pattern. All Slotted tables feature patented reversible and self-locating tabletop plates.

#### Tabletop Size

96" × 46"
78" × 46"
78" × 36"
47" × 46"
47" × 38"
22" × 38"

Plate Thickness	0.63" ±0.004
Tabletop Flatness	±0.005 per 24"
Tabletop Height	6¼ inches
Hole Diameter	0.625" ±0.002
Hole Spacing	2 inches



It's a jungle out there... be ready to handle any build, repair, or assembly job with the Rhino Cart mobile working station. The Rhino Cart allows you to quickly clamp down on a workpiece at any point on the surface of the tabletop using the CNC machined Ø5/8" boreholes. Each cart also features a convenient storage area below the tabletop for tool storage and organization. Additional attachments like the tube notcher and plasma cutting tray are available that further expand the Rhino Cart's capabilities.

#### Tabletop Size

48" × 30"
-----------

Plate Thickness	0.63" ±0.004
Tabletop Flatness	±0.005 per 24"
Static Load Cap.	1,500 lbs.
Hole Diameter	5/8"
Hole Spacing	2 inches



**MAX**

**SLOTTED**



**Tabletop Size**

3.0 × 1.5 M

2.4 × 1.2 M

2.0 × 1.0 M

1.5 × 1.0 M

1.2 × 1.2 M

**Leg Options**

650 mm H Leg

500 mm H Leg

400 mm H Leg

500-900 mm H + Adjustable Leg

550-750 mm H  
Adjustable Leg + Caster

600 mm H Leg + Caster



**Tabletop Size**

120" × 60"

96" × 48"

72" × 48"

72" × 36"

48" × 48"

**Leg Options**

28" Heavy Duty Leg

22" Heavy Duty Leg

22.3 ~ 32.3" Adjustable Leg

27 ~ 37" Adjustable Leg



**Tabletop Size**

96" × 48"

72" × 48"

60" × 36"

48" × 48"

**Leg Options**

28" Heavy Duty Leg

22" Heavy Duty Leg

22.3 ~ 32.3" Adjustable Leg

27 ~ 37" Adjustable Leg



**Tabletop Size**

96" × 46"

78" × 46"

78" × 36"

47" × 46"

47" × 38"

22" × 38"

**Leg Options**

28" Heavy Duty Leg

22" Heavy Duty Leg

22.3 ~ 32.3" Adjustable Leg

27 ~ 37" Adjustable Leg



PART NO.	DESCRIPTION
TD5-4830Q-K1	Rhino Cart + 66 Piece Fixture Kit
TD5-4830Q-F1	Rhino Cart
TD5-4830Q	Tabletop Only
TD5-4830Q-N	Tabletop + Frame
TPL3021	Plasma Cutting Tray
TPLK3021	Replacement Slats


**ALPHA 28 LEGS**

**ALPHA 5/8, MAX & SLOTTED TABLE LEGS & ACCESSORIES**



**HEAVY DUTY LEGS**  
These legs feature steel leveling pads to ensure proper leveling of your table on uneven surfaces.

Leg Height	28"	22"
Leg Height + Leveling Pad	30.3"	24.3"



**ADJUSTABLE LEGS**  
These dynamic legs are adjustable at 1" increments. They have a telescoping adjustable range (L) from 20" to 30."

Leg Height	20 ~ 30"	20 ~ 30"
Leg Height + Leveling Pad	22.3 ~ 32.3"	27 ~ 37"

