

# MAGNUM™



**2017**  
**RESIDENTIAL**

## MODELS:

- 2450KW** 24hp, 50" Deck
- 2550KO** 25hp, 50" Deck
- 2460KW** 24hp, 60" Deck
- 2560KO** 25hp, 60" Deck



Magnum 2560KO model shown\*

## COMMERCIAL QUALITY AT A RESIDENTIAL PRICE.

The **Magnum** is the highest quality residential mower in the market, packing speed, power, and performance in a compact sized zero-turn mower.

- **X2 Cutting System** – Offered in two cutting widths (50" and 60"), the X2 Deck combines X-Blade Technology with the industry leading 2 inches of blade overlap to ensure every blade of grass is cut cleanly.
- **Hydro-Gear® Transaxles** – With proven reliability and performance, Hydro-Gear® ZT-3200 series transaxles feature an external oil filter for easier maintenance and extended operating life expectancy.
- **High Horsepower** – Choose from a 24 horsepower Kawasaki® engine or a 25 horsepower engine from Kohler® to tackle your toughest mowing jobs.
- **Mulching Effect** – Add a Twist blade to the existing X-Blade to boost mulching performance.
- **Upgrades Available** – Accessorize your Magnum by adding the patented OCDC (Operator Controlled Discharge Chute), a set of Springer Forks, suspension seat, mulch kit, striping kit, or PECO® bagger.



**Fuel Sight** – Check how much fuel is left in the tank without removing the cap.



### DUAL BLADES

**X-Blade Technology** – Add a Twist blade for mulching effect.



**Hydro-Gear® ZT-3200** – Smooth operation and fully serviceable.



**Heavy-Duty Spindles** – Tried and true design for over 25 years.



**50" and 60" X2 Cutting System** – X-Blade Technology with 2" blade overlap.



\*unlimited hour limited residential warranty

\*Actual production model may vary

765.246.7737 | [www.dixiechopper.com](http://www.dixiechopper.com)



	50" Deck		60" Deck	
Model	2450KW	2550KO	2460KW	2560KO
<b>Engine</b>				
Manufacturer	Kawasaki® FR	Kohler® Confidant	Kawasaki® FR	Kohler® Confidant
Horsepower	24	25	24	25
Displacement	726cc	724cc	726cc	724cc
Air-cleaner	2 stage			
Cooling	Air cooled			
Starter	Electric			
Engine warranty	3 Year			

<b>Drive System</b>	
Dual hydrostatic	Hydro-Gear® ZT-3200
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

<b>Mower Deck</b>	
Deck size	50"   60"
Acres/hour	3.2   3.9
Cutting height	1.5" - 4.5"
OCDC (operator controlled discharge chute)	Optional
Deck height adjustments	Manual lift, 1/4" increments
Electric lift	Optional
Deck engagement	Ogura® 150 ft-lbs
Construction	10 ga formed & welded
Top plate	7 ga bolted (not welded)
Blades	3 - 17.875" x 2.5"   3 - 21.375" x 2.5"
Blade tip speed (approximate)	17,875 fpm   18,200 fpm
Spindles	1.25" effective diameter machined shaft
Spindle housings	Serviceable cast iron
Anti-scalp rollers	4
Pulleys	Vented split 3/16" steel deep groove

<b>General</b>	
Battery	12 Volt, 300cca
Digital display	Tachometer & hour meter
Fuel capacity	8 gallons
Rear tires	23 x 10.5-12 GrassMaster
Front tires	13 x 6.5-6
Frame	Welded 2" x 2" tube, 7 ga formed
Fenders	Stainless steel
Floor-pan	Flip-up, steel
Seat	20" high-back padded seat w/ armrest, suspension springs
Springer Forks	Optional

<b>Dimensions</b>	
Overall height	49"
Overall width (with chute)	61"   71"
Overall length	80"
Weight	730 lbs   750 lbs