



MODELS: 2244KW 22hp, 44" Deck 2250KW 22hp, 50" Deck 2750KOE 27hp, 50" Deck 2460KW 23.5hp, 60" Deck 2760KOE 27hp, 60" Deck

2017 LIGHT-COMMERCIAL

## HEAVY-DUTY FEATURES AT A SURPRISINGLY AFFORDABLE PRICE.

The **Magnum HP** provides the best of both worlds: the durability of a commercial mower at a surprisingly non-commercial price point. Highlights include:

- **Proven Power** Equipped with the industry preferred Kawasaki<sup>®</sup> FX and Kohler<sup>®</sup> EFI Confidant engines for trusted reliability and performance.
- **X2 Cutting System** Offered in three cutting widths (44", 50", and 60"), the X2 Deck combines X-Blade Technology with the industry leading 2 inches of blade overlap to ensure every blade of grass is cut cleanly.
- **Commercial Transmissions** The Hydro-Gear<sup>®</sup> ZT-3400 series transaxles are designed for heavy-duty commercial applications and feature an external oil filter for easier maintenance.
- **Complete Discharge Control** Our operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly.
- **Total Comfort** The 23" high-back deluxe seat keeps you comfortable all day long with an extra plush cushion design.





**OCDC** – Open and close the discharge chute on command.



Hydro-Gear<sup>®</sup> ZT-3400 – Commercialgrade transaxle with serviceable filter.



**44", 50", and 60" X2 Cutting System** – X-Blade Technology with 2" blade overlap.



Magnum 2250KW shown\*

Foldable ROPS – Keep the operator safe when accessing hillsides.



Heavy-Duty Spindles – Tried and true design for over 25 years.



\*up to 500 hour limited warranty



	44" Deck	50" Deck		60" Deck	
Model	2244KW	2250KW	2750KOE	2460KW	2760KOE
Engine					
Manufacturer	Kawasaki® FX		Kohler <sup>®</sup> EFI	Kawasaki <sup>®</sup> FX	Kohler <sup>®</sup> EFI
Horsepower	22		27	23.5	27
Displacement	726сс		747cc	726cc	747cc
Air-cleaner	2 stage				
Cooling	Air cooled				
Starter	Electric				
Engine warranty	3 Year				

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-3400
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

Mower Deck				
Deck size	44"	50 "	60 "	
Acres/hour	2.8	3.2	3.9	
Cutting height	1.5" - 4.5"			
<b>OCDC</b> (operator controlled dis- charge chute)	Standard			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura® 150 ft-lbs			
Construction	10 ga formed & welded			
Top plate	7 ga bolted (not welded)			
Blades	3 - 17" x 2.5"	3 - 17.875" x 2.5"	3 - 21.375" x 2.5"	
Blade tip speed (approximate)	17,875 fpm 17,399 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Serviceable cast iron			
Anti-scalp rollers	2 4			
Pulleys	Vented split 3/16" steel deep groove			

General				
Battery	12 Volt, 300cca			
Digital display	Tachometer & hour meter			
Fuel capacity	8 gallons			
Rear tires	23 x 10.5-12 GrassMaster			
Front tires	13 x 6.5-6			
Frame	Welded 2" x 2" tube, 7 ga formed			
Fenders	Stainless steel			
Floor-pan	Flip-up, steel			
Seat	23" high-back adjustable padded seat w/ armrest, suspension springs			
Springer Forks	Optional			

Dimensions						
Overall height	49"					
Overall height (rollbar up)	74"					
Overall width	49"	55 "	65 "			
Overall length	80"					
Overall length (rollbar down)	87"					
Weight	824 lbs	844 lbs	924 lbs			



765.246.7737 www.dixiechopper.com