

BLACK HAWK™



MODELS:

2248KW 22hp, 48" Deck

2454KW 24hp, 54" Deck

2554BR 25hp, 54" Deck

2460KW 24hp, 60" Deck

2560BR 25hp, 60" Deck

2017

LIGHT-COMMERCIAL

NEW



BlackHawk 2560BR shown*

REDEFINE YOUR MOWING EXPERIENCE.

The new **BlackHawk** provides the ultimate mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- **Foot-Operated OCDC** – Our new foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- **Proven Power** – Equipped with the industry preferred Kawasaki® FS or Briggs & Stratton® Cyclonic engines for trusted reliability and performance.
- **V6 Cutting System** – Offered in three cutting widths (48", 54", and 60"), the V6 Deck features a deep 7 gauge shell to handle more volume and produce more vacuum.
- **Smoothest Steering** – The Parker® HTE series transmissions offer super smooth steering up to 9 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** – The high-back, padded, and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer® Turf Xtreme™ Spindles** – Maintenance free and constructed of high-strength ductile iron.


*Actual production model may vary



OCDC – Foot-operated to keep your hands on the steering levers




Hitch Receiver – Class 1 hitch for easier mounting of accessories



Parker® HTE – Smooth steering and 1000 hour oil change intervals



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



48", 54", and 60" Decks – Deep 7 gauge shell to tackle deep grass with ease

4 YEAR
BUMPER-TO-BUMPER
WARRANTY*

*up to 750 hour limited warranty

765.246.7737 | www.dixiechopper.com



	48" Deck		54" Deck		60" Deck	
Model	2248KW	2454KW	2554BR	2460KW	2560BR	
Engine						
Manufacturer	Kawasaki® FS		Briggs & Stratton® Cyclonic®	Kawasaki® FS	Briggs & Stratton® Cyclonic®	
Horsepower	22	24	25	24	25	
Displacement	726cc		724cc	726cc	724cc	
Air-cleaner	2 stage		5 stage	2 stage	5 stage	
Cooling	Air cooled					
Starter	Electric					
Engine warranty	3 Year					

Drive System	
Dual hydrostatic	Parker® HTE
Ground speed	9 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

Mower Deck	
Deck size	48" 54" 60"
Acres/hour	3.4 3.9 4.3
Cutting height	1" - 5"
OCDC (operator controlled discharge chute)	Foot-operated (standard)
Deck height adjustments	Manual lift, 1/4" increments
Electric lift	Optional
Deck engagement	Ogura® 150 ft-lbs with SoftStart
Construction	7 ga formed & welded
Blades	(3) -2.5" x 17.25" (3) - 2.5" x 19" (3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,398 fpm 18,257 fpm 18,541 fpm
Spindles	1" effective diameter machined shaft
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)
Anti-scalp rollers	4
Pulleys	7 ga steel deep groove

General	
Battery	12 Volt, 350cca
Digital display	Tachometer, hour meter, fuel gauge
Fuel capacity	6.8
Rear tires	23 x 10.5-12 GrassMaster
Front tires	13 x 6.5-6
Frame	Welded C-channel, 7 ga formed
Floor-pan	Removable, steel
Seat	24" high-back adjustable padded seat w/ armrest, suspension springs
Springer Forks	Optional accessory

Dimensions	
Overall height (rollbar down)	50"
Overall height (rollbar up)	71"
Overall width (chute down)	63.6" 69.6" 76"
Overall width (chute up)	49.2" 55.4" 61.9"
Overall length (rollbar down)	85.8"
Overall length (rollbar up)	81.3"
Weight	1104 lbs 1114 lbs 1118 lbs 1121 lbs 1138 lbs