BLACKHAWK HP



MODELS:

2248KW 22hp, 48" Deck **2548KOE** 25hp, 48" Deck **2454KW** 23.5hp, 54" Deck **2554KOE** 25hp, 54" Deck **2460KW** 23.5hp, 60" Deck

2560KOE 25hp, 60" Deck

2017

LIGHT-COMMERCIAL





The **BlackHawk HP** provides the superior mowing experience with advanced operator controls, commercial grade components, and unmatched performance and comfort.

- InCommand™ Console Full control at your fingertips. Features a keyless ignition, blade and job timer, tachometer, fuel gauge, and SoftStart clutch engagement.
- Foot-Operated OCDC Our new foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge
- **Proven Power** Equipped with the industry preferred Kawasaki® FX and Kohler® EFI engines for trusted reliability and performance.
- Smoothest Steering The Parker® HTJ series transmissions offer super smooth steering up to 10 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** Full suspension with high-back padded design provides lateral stability and ultimate comfort.
- Peer® Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.



InCommand™ Console – Keyless ignition, SoftStart clutch engagement, and more



BlackHawk HP 2560KOE shown*

OCDC - Foot-operated to keep your hands on the steering levers



Parker® HTJ - Smooth steering and 1,000 hour oil change intervals



ultimate comfort all day long



48", 54", and 60" Decks - Deep 7 gauge shell to tackle deep grass with ease



*up to 750 hour limited warranty

^{*}Actual production model may vary



	48" Deck		54" Deck		60" Deck	
Model	2248KW	2548KOE	2454KW	2554KOE	2460KW	2560KOE
Engine						
Manufacturer	Kawasaki® FX	Kohler [®] Confidant EFI	Kawasaki® FX	Kohler® Confidant EFI	Kawasaki® FX	Kohler® Confidant EFI
Horsepower	22	25	23.5	25	23.5	25
Displacement	726cc	747cc	726cc	747cc	726cc	747cc
Air-cleaner	2 stage					
Cooling	Air cooled					
Starter	Electric					
Engine warranty	3 Year					

Drive System				
Dual hydrostatic	Parker® HTJ			
Ground speed	10 mph			
Parking brake	Integrated in transaxle			
Towing capacity	200 lbs			

Mower Deck					
Deck size	48"	54"	60"		
Acres/hour	3.8	4.3	4.8		
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Foot-operated (standard)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Ogura® 150 ft-lbs with SoftStart				
Construction	7 ga formed & welded				
Blades	(3) - 2.5" x 17.25"	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"		
Blade tip speed (approximate)	18,398 fpm	18,257 fpm	18,541 fpm		
Spindles	1" effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	7 ga steel deep groove				

General				
Battery	12 Volt, 350cca			
Digital display	InCommand™ Console - Tachometer, hour meter, blade timer, fuel gauge, and ignition			
Fuel capacity	6.8			
Rear tires	23 x 10.5-12 GrassMaster			
Front tires	13 x 6.5-6			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrest			
Springer Forks	Optional accessory			

Dimensions						
Overall height (rollbar down)	50 "					
Overall height (rollbar up)	71 "					
Overall width (chute down)	63.6"		69.6"		76"	
Overall width (chute up)	49.2"		55.4"		61.9"	
Overall length (rollbar down)	85.8"					
Overall length (rollbar up)	81.3"					
Weight	1116 lbs	1121 lbs	1132 lbs	1138 lbs	1140 lbs	1144 lbs

