LIASSIC



MODELS:

2750KW 27hp, 50" Deck **2760KW** 27hp, 60" Deck **3160KW** 31hp, 60" Deck **3160KOE** 31hp, 60" Deck **3572KW** 35hp, 72" Deck **3572KOE** 35hp, 72" Deck **3672BR** 36hp, 72 " Deck



POWER THROUGH COMMERCIAL CUTS QUICKER AND EASIER.

The **Classic** is the ultimate moving machine with the perfect combination of commercial quality with industrial features.

- Power and More Power Choose from a Kawasaki® FX or Kohler® EFI engine up to 35 horsepower, or a 36 horsepower Vanguard® engine to power through the tough jobs with ease.
- Lifetime Warranty Frame The strongest frame in the industry with a 1"x 2" 7 gauge steel construction guaranteed not to break.
- Over-Sized Hydraulics Reduces the system pressure within the components to extend drivetrain life expectancy.
- Complete Discharge Control An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly.
- Tried and True Decks Offered in three deck widths (50", 60", and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- Comfort Package Our suspension seat and unique Springer Forks comes standard on select Classic models to provide a smooth ride in all terrain.



High Performance Package - Comes standard on select models



Pumps & Wheel Motors - Stronger transmissions for extended system life.



50", 60", and 72" Elite X Deck -Gives a quality cut in all types of grass



OCDC - Open and close the discharge chute on command



Spindle Fans - Cleans the top of the deck and keeps spindles and belts cool.



*up to 600 hour limited warranty

^{*}Actual production model may vary



| | 50" Deck | ' Deck 60" Deck | | 72" Deck | | | |
|-----------------|--------------|-----------------|--------|-------------|--------------|-------------|-----------|
| Model | 2750KW | 2760KW | 3160KW | 3160KOE | 3572KW | 3572KOE | 3672BR |
| Engine | | | | | | | |
| Manufacturer | Kawasaki® FX | | | Kohler® EFI | Kawasaki® FX | Kohler® EFI | Vanguard® |
| Horsepower | 27 | | 31 | | 35 | | 36 |
| Displacement | 852cc | | 999сс | 824cc | 999cc | | 993cc |
| Air-cleaner | 2 stage | | | | | | |
| Cooling | Air cooled | | | | | | |
| Starter | Electric | | | | | | |
| Engine warranty | 3 Year | | | | | | |

| Drive System | | | | |
|-----------------|-----------------------------------|---------------|--|--|
| Pumps | Hydro-Gear® 16cc Hydro-Gear® 21cc | | | |
| Wheel motors | Parker® DG280 | Parker® DG335 | | |
| Ground speed | 12 mph | 13 mph | | |
| Parking brake | Automotive Style | | | |
| Towing capacity | 2000 lbs | | | |

| Mower Deck | | | | | | |
|--|--|------------------|----------------|--|--|--|
| Deck size | 50" | 60" | 72" | | | |
| Acres/hour | 4.8 | 5.8 | 7.5 | | | |
| Cutting height | 1.5" - 5" | | | | | |
| OCDC (operator controlled discharge chute) | Standard | | | | | |
| Deck height adjustments | Manual lift, 1/4" increments | | | | | |
| Electric lift | Optional | | | | | |
| Deck engagement | Ogura® 250 ft-lbs | | | | | |
| Construction | 10 ga formed & welded 7 ga formed & welded | | | | | |
| Top plate | 7 ga bolted (not welded) | | | | | |
| Blades | 3 - 17" x 2.5" | 3 - 20.5" x 2.5" | 3 - 24" x 2.5" | | | |
| Blade tip speed (approximate) | 18,800 fpm | 17,143 fpm | 17,637 fps | | | |
| Spindles | 1.25" effective diameter machined shaft | | | | | |
| Spindle housings | 1pc keyless sealed cast iron | | | | | |
| Spindle cooling fans | 3 | | | | | |
| Anti-scalp rollers | 4 5 | | | | | |
| Pulleys | Vented split 3/16" steel deep groove | | | | | |

| General | | | | | |
|-----------------|---|---------------------------------|--|--|--|
| Battery | 12 Volt, 350cca | | | | |
| Digital display | Tachometer, voltmeter, service alerts | | | | |
| Fuel capacity | 8 gallor | 8 gallons 10 gallons 12 gallons | | | |
| Rear tires | 25 x 12-9 GrassMaster | 25 x 12-12 GrassMaster | | | |
| Front tires | 15 x 6-8 | | | | |
| Frame | Welded 1" x 2" tube, 7 ga formed | | | | |
| Fenders | Stainless steel | | | | |
| Floor-pan | Removable, steel | | | | |
| Seat | Full suspension, adjustable seat w/ armrest | | | | |
| Springer Forks | Optional Standard | | | | |

| Dimensions | | | | | |
|-------------------------------|----------|----------|----------|----------|--|
| Overall height | 53" | | | | |
| Overall height (rollbar up) | 78" | | | | |
| Overall width | 55.5" | 65.5" | | 76" | |
| Overall length | 77.5 | 5" 78" | | 79" | |
| Overall length (rollbar down) | 81" | | | 83" | |
| Weight | 1074 lbs | 1134 lbs | 1228 lbs | 1425 lbs | |

