



ZT400[™]

Dependable Performance. Professional Results.

The new Jacobsen **ZT400** series delivers the productivity, quality, and reliability expected with over 95 years of industry leading turf innovation.

- High Horsepower Features powerful engines from Briggs & Stratton® and Kawasaki® to power you through up to 4.3 acres per hour.
- Cutting System Offered in three cutting widths (48-, 54- and 60-inch), the deep deck easily tackles large volumes of grass and provides a more attractive after-cut appearance.
- Proven Drivetrain Parker® HTE transmissions provide smooth, reliable steering and are up to 15% more fuel efficient than the competition.
- Robust Deck Spindle The Turf Xtreme™ spindles are maintenance-free and provide longer bearing life with Contamination Exclusion Technology. The high-strength ductile iron is 60% stronger than aluminum housings.
- Optional Accessories Add an electric deck lift for easy deck height adjustments, a foot-operated Operator Controlled Discharge Chute for opening and closing the discharge chute on the fly, springer forks or a suspension seat for a smoother ride.

ZT400 MODELS:

2248KW: 22 hp, 48-inch Deck 2454KW: 24 hp, 54-inch Deck **2554BR:** 25 hp, 54-inch Deck 2460KW: 24 hp, 60-inch Deck **2560BR:** 25 hp, 60-inch Deck

*Actual production model may vary.






InCommand™ Console -Keyless ignition, SoftStart clutch engagement, and more



Parker® HTE - Smooth and efficient transmissions with 1,000 hour oil change intervals



PEER® Spindles – Sealed with Contamination Exclusion Technology for reliable performance expectancy up to three times



PerfectTension™ – Optimal belt tension to increase belt life



SPECIFICATIONS

Zero-Turn Rotary Mower

	48-inch Deck 54-inch Deck		h Deck	60-inch Deck	
Model	2248KW	2454KW	2554BR	2460KW	2560BR
Engine	<u> </u>	<u>'</u>	<u>'</u>		<u>'</u>
Manufacturer	Kawasaki® FS		Briggs & Stratton® Commercial Turf®	Kawasaki® FS	Briggs & Stratton® Commercial Turf®
Horsepower	22 hp	24 hp	25 hp	24 hp	25 hp
Displacement	72	6cc	724cc	726cc	724cc
Air-cleaner	2 stage		5 stage	2 stage	5 stage
Cooling			Air cooled		
Starter	Electric				
Engine warranty			3 Year		
Drive System					
Dual hydrostatic	Parker® HTE				
Ground speed	9 mph				
Parking brake	Integrated in transaxle				
Towing capacity	200 lbs				
Mower Deck					
Deck size	48 in 54 in		60 in		
Acres/hour	3.4	3.9		4.3	
Cutting height	1 in - 5 in				
OCDC (operator controlled	Foot-operated (optional)				
discharge chute)					
Deck height adjustments	Manual lift, 1/4 in increments				
Electric lift	Optional				
Deck engagement	Ogura® 150 ft-lbs				
Construction		1	7 ga formed & welded	T (2) 2.5; 22.5;	
Blades	(3) -2.5 in x 17.25 in	(3) - 2.5 in x 19 in		(3) - 2.5 in x 20.5 in	
Blade tip speed (approximate)	18,398 fpm 18,257 fpm 18,541 fpm				11 tpm
Spindles	1.25 in effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys			7 ga steel deep groove		
General					
Battery	12 Volt, 350cca				
Digital display	InCommand™ Console - Tachometer, hour meter, blade/job timer, fuel gauge, engine warnings, ignition				
Fuel capacity	6.8				
Rear tires	23 x 10.5-12 GrassMaster				
Front tires	13 x 6.5-6				
Frame	Welded C-channel, 7 ga formed				
Floor-pan	Removable, steel				
Seat	Deluxe (non-suspension) adjustable seat w/ armrest, suspension springs				
Springer Forks			Optional accessory		
Dimensions			EC.		
Overall height (rollbar down)	50 in				
Overall height (rollbar up)		71 in			
Overall width (chute down)	63.6 in		6 in	76 in	
Overall width (chute up)	49.2 in	55.4 in 61.9 in			
Overall length (rollbar down)	85.8 in				
Overall length (rollbar up)		1	81.3 in		
Weight	1104 lbs	1114 lbs	1118 lbs	1121 lbs	1138 lbs

Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.





^{*}Acres/hour at top speed and 80% efficient