

Solitaire PTK 362 PTZ Camera

Capture every angle seamlessly with Solitaire's PTZ camera for unparalleled visual clarity and versatility



1080P 30FPS



4 Mic Array



Speaker Out



20X Optical
Zoom



10 Meters
Voice Pickup



Voice
Tracking

Tracks The Voice

Camera automatically rotates 360° and tracks the voice then the speaking person appears automatically



2.0 Million Pixels

1/2.8" FHD COLOR CMOS



10 Meters Far Field Voice Pickup

4 Digital Microphones Array and 10 meters voice pickup



The Solitaire PTK 362 PTZ camera offers an impressive 10 meters far-field voice pickup capability, ensuring clear and crisp audio capture even in larger spaces. With its advanced technology, this camera delivers unparalleled voice clarity, making it ideal for conferences, classrooms, and boardrooms alike. Whether you're presenting, teaching, or collaborating, the Solitaire PTK 362 PTZ camera ensures that every voice is heard with exceptional precision, enhancing communication and productivity in any setting.

20X Optical Zoom



0X optical zoom



12X optical zoom



20X optical zoom



Auto Focus

Input / Output Ports



Computer



Television
(or projector & display)

Compatible With All VC Platform



Compatible Systems



Long Distance Remote Control Function



Experience seamless long-distance control with Solitaire's advanced remote, empowering users to effortlessly navigate and manage their devices from afar with precision and ease

4 MIC Array, Tilt & Pan Rotation



Tilt Rotation -30° to +90°



Pan Rotation -170° to +173°

Application Scenarios



Video conference



Live Broadcasting



Live Streaming



Hybrid Classrooms

The Solitaire PTK-362 PTZ camera stands as the ultimate solution for a multitude of applications, including video conferencing, hybrid classrooms, classroom recording, live streaming, YouTube video recording, and live broadcasting. With its versatile functionality and high-performance capabilities, this camera seamlessly adapts to various settings, ensuring exceptional video quality and reliable performance. Whether facilitating virtual meetings, capturing engaging classroom lectures, streaming live events, or creating professional-grade content for online platforms, the Solitaire PTK-362 PTZ camera delivers unparalleled versatility and reliability, empowering users to elevate their communication and content creation endeavors effortlessly.

Product Specification: Solitaire PTK 362

Camera, Lens parameters	Image Sensor	1/2.8inch CMOS
	Min Lux	0.1Lux(F1.2)
	Effective Pixel	2.2 MP
	Zoom	20X Optical
	Shutter Speed	1 to 1/10000s
	Field of View	61° (W) ~ 3.64° (T)
	Frame Rate	1920×1080, 1280×720, 640×480
	Focus Mode	Auto
	Aperture Mode	Auto
	Backlight Compensation	Support
	Wide Dynamic	Support
	Picture Adjustment	Brightness, Chroma, Saturation, Contrast, Acutance
Microphone parameters	MIC Array Quantity	4
	MIC Array Form	linear
	Microphone Spacing	45.8mm
	Sampling Rate	16KHz/48KHz
	Sensitivity	-26dBfs
	Far-field Pick up Voice Distance	0-10meters
	Horizontal Voice Pick up Angle	Horizontal 180°
	SNR	65.5dB
	Communication Mode	full duplex
Interface Parameter	Video Interface	USB3.0 HDMI
	Video Compressed Format	MJPEG/H.264
	Control Interface	RS-232, USB2.0, UVC
	Control Agreement	VISCA/PELCO-D/PELCO-P
	Communicate Baud Rate	2400/4800/9600/11520/19200/38400
	Power Interface	DC-038 power socket (DC12V)
PTZ Parameter	Pan Rotation	-170°~ +173°
	Tilt Rotation	-30°~ +90°
	Horizontal Rotate Speed	0.1~100°/second
	Vertical Rotate Speed	0.1~80°/ second
Other Parameters	Power Adapter	Input AC100V~AC240V Output DC12V/2A
	Decoder	Built in
	Input voltage	DC12V
	Power Consumption	12W(MAX)
	Storage Temperature and Humidity	-10°C ~ +60°C / 20% ~ 95%
	Working temperature and Humidity	-10°C ~ +50°C / 20% ~ 80%
	Operating Environment	Indoor
	Size	180x180x172mm
Weight	1360g	

Disclaimer: Due to product configuration and manufacturing process, actual body size/body weight may vary, please refer to the actual product. The product images in this specification are for illustrative purposes only, may be adjusted and revised in order to match the actual product performance and specifications. In the event that such changes and adjustments are necessary, no special notice will be given. The actual product effect (including but not limited to appearance, color and size) may vary slightly. Please refer to the actual product. In order to provide accurate specifications as far as possible, the text expressions and pictures in this specification may be adjusted and revised in real time. The product specification

solitaire[®]

Interactive Flat Panel Displays & UC Products

www.solitairetech.in

Contact us:

HQ: SUPERTRON ELECTRONICS PRIVATE LIMITED
2, Cooper Lane, Mission Row Extension, Kolkata 700001, WB, India
Manufacturing Unit: G3, Sector 63, Noida 201301, UP, India
Phone No.: +91-120-3584790, +91-120-3645968, +91-120-4166298,
WhatsApp: +91-9818778982, **Toll-Free No.:** 1800-571-6767
Email: Solitaire.Products@supertronindia.com
Website: www.solitairetech.in

