ARTEOR™ WITH NETATMO PRODUCT GUIDE





Contact details

United Kingdom

Great King Street North, Birmingham, B19 2LF

Customer Services: Tel: +44 (0) 345 605 4333 E-mail: legrand.sales@legrand.co.uk

Quotations and Technical Support: Tel: +44 (0) 370 608 9020 E-mail: uk-uisales@legrand.co.uk

Republic of Ireland: Tel: 01 295 9673 Fax: 01 295 4671 E-mail: legrand.sales@legrand.co.uk



La legrand®

Head office (UK and Ireland): Legrand Electric Limited Great King Street North, Birmingham, B19 2LF Tel: +44 (0) 370 608 9000 Fax: +44 (0) 370 608 9004 Website: www.legrand.co.uk 999558 Arteor with Netatmo product guide 03/2021. 1K

In accordance with its policy of continuous improvement, the Company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in this catalogue are for guidance and cannot be held binding on the Company. All contents and design presentation included in this publication are © Legrand Electric Limited. All rights reserved. 2021

Global strength built on local knowledge

Legrand is the global specialist in electrical and digital building infrastructures. Innovation is the driving force behind its development.

With an increasing investment in research and development (circa 5% of sales) and around 3,900 active patents, the Legrand Group is focused on maintaining a high rate of new product launches that present innovative solutions to the market.


CORPORATE SOCIAL RESPONSIBILITY

Legrand's CSR roadmap is a natural extension to the governance and sustainable development approach in which the company has been engaged for many years. The CSR roadmap firmly asserts Legrand's ongoing commitment to sustainable development.

Respect human rights and communities Ensure health, safety and well-being Develop skills [–] Promote equal opportunity and diversity

> Provide sustainable solutions Ensure sustainable procurement _ Act ethically





HOSPITALITY







Clegrand







SMART HOMES made accessible



Arteor with Netatmo forms part of Legrand's Eliot programme. The programme is dedicated to developing sustainable connected solutions that are easy to use and maintain, accessible for everybody and customisable to the users' needs, desires and habits. To enhance the value of any home and make everyday life just that little bit more comfortable and secure.

FEATURES & FUNCTIONS

Introduction	4-5
Lighting control	6-7
Centrally controlled lighting	8
Smart blind control	9
Scenario switches	10-11
Connected socket outlets	12-13
Wired and wireless controls	14-17
Five steps to a connected home	18-19
Smarthome via a smartphone	20-21
Voice control	22-23
Technology meets design	24-25
Smarther with Netatmo - the new connected thermostat	26

PRODUCT SELECTION

Connected gateway	27
Connected wired light switches	28
Connected socket outlets	29
Connected contactor and electricity meter	30
Connected curtain/blind switches	30
Connected wireless controls	31
Connected wireless scene switches	32
Connected wireless curtain/blind controls	33
International support frames and blank modules	33
Stanit in 6 a d too	
Arteor™ surround plate selection chart	34-35

S N N S N S N S

CONNECTED LIVING

LIFE CAN BE THIS SIMPLE

ARTEOR[™] Netatmo

In today's world, digitalisation and networking are simplifying our lives and adding greater convenience. As technology transforms the way we work, communicate, travel and live, it also brings greater complexity. This is why Legrand has sought to make networked digital technology as easy as possible for designers, installers and users.

The result is the Arteor with Netatmo solution, which combines innovative Netatmo smart home technology with Legrand's elegant and modular wiring accessories. Enhancing individual comfort and security in the connected home, it is quick and easy to install and will adapt to changing habits and needs over time.

All functions in an Arteor with Netatmo installation can be controlled on a smartphone or tablet via the Home + Control app, available for Android and iOS devices. The app allows users to conveniently turn individual lights on or off, control blinds, curtains and electrical appliances or trigger more complex scenarios.








THE SMART RADIO SOLUTION

Arteor with Netatmo is a radio-based solution for the connected home. The intelligent products communicate with one another via radio Zigbee (2.4 GHz waveband), meaning there is no need for specific or extensive cabling. The products can be used to create individual solutions for a more customised feel at home.

SIMPLE, ADAPTABLE AND OPEN

Arteor with Netatmo has been designed and developed as a simple solution to make every house more individual, convenient and secure. Simple for designers, who are able to integrate many useful functions without having to provide for complicated cabling. Simple for installers, who are able to install the system without a great deal of effort or specialist knowledge. Simple for users, who will find it convenient to operate, easy to extend and are able to make changes at any time. The Works with Legrand programme and Zigbee 3.0 certification allows the Arteor with Netatmo system to integrate and enhance third-party solutions. Find out more at legrand.co.uk.



Connected wired switch without neutral, with dimmer option see p. 28

Connected wired switch with neutral, with dimmer option see p. 28

Vireless light switch see p. 31

MORE THAN JUST ON OR OFF

With the integrated dimmer function, switches no longer just turn a light on or off, use them to create different lighting moods to suit every occasion. The switches with dimmer option are available with or without a neutral. They are designed for all modern light sources, including dimmable LEDs, which allow a flexible lighting system to help save energy. They can be controlled by one or more wireless light switches offering complete freedom for design and planning, whether it's a new build or renovation project.







CONVENIENT, CONNECTED LIGHTING

Arteor with Netatmo switches with dimmer option have a handy memory level function, so the light comes back on again at the same level of brightness as when it was switched off. For ultimate convenience just use the Home + Control app to create any lighting mood using a smartphone.

Micromodule switch to connect lights with a ceiling box installation, see p. 28



The lighting micromodule is installed in the ceiling box near the light. This makes it possible to transform a conventionally installed light into a convenient connected light, without any need for expensive rewiring.

Wireless flush mounting switch

The wireless switch, which can be installed in the flush mounting box, easily expands the options of a wired lighting system without compromising on aesthetics. See p. 31



CENTRALLY CONTROLLED

LIGHTING OPTIONS



Wireless light switch see p. 31

LIGHTING MANAGEMENT MADE EASY

Compatible with the Arteor with Netatmo and EDMX³ with Netatmo gateways, the CX³ with Netatmo connected latching relay is installed in the electrical enclosure. The connected latching relay can be controlled by either wired mechanical push buttons or wireless light switches. In either case, lighting can be controlled via the Home + Control app or by voice. Whether by individual control, integration into scenarios, or preprogrammed daily or weekly routines that are easy to set up – the choice is there. Energy consumption can also be monitored on the app, helping towards targeted energy savings.



CX³ with Netatmo connected latching relay see p. 28





Connected wired curtain/blind switch see p. 30

Wireless curtain/blind switch see p. 33

The regular opening and closing of curtains and blinds is made much more convenient by Arteor with Netatmo. In addition, the connected curtain/blind switches offer a stop function and level management.



A single wireless control can manage up to 20 wired curtain/blind switches, so that a touch of a button operates whole groups of curtains or blinds in centralised mode, or as part of preprogrammed scenarios. Opt for even more convenience by choosing to control the system using the Home + Control app or virtual assistants.

Flush mounting wireless curtain/blind switch, see p. 33



MORE OPTIONS FOR A MORE PERSONAL TOUCH



(+

(>

Wireless wake up/sleep switch see p. 32

-;0;-

5


For regular everyday situations, scenarios provide time-saving convenience to simplify daily life. The switches have scenarios that are ready for programming and can easily be personalised in the Home + Control app to suit individual needs. For example, users can simply press a switch by the door to open the blinds and turn on the lights when arriving home. Similarly, when leaving the house, one push of a button is enough to close all blinds and turn off the lights.

FOUR CUSTOMISABLE SCENARIOS

The Arteor with Netamo wireless 4 scenes switch allows four individual scenarios to be programmed as the user wishes. The app can be used to assign names as well as specific icons. With configuration made that easy there's no need to worry about changing the scenarios at a later stage. See p. 32



Relaxing evening in



CONNECTED SOCKET OUTLETS

REMOTE CONTROL MADE EASY






Connected switched socket outlet 13 A - 2 gang see p. 29

Connected switched socket outlet 13 A - 1 gang see p. 29

MORE FREEDOM IN PLANNING AND IN USE

Arteor with Netatmo turns socket outlets into smart components of the connected home. This allows any type of electrical appliance to be switched on and off remotely or integrated into individual scenarios. Connected socket outlets are controlled using switches that can be positioned freely on the wall, using the Home + Control app or virtual assistants. In addition, the connected sockets provide useful information about weekly and monthly energy consumption and will send an error message to a smartphone in the event of any problem, so users can take the appropriate action.





A POWERFUL SOLUTION FOR LOADS UP TO 20 A

Using the CX³ with Netatmo connected contactor in combination with the Arteor with Netatmo or EDMX³ with Netatmo gateway, even high-power consuming devices can be operated safely from a distance and integrated into the smart home installation. Whether they are being used to control water heaters or electric vehicle chargers for example, users can rely on the convenience of remote control and preprogrammed processes. Energy consumption can also be monitored on the app, helping towards targeted energy savings.

CX³ with Netatmo connected contactor For specific circuits up to 20 A see p. 30 20AX *: I ON *: AUTO O: 0 OFF

-

legrand

6

1217

FEW COMPONENTS

MORE OPTIONS

The Arteor with Netatmo system consists of a few simple components. A gateway pack or DIN rail gateway needs to be installed to start, along with connected controls which trigger actions such as controlling lights, curtains or blinds and electrical appliances. They manage scenarios, create centralised functions and allow remote control of individual actions.

CONNECTED WIRED PRODUCTS

The wired products are installed in the same way as conventional components and then paired with the wireless switches (which can be positioned anywhere) via the Zigbee 2.4 Ghz waveband. Thanks to the dynamic mesh network, all functions can easily be reconfigured at any time. It is also easy to add extra modules. START




A gateway creates the radio network and the Wi-Fi connection of the connected installation. The gateway pack consists of a Zigbee/Wi-Fi gateway and a home/ away wireless master switch.



The Home + Control app, which can be used to control the system via smartphone and tablet, is available for Android and iOS devices. Download it for free from your usual app stores.






FEW COMPONENTS

MORE OPTIONS


FUNCTIONS



WIRELESS CONTROLS

Wireless light and curtain/blind switches are used to extend the installation and enable individual, group-based or centralised remote control of lighting, curtains and blinds. They can adapt to changes to the installation over time. Wireless scenario controls are used to activate preprogrammed, more complex scenarios that enhance comfort when you wake up in the morning or go to bed at night, leave the house or come home. Additionally, the wireless 4 scenes switch allows four individual scenarios to be programmed.


Wireless devices (battery powered)





EASY INSTALLATION FOR NEW BUILDS AND RENOVATIONS

FIVE STEPS TO A CONNECTED HOME




Once all wired devices are installed and the power is on, all LEDs will light up in red. Press the master switch in the centre and hold for 5 seconds.

The LEDs now light up in green, showing that the network has been created.



Arteor with Netatmo is a radio solution that requires no extra wiring, as it uses the existing infrastructure. This makes it the ideal choice for upgrading an existing installation into a connected home. For new building projects, it offers a range of benefits such as reduced labour time thanks to its simple installation.



To add a wireless switch, press and hold the switch while tapping it three times onto the wired device to be controlled. The LED's blue light indicates that the pairing was successful.

After a short press on the master switch, all LEDs will turn off.

SMARTHOME VIA SMARTPHONE

ADD A TOUCH OF SMARTNESS



The Home + Control app changes everything, not only in terms of control of the smart home but also in terms of its configuration. The app can be used to conveniently configure the entire system, based on individual preferences. Create tailored scenarios, remotely control individual devices and monitor energy consumption.







The same app used by the installer for configuration is also used by the end user to control the entire system. The remote control options it provides are particularly useful. The app displays smart alerts if, for instance, the refrigerator loses power or a light is left on when nobody is home. This allows the user to remotely control the system and act accordingly.



Configuration is based on a set of simple steps



Each room is configured individually



All functions can be set individually



Users can invite each member of their family



Energy consumption can be monitored for individual devices



Enables fast response to faults



Smart alerts reach the user wherever they may be

VOICE CONTROL

ADD A VIRTUAL ASSISTANT



As modern home technology becomes increasingly complex, it also becomes easier to operate. Arteor with Netatmo makes it possible to control functions via virtual assistants. Used in combination with Google Assistant, Amazon Alexa or Apple Siri, the system listens for the command, such as "Turn on the living room lights", and reacts accordingly.



Connected wired and wireless controls for local and remote control, see p. 28, 31-33

EASY TO USE ANY WAY YOU LIKE

Arteor with Netatmo makes it possible to control all connected devices using virtual assistants: Google Assistant, Amazon Alexa and Apple Siri. Voice control enables users to easily switch the lights on or off, run scenarios or set the desired temperature hands-free.



iPhone, iPod and iPad are registered trademarks of Apple Inc, registered in the United States and other countries. HomeKit is a registered trademark of Apple Inc. App Store is a servicemark of Apple Inc. Android, Google, Google Play and the Google Play logo are trademarks of Google LLC. Amazon, Alexa and their associated logos are trademarks of Amazon. Inc. or its subsidiaries.

TECHNOLOGY MEETS DESIGN

ADD A TOUCH OF STYLE



Champagne

NEUTRAL



White



Graphite



Soft Alu



Magnesium



Dark Bronze



Black



Stainless Steel

BRUSHED METAL



Gold Brass



Pink Champagne

REFLECTIVE METAL







Black

Stainless Steel

Gold

MIRROR



Mirror Black





Grey Oak

SIGNATURE

Mirror White



Cube

THE NEW CONNECTED THERMOSTAT Smarther

T

Netatmo

(4)

The Smarther with Netatmo connected thermostat monitors and controls the temperature of the home simply. With the Home + Control app and compatibility with virtual assistants, users have smart management of their home temperature.

 $\overline{\Delta}$

Find out more at legrand.co.uk

The Home + Control app is available on App Store

e Pla

Connected home

connected gateway

Connected installations require a gateway module





5742 09

لو

Support frames and surround plates selection chart p. 34 to 35

Used to create the radio network and the Wi-Fi connection of the connected installation Enables remote control of the home (lighting, blinds and electrical appliances) using a smartphone via the Home + Control app and/or voice control

4121 81

using a virtual assistant

Must be ordered to start any connected installation To be completed by adding individual connected products 2.4 GHz Wi-Fi connection required

Pack	Cat. Nos.	Connected gateway pack	Pack	Cat. Nos.	EMDX ³ with Netatmo DIN rail gateway
		Composition: - 1 flush mounted Zigbee/Wi-Fi gateway Mechanisms supplied with integrated plastic cover and to be equipped with support frames (p. 33) and surround plates (p. 34 to 35) Can be installed in place of an existing product Suitable for flush mounting box with recommended	1	4121 81	moduleFor installation in the electrical panel with DIN rail support $100 - 240 V \sim - 50/60 Hz$ Consumption: 2 W maximum Connection via screw terminals Width: 2.5 x 17.5 mm modules
		depth of 47 mm - 1 home/away wireless master switch with customisable preset life scenes Supplied with integrated plastic cover and multi- standard support frame (with removable fins) To be equipped with 2 module surround plates (p. 34 to 35) Used to create the radio network and to control life scenes Supplied with CR2032 3 V long-life battery for power supply and 2 removable stickers for fixing the control unit on any substrate			
1	5742 09	LED function for low battery indication			
1	5742 27 5742 36	Magnesium			
1	5742 36	Champagne			







Connected home

connected wired light switches

Step 2: Connected products



5742 01

5742 12

Support frames and surround plates selection chart **p. 34 to 35** Used to create a connected home. Requires prior installation of a Netatmo gateway module (p. 27)

Pack Cat. Nos. Connected wired light switches

		Switch with neutral 250 W - 1 module
1 1 1 1	5742 01 5742 20 5742 29 5742 11	Mechanisms supplied with integrated plastic cover and to be equipped with support frames (p. 33) and surround plates (p. 34 to 35) For local or remote control of lighting Can be controlled by one or more wireless light switches or mechanical 2 way switches Compatible with all loads Can be installed in place of an existing switch in a flush mounting box with recommended depth of 47 mm Locator/indicator function can be activated from the Home + Control app Zigbee Certified Product O White Magnesium Champagne Soft Alu
		Switch without neutral 5 - 300 W with dimmer
		option - 2 modules Mechanisms supplied with integrated plastic cover and to be equipped with support frames (p. 33) and
		surround plates (p. 34 to 35) For local or remote ON/OFF or dimming control of
		lighting Can be controlled by one or more wireless light switches
		Dimmer mode and locator/indicator function can be activated from the Home + Control app
		Compatible with all loads: - Dimmable LEDs: 50 W - Halogen with transformer: 300 VA
		- Fluorescent tube: 300 VA - Halogen 230 V \sim and incandescent: 300 W
		Supplied with a bleeder (synthetic load) Memory level function
		Can be installed in place of an existing switch in a flush mounting box with recommended depth of 47 mm
1	5742 02	Zigbee Certified Product
1 1	5742 21 5742 30	Magnesium Champagne
1	5742 12	Soft Alu



5743 40

F



5742 43

4121 70

Home + Control LEGRAND

Pack	Cat. Nos.	Connected wired light switches
		Switch with neutral 150 W with dimmer option - 1 module
		Mechanisms supplied with integrated plastic cover and to be equipped with support frames (p. 33) and surround plates (p. 34 to 35) For local or remote ON/OFF or dimming control of
		lighting Can be controlled by one or several wireless light switches or mechanical push buttons without neon Dimmer mode and locator/ indicator function can be activated from the Home + Control app Compatible with all loads: - Dimmable LEDs: 150 W - Halogen with transformer: 150 VA - Fluorescent tube: 150 VA - Halogen 230 V√ and incandescent 150 W Memory level function Can be installed in place of an existing switch in a
		flush mounting box with recommended depth of 47 mm
1 1 1 1	5743 40 5743 42 5743 43 5743 41	Zigbee Certified Product O White Magnesium Champagne Soft Alu
		Micromodule switch with neutral 300 W
1	5742 43	Used to connect lights with a ceiling box installation Can be controlled by one or more wireless light switches or mechanical push buttons Paired by tapping the wireless control on the micromodule Zigbee Certified Product
		CX ³ with Netatmo connected latching relay
1	4121 70	Can be controlled by standard wired push buttons and/or be combined with Arteor with Netatmo connected wireless switches Self-protected upstream control terminals: no need for protection such as a 2 A circuit breaker or a fuse
		Silent latching relay (< 10 dB) Single pole, 16 A, 100 - 240 V \sim - 50/60 Hz Conforms to standard: IEC/EN 60669-2-1 Allows the user via the Legrand Home + Control app to:
		- Control devices remotely (one-off control or integrated in a scenario with one or more lighting points)
		- Measure and track consumption (kWh) of the controlled circuit
		- Programme devices according to a daily and/or weekly schedule Connection via screw terminals



L¹ legrand

Connected home



Connected home

connected contactor and energy meter

Step 2: Connected products Step 2: Connected products Home + Control LEGRAND 4121 71 4120 15 5742 04 Used to create a connected home. Requires prior installation of a Support frames and surround plates selection chart p. 34 to 35 Netatmo gateway module (p. 27) Used to create a connected home. Requires prior installation of a Pack Cat. Nos. CX³ with Netatmo connected contactor Netatmo gateway module (p. 27) Eler Call 4121 71 Multifunction silent contactor (< 10 dB) 1 Pack Cat. Nos. Connected wired curtain/blind switch 20 A, 100 - 240 V - 50/60 Hz Conforms to IEC/EN 60669-2-1 Mechanisms supplied with integrated plastic cover and to be equipped with support frames (p. 33) and surround plates (p. 34 to 35) Can be used to control (ON/OFF) any type of load remotely (water heater, heating, swimming pool pump, charging socket for an For local and remote control of a 230 V~ curtain/ electric vehicle, etc) Peak/off-peak function blind (open/close/stop functions and level management) Allows the user via the Legrand Home + Control Compatible with blinds with mechanical or electronic - Set the contactor operating mode (peak/off-peak or ON/OFF) according to the nature of the load (water heater or other load) stop, not compatible with radio-controlled curtain/ blind Can be paired with one or more wireless curtain/ blind switches Measure and track consumption (kWh) of the Can be installed in place of an existing curtain/blind controlled circuit switch in a flush mounting box with recommended - Control another single or three phase contactor depth of 47 mm Zigbee Certified Product 1 module - with neutral > 20 A - Directly control electrical appliance up to 4800 W. or motors up to 2400 VA, or sockets for electric 5742 04 vehicles up to 16 A EV 5742 22 Magnesium Self-protected upstream control terminals: no need 5742 31 Champagne for protection such as a 2 A circuit breaker or a fuse 5742 13 Soft Alu Screw terminals Width: 1 x 17.5 mm module Connected wired curtain/blind micromodule **EMDX³** with Netatmo **IP 44** connected energy meter 0676 97 For local and remote control of a 230 V \sim Maximum circuit rating 80 A Supplied with 1 closed current transformer 1 4120 15 curtain/blind (open/close/stop functions and P level management) Allows the user to: Compatible with curtains/blinds with mechanical or electronic stop, not ٩

 Allows the user to:
Measure the total instantaneous power consumption of an alternating single phase circuit
Track the daily/weekly/monthly/annual history of the total consumption of the circuit with

which it is associated (in kWh and as a value) - Send a notification if an adjustable threshold of total instantaneous power is reached $100 - 240 V_{\sim} - 50/60 Hz$ Width: 1 x 17.5 mm module

compatible with radio-controlled curtains/ blinds Can be paired with one or more curtain/blind

To be installed in the ceiling box or curtain/blind box

to connect a new or existing curtain/blind Zigbee Certified Product

Connected home

connected curtain/blind switches

L¹ legrand

Connected home

connected wireless controls

Step 2: Connected products









5742 91



5742 05

Support frames and surround plates selection chart **p. 34 to 35**


Used to create a connected home. Requires prior installation of a Netatmo gateway module (p. 27)

Pack Cat. Nos. Wireless light switches Pack Cat. Nos. Wireless motion sensor IP 44 5742 52 Allows to control up to 20 wired switches, Used to add extra lighting control micromodules and socket outlets Easy pairing by tapping the wired products or by using the Home + Control app Easy pairing by tapping the wired product or by using the Home + Control app Supplied with CR2032 3 V long-life battery for power Supplied with 2 x AA battery subbly For indoor and outdoor use LED function for low battery indication Recommended distance between 2 sensors: 6 m Zigbee Certified Product Recommended installation height: 2.5 m Time delay adjustable from 15 s to 15 min Surface mounting version - 1 gang Supplied with integrated plastic cover, Range: 8 m multi-standard support frame (with removable fins) Detection angle: 140° and 2 removable stickers for fixing the control unit on Sensor range adjustable from 2 m to 8 m any substrate Light level threshold adjustable from 1 to 1000 lux To be equipped with 2 module surround plates Zigbee Certified Product (p. 34 to 35) Controls up to 20 wired products: switches, Wireless switch on/off module micromodules, socket outlets O White 0676 94 Allows to transform a mechanical 2 way 5742 05 1 switch or push button into a wireless on/off switch. Small size for easy 5742 23 Magnesium 1 5742 32 Champagne integration into the wall box 5742 14 Soft Alu 1 To be paired with one connected switch, micromodule, socket outlet Supplied with CR2032 3 V long-life battery for power Surface mounting version - 2 gang Supplied with integrated plastic cover, supply multi-standard support frame (with removable fins) Zigbee Certified Product and 2 removable stickers for fixing the control unit on any substrate To be equipped with 2 module surround plates (p. 34 to 35) Controls up to 2 x 20 wired products: switches, micromodules, socket outlets 5742 44 ○ White 1 5742 46 1 Magnesium Champagne 1 5742 47 5742 45 Soft Alu Flush mounting version - 1 module Mechanism supplied with integrated plastic cover and to be equipped with support frames (p. 33) and surround plates (p. 34 to 35) Controls up to 20 wired products: switches, micromodules, socket outlets Can be installed in a flush mounting box, in addition to wired products with recommended depth of 47 mm ○ White 1 5742 91 5742 76 Magnesium 1 5743 26 Champagne 1 5742 75 Soft Alu

L¹ legrand

Connected home

connected wireless scene switches




Connected home

connected wireless curtain/blinds controls

Arteor[™]

international support frames and blank modules



Clegrand

Arteor[™] surround plate selection charts

60.3 mm fixing centres - flush mounting boxes, support frames and surround plates

								{	SURROUN		LATES					
Number of modules per mechanism	Flush mounting	Support frames	Plates	-	White	٤	Soft Alu	G	Neu Graphite	utral Ma	agnesium	Ch	ampagne	Da	ırk Bronze	
mechanism	boxes ¹	Traffies						1								
				Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	
1 module		5760 03		10	5752 00	10	5713 01	10	5752 02	10	5713 11	10	5713 21	10	5713 31	
2 modules	1 gang ²	5760 03 5760 01 ⁵		10	5752 10	10	5713 02	10	5752 12	10	5713 12	10	5713 22	10	5713 32	
3 modules - 1 gang	1 gang²	5760 01 ⁶		5	5751 60	5	5713 03	5	5751 62	5	5713 13	5	5713 23	5	5713 33	
2 x 3 modules - 2 gang	2 gang ³	N/A ³		1	5712 10	1	5712 11	1	5712 12	1	5712 13	1	5712 14	1	5712 15	
3 modules and shaver sockets	2 gang ⁴	5760 02		5	5750 70	5	5713 05	5	5750 72	5	5713 15	5	5713 25	5	5713 35	
4 modules	2 gang ⁴	5760 00		5	5750 80	5	5713 04	5	5750 82	5	5713 14	5	5713 24	5	5713 34	
6 modules	6890 27	Supplied with support frame		5	5753 70	5	5713 06	5	5753 72	5	5713 16	5	5713 26	5	5713 36	
8 modules	6890 38	Supplied with support frame		5	5767 00	5	5713 08	5	5767 02	5	5713 18	5	5713 28	5	5713 38	
2 x 6 modules	6890 28	Supplied with support frame		2	5753 90	2	5716 00	2	5753 92	2	5716 02	2	5716 04	2	5716 06	
3 x 6 modules	0818 56	Supplied with support frame		2	5754 00	2	5716 01	2	5754 02	2	5716 03	2	5716 05	2	5716 07	
Blanking cover plate	1 gang²	5760 03 or 5760 01		5	5751 30	5	5716 08	5	5751 32	5	5716 10	5	5716 12	5	5716 14	
Blanking cover plate	2 gang ⁴	5760 02	\square	5	5751 40	5	5716 09	5	5751 42	5	5716 11	5	5716 13	5	5716 15	

1 : For full details of flush mounting boxes, see Wiring Accessories guide p. 31

2 : Suitable for use with 1 gang back boxes. For Legrand options, see Wiring Accessories guide p. 31

3 : 2 x 3 modules - 2 gang surround plates are only for use with 2 gang connected socket outlets, see p. 29. Outlet supplied with support frame

4 : Suitable for use with 2 gang back boxes. For Legrand options, see Wiring Accessories guide p. 31 Use Cat. No. 5760 1 support frame for 2 module mechanisms to be mounted on 3 module support frame, see p. 33

6 : Support frame not needed for use with connected socket outlets Cat. Nos. 574256, 574257, 574258, 574259 see p. 29

For the full range of wiring accessories, see Wiring Accessories guide



									SUR	ROI	JND PLA	TES									
	Mir	ror					Brushe	d Me						Re	flective			1	Wood	Si	gnature
Mirr	or White	Mir	ror Black		ainless Steel	Gol	d Brass	Ch	Pink ampagne		Black	Stainless Steel Black Gold Grey Oak		Cube							
Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. Nos.	Pack	Cat. N
1	5752 04	1	5752 03	1	5752 06	1	5761 00	1	5713 51	1	5713 41	1	5713 61	1	5713 81	1	5713 71	1	5713 91	1	5714
1	5752 14	1	5752 13	1	5752 16	1	5761 20	1	5713 52	1	5713 42	1	5713 62	1	5713 82	1	5713 72	1	5713 92	1	5714
1	5751 64	1	5751 63	1	5751 66	1	5761 80	1	5713 53	1	5713 43	1	5713 63	1	5713 83	1	5713 73	1	5713 93	1	5714
1	5712 16	1	5712 17	1	5712 18	1	5712 19	1	5712 20	1	5712 21	1	5712 22	1	5712 23	1	5712 24	1	5712 25	1	5712
1	5750 74	1	5750 73	1	5750 76	1	5761 60	1	5713 55	1	5713 45	1	5713 65	1	5713 85	1	5713 75	1	5713 95	1	5714
1	5750 84	1	5750 83	1	5750 86	1	5761 40	1	5713 54	1	5713 44	1	5713 64	1	5713 84	1	5713 74	1	5713 94	1	5714
1	5753 74	1	5753 73	1	5753 76	1	5763 70	1	5713 56	1	5713 46	1	5713 66	1	5713 86	1	5713 76	1	5713 96	1	5714
1	5767 04	1	5767 03	1	5767 06	1	5767 10	1	5713 58	1	5713 48	1	5713 68	1	5713 88	1	5713 78	1	5713 98	1	5714
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	_	-	-	-	-	-	-	-	-	_	-	_	-	-	-	_	-	-	-	_	-
-	-	-	-	_	-	_	-	-	-	-	-	-	-	-	-	-	-	-	-	_	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-