



SYNTHETIC ROOF UNDERLAYMENT

Specifications (meets or exceeds applicable standards)		
	Standard	SIPA ROOFING UDL 100
Permeability	ASTM E96	.06 perms
Water Transmission	ASTM D4869	pass
Nail Seal ability	ASTM D1970	pass
Pliability	ASTM D266	pass
Tear Strength	ASTM D4533	MD 25 lbs /CD 25 lbs
Tensile Strength	ASTM D751	MD 109 lbs /CD 87 lbs
Elongation	ASTM D751	MD 20% / CD 20%
Wt Per Square	ASTM D5261	2.3 lbs
Nominal Thickness	ASTM D5261	100 GSM
Range of Temperature		- 40° F to 240° F
Fire Rating UL Class A	ASTM E108	pass

PHYSICAL INFORMATION			
Roll Size	48"x250'	Rolls Per Pallet	56 rolls
Material Per Roll	1000 sq.ft.	Wt Per Pallet	1,344 lbs
Squares Per Roll	10 squares	Limited Warranty	25 Years
Weight Per Roll	24 lbs		

COMPLIANCE: CODES
Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
Performance characteristics meet or exceed ASTM D226 – Type I, II
Tested in accordance with ICC-AC-207-UV Exposure -180 days
U.L. Classified as a Prepared Roofing Accessory
Meets the requirements of ICC-AC-188
FBC Approved - #17188
TDI Listed – CCRR #AC207