

BM990 TECHNICAL FEATURES

RECEIVER	
Signal Tracking	GPS: L1 C/A, L1C, L2P, L2C, L5
	GLONASS: L1, L2, L3
	BEIDOU: B1I, B2I, B3I, B1C, B2a, B2b
	GALILEO: E1, E5a, E5b, E6
	QZSS: L1, L2, L5
	IRNSS: L5
	SBAS
PPP	B2b PPP, HAS
Channels	1408
Position Rate	Up to 20Hz
Signal Reacquisition	< 1 s
RTK Signal Initialization ¹	Typically < 10 s
Hot Start	Typically < 15 s
Initialization Reliability	> 99.9 %
Internal Memory	8 GB
OS	Linux
Display	1.45" TFT LCD, 240 x 320 pixels
Tilt Sensor	IMU and E-bubble

POSITIONING ²	
STATIC SURVEYING	
High Precision Static Horizontal	2.5 mm + 0.1 ppm RMS
High Precision Static Vertical	3.5 mm + 0.4 ppm RMS
Static and Fast Static Horizontal	3 mm + 0.5 ppm RMS
Static and Fast Static Vertical	5 mm + 0.5 ppm RMS
CODE DIFFERENTIAL POSITIONING	
Horizontal	0.25 m + 1 ppm RMS
Vertical	0.50 m + 1 ppm RMS
SBAS POSITIONING ³	
Accuracy	0.60 m RMS
REAL TIME KINEMATIC (< 30 Km) – NETWORK RTK ⁴	
Fixed RTK Horizontal	5 mm + 0.5 ppm RMS
Fixed RTK Vertical	10 mm + 0.5 ppm RMS

INTEGRATED GNSS ANTENNA	
High accuracy multi-constellation antenna, zero phase center, with internal multipath suppression	

INTERNAL RADIO (optional) ⁵	
Type	Tx – Rx
Frequency Range	410 - 470 MHz 902.4 – 928 MHz
Channel Spacing	12.5 KHz / 25 KHz
Range	3-4 Km in urban environment Up to 10 Km with optimal conditions ¹

Illustrations, descriptions and technical specifications are not binding and may change

1. Varies with the operating environment and with electromagnetic pollution.
2. Accuracy and reliability are generally subject to satellite geometry (DOPs), multipath, atmospheric conditions and obstructions. In static mode they are subject even to occupation times: the longer is the Baseline, the longer must be the occupation time.
3. Depends on SBAS system performance.
4. Network RTK precision depends on the network performances and are referenced to the closest physical base station.
5. Optional, activated via activation code.

INTERNAL MODEM	
Band	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/ B13/B18/B19/B20/B25/B26/B28 LTE TDD: B38/B39/B40/B41 UMTS: B1/B2/B4/B5/B6/B8/B19 GSM: B2/B3/B5/B8 Nano SIM card

COMMUNICATION	
I/O Connectors	5-pin Lemo connects the external power supply and external radio Type-C, for receiver power supply and data transfer 1PPS port
Bluetooth	2.1 + EDR, V5.0
Wi-Fi	802.11 b/g/n
Web UI	To upgrade the software, manage the status and settings, data download, etc. via Smartphone, tablet or other electronic device with Wi-Fi capability
Reference Outputs	RTCM2.3, RTCM3.0, RTCM3.2 MSM, CMR, CMR+, DGPS
Navigation Outputs	NMEA 0183

POWER SUPPLY	
Battery	Internal rechargeable 7.2 V – 10200 mAh
Voltage	9 to 28 V DC external power input with over-voltage protection (5-pin Lemo)
Working Time	Up to 12 hours
Charge Time	Typically 4 hours

PHYSICAL SPECIFICATION	
Dimensions	Ø 151 mm x 94.5 mm
Weight	1.3 Kg
Operating Temperature	-40°C to 65°C (-40°F to 149°F)
Storage Temperature	-40°C to 80°C (-40°F to 176°F)
Waterproof/Dustproof	IP67
Shock Resistance	Designed to endure to a 2 m pole drop on hardwood floor with no damage
Vibration	Vibration resistant



BENCHMARK TOOL AND SUPPLY
2720 Discovery Drive, Raleigh, NC 27616
Phone: 984-664-9260
www.benchmarksupply.com



BM990 GNSS Receiver

High Performance
with IMU



MK.1.1 - REV.02 - \$990* - JULY 2024 - VER.03