



Since 1958
Trisco®

Medical Furniture Catalogue

By

TRICHUR SURGICALS

AN ISO 13485 CERTIFIED COMPANY

+91 8594 01 5554 trichur@trisco.in

www.trichursurgicals.com

index

CATALOGUE

About us	1
Critical Care Bed	2
Hospital Beds	3
Dialysis Bed	5
Delivery Bed	6
Emergency, Transport Stretchers	7
Recliner	10
Bedside Lockers, Over Bed Table	11



ABOUT US

Trisco, registered trademark owned by Trichur Surgicals, has come a long way in establishing itself as pioneers in the healthcare field. Over the years we carved a niche for ourselves through our professional excellence and dedicated services. We strive to obtain and retain our loyal customers by exceeding their expectations with innovative and quality products, competitive pricing and unparalleled services.

Keeping in line with the professionalism, scripted a glorious growth story with its exclusive range of medical equipment.

We provide sales, services and technical support from our offices in Thrissur, Kochi, Calicut, Trivandrum, Chennai and Bangalore.

We offer an exclusive range of wide variety of hospital & surgical equipment designed as per the specifications of our esteemed customers, manufactured using ultra-modern machines and sophisticated technology. We extend our clients superior quality products at affordable and competitive prices. Our engineering business is certified with International Quality Standard Operations (ISO 9001) and CE.



CRITICAL CARE BED TS 301 PRC

TECHNICAL INFORMATION

- Mattress platform is four section, three of them adjustable. Covered with integrated plastic Two-ply surface.
- Airflow capability under the mattress
- Backrest, knee raise, Hi-Low and Trend/Rev. Trend adjustments are electrically.
- Backrest section is radiolucent with a cassette holder.
- Four tuck away plastic sideboards
- Angle indicator for backrest adjustment
- Two ACP embedded in side boards that can be adjusted and locked by the nurse.
- Three-functional positioning embedded control panel accessible to the patient that can be locked by ACP.
- Detachable head/foot boards
- Washable and disinfectable
- CPR handle on both sides for flattening backrest rapidly
- Electrical CPR is available for flattening bed rapidly.
- Foot section is adjustable by means of telescopic bracket.
- Four castors with central/directional brakes
- Electrostatic powder coating
- Four rubber bumpers at corners
- ABS cover for base frame
- Backup battery
- **Main power supply** 220V - 50 Hz, 24 DC
- **Max. power input** 500 watt
- **Electrical current protection** Class2
- **Electrical shock position** Type B
- **Duty cycle** %10
- **Dust proof and water resistant** IP66
- IV stand holder at each corner
- Traction holder
- Chest bottle holder
- Hand grip holder



- Urine bag holder at both sides
- Orthopedic frame holder

DIMENSIONS and BASIC INFORMATION

- Overall 2300 x 1100 (mm)
- Mattress platform 2000 x 900 (mm)
- Backrest angle 0° - 80°
- Knee raise 0° - 35°
- Hi - Low 530 - 800 (mm)
- Trend / Rev. Trend angle +15° / -15°
- Castors 150 (mm) diameter
- Bed net weight 155 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES (Optional)

- IV stand
- Hand grip
- Orthopedic frame
- Traction Bar

STANDARDS

- ISO 9001
- ISO 13485
- CE

Trisco HOSPITAL BED

TS MT 1.2

TECHNICAL INFORMATION

- Mattress platform is four section, three of them adjustable. Covered with integrated plastic Two-ply surface.
- Airflow capability under the mattress
- Backrest and knee raise adjustments are manually with two freewheeling and foldable screw mechanisms
- Plastofold collapsible siderails with metal chassis inside
- Strong siderail hinges made of P.P
- Detachable head and foot boards with metal connection and suitable ergonomic style for easy handling
- Washable and disinfectable
- Four swivel metal castors with cross brake
- Electrostatic powder coating
- IV Stand holder positioned at head / foot board
- Urine bag holder at both sides

DIMENSIONS and BASIC INFORMATION

- Overall 2290 x 1020 x 590 (mm)
- Mattress platform 2000 x 900 (mm)
- Backrest angle 0°- 85°
- Knee raise angle 0°- 35°
- Castors 125 (mm) diameter
- Bed net weight 110 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco HOSPITAL BED TS A 311 PO

TECHNICAL INFORMATION

- Mattress platform is four section, three of them adjustable. Covered with integrated plastic Two-ply surface.
- Airflow capability under the mattress
- Backrest and knee raise adjustments are manually with two freewheeling and foldable screw mechanisms.
- Collapsible siderails
- Detachable head and foot boards
- Washable and disinfectable
- Four swivel metal castors with cross brake
- Electrostatic powder coating
- Four rubber bumpers at corners
- Rotating IV stand holder
- Urine bag holder at both sides

DIMENSIONS and BASIC INFORMATION

- Overall 2170 x 990 x 620 (mm)
- Mattress platform 2000 x 900 (mm)
- Backrest angle 0° - 70°
- Knee raise angle 0° - 25°
- Castors 125 (mm) diameter
- Bed net weight 80 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES

(Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco DIALYSIS BED TS H 314

TECHNICAL INFORMATION

- Mattress platform is three section, two of them adjustable.
- Detachable three section mattress made of 70mm thickness foam and artificial washable leather cover
- Mattress platform covered with MS sheet
- Backrest, knee raise, Rev. Trend and Hi-low adjustments are electrically.
- Four- functional positioning wired handset
- Arm rest height is fixed.
- Arm rest left - right movement is accessible through knob.
- CPR handle at both sides for flattening backrest rapidly
- Extendable Foot section (120 mm)
- ABS cover for protecting electrical set
- Washable and disinfectable
- Four castors, three with brake
- Electrostatic powder coating
- Backup battery
- **Main power supply** 220V - 50 Hz, 24 DC
- **Max. power input** 500 watt
- **Electrical current protection** Class2
- **Electrical shock position** Type B
- **Duty cycle** %10
- **Dust proof and water resistant** IP66
- Rotating IV stand holder
- Paper roller

DIMENSIONS and BASIC INFORMATION

- Hi - Low 580 - 860 (mm) without mattress
- Length (in chair position) 1840 (mm)
- Length (in bed position) 2070 (mm)
- Width (including arms) 950 (mm)
- Backrest angle 0° - 80°
- Foot rest angle 0° - 60°
- Rev. Trend angle -15°
- Castors 150 (mm) diameter
- Chair net weight 106 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco DELIVERY BED TS DT 310

TECHNICAL INFORMATION

- Backrest, Hi-Low and Trend/ Rev. Trend adjustments are electrically.
- Smooth Hi-Low and Trend/ Rev. Trend adjustments with the help of gas spring damper
- Two plastic tuck away sideboards
- Three- functional positioning wired handset
- Leg section can be slid under backrest for lithotomic positions.
- Telescopic section for transformation to delivery and labor bed
- Two sliding lithotomic positions made of SS grade 304 (11 positions), calf supports covered with artificial leather
- Pull out and removable stainless-steel bowl (10 liters) on roller rails
- Squat bar
- Foldable hand grip on both sides
- Detachable head/ footboards
- Washable and disinfectable
- Three section detachable mattress with washable artificial leather cover
- Four castors with central/directional brakes
- Four rubber bumpers
- ABS cover for covering required parts
- Detachable cover for pelvis and seat
- Electrostatic powder coating
- Backup battery
- **Main power supply** 220 V - 50 Hz, 24 DC
- **Max. power input** 500 Watt
- **Electrical current protection** Class2
- **Electrical shock position** Type B
- **Duty cycle** %10
- **Dust proof and water resistant** IP66
- Exclusive lithotomy, telescopic section mattress, foot board, squat bar holder designed at the back section
- IV stand holder at each corner
- Holder for squatting position
- Push grips over the head
- With doctor's foot support
- Sliding step for the patient



DIMENSIONS and BASIC INFORMATION

- Overall 2340 x 1000 (mm)
- Mattress platform 2000 x 865 (mm)
- Backrest angle 0° - 65°
- Hi - Low 695 - 885 (mm) without mattress
- Trend/Rev.Trend +15 /-15
- Castors 150 (mm) diameter
- Bed net weight: 192 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco EMERGENCY, TRANSPORT STRETCHERS TS 414 3.1

TECHNICAL INFORMATION

- Mattress platform is two section, head section is adjustable.
- Detachable, antistatic mattress with foam of 70(mm) thickness and artificial washable leather cover
- Hi-Low, Trend/Rev. Trend adjustments are possible by two hydraulic column jacks
- Bilateral pedal for Trend/Rev. Trend and Hi-Low adjustments
- Collapsible siderails
- Backrest adjustment by gas spring
- Foldable push handles
- Patient file holder
- Security belt for protecting patient during transport
- Base and columns are protected with cover.
- Washable and disinfectable
- Four castors with central/directional brakes and pedals available at head and foot end
- Electrostatic powder coating
- IV stand holder at each corner
- Four rubber bumpers at corners
- Protection guard for siderails at both sides
- Oxygen cylinder holder imbedded in the base cover of stretcher
- Urine bag holder at both sides

DIMENSIONS and BASIC INFORMATION

- Overall 2000 x 754 (mm)
- Mattress platform 1770 x 630 (mm)
- Hi-Low 550 - 870 (mm) (without mattress)
- Backrest angle 0° - 90°
- Trend / Rev. Trend angle +15°/-15°
- Castors 200 (mm) diameter
- Stretcher net weight 112 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE

TECHNICAL INFORMATION

- Mattress platform is three section, two of them adjustable with airflow capability under the mattress.
- Detachable, antistatic mattress with foam of 70(mm) thickness and artificial washable leather cover
- Mattress platform cover with PE sheet
- Backrest and knee raise adjustments are manually with two freewheeling foldable screw mechanisms.
- Height adjustment is available by hydraulic jack system.
- Collapsible siderails
- Washable and disinfectable
- Four castors with central/directional brakes and pedals available at head and foot end
- Electrostatic powder coating
- Four rubber bumpers at corners
- IV stand holder at each corner
- Fixed pushing handle at head end
- Security belt for protecting patient during transport
- Oxygen cylinder holder positioned on the base with fixing straps
- Basket for patient personal goods

DIMENSIONS and BASIC INFORMATION

- Overall 2024 x 850 (mm)
- Mattress platform 1810 x 630 (mm)
- Hi - Low 550 - 800 (mm) without mattress
- Backrest angle 0° - 65°
- Knee raise angle 0° - 15°
- Castors 200 (mm) diameter
- Stretcher net weight 115 Kg
- Safe working load capacity 170Kg
- Max. load capacity 250Kg

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE

Trisco EMERGENCY, TRANSPORT STRETCHERS TS S 4100





TECHNICAL INFORMATION

- Mattress platform is two section, head section is adjustable with airflow capability under the mattress.
- Detachable, antistatic mattress with foam of 70(mm) thickness and artificial washable leather cover
- Backrest adjustment is manually with a freewheeling and foldable screw mechanism.
- Collapsible siderails
- Washable and disinfectable
- Four swivel metal castors with cross brake
- Electrostatic powder coating
- Four rubber bumpers at corners
- IV stand holder at each corner
- Fixed pushing handle at head end
- Oxygen cylinder holder positioned on the base
- Patient file holder

DIMENSIONS and BASIC INFORMATION

- Overall 2050 x 750 x 800 (mm)
- Mattress platform 1950 x 630 (mm)
- Backrest angle 0° - 45°
- Castors 125 (mm) diameter
- Stretcher net weight 65 Kg
- Safe working load capacity 170 Kg
- Max. load capacity 250 Kg

Trisco

EMERGENCY, TRANSPORT STRETCHERS TS S 1200

ACCESSORIES (Optional)

- IV stand

STANDARDS

- ISO 9001
- ISO 13485
- CE





Trisco RECLINER TS ASA R 612

TECHNICAL INFORMATION

- Mattress platform is four sections.
- Mattress made of polyurethane foam covered with anti-scratch and fire-retardant artificial leather
- Adjustable in three positions: chair, TV and bed
- Strengthened plastic arm with artificial leather cover at both sides of the chair
- Four plastic castors with brake system
- Back roller bumper
- Backrest movement is supported by gas spring damper.

DIMENSIONS and BASIC INFORMATION

- Overall at chair position 1000 x 765 x 1115 (mm)
- Overall at TV position 1480 x 765 x 1070 (mm)
- Overall at bed position 1700 x 765 x 920 (mm)
- Seating area 540 x 520 (mm)
- Arm height from mattress platform 260 (mm)
- Mattress platform height 465 (mm)
- Backrest angle 10° - 87°
- Knee raise angle -80° - 0°
- Castors 75 (mm) diameter
- Chair net weight 50 Kg
- Max. load capacity 120 Kg



STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco

BED SIDE LOCKER TS M 52



TECHNICAL INFORMATION

- Plastic ABS surface
- Frame strengthened with metallic chassis
- Consists of a drawer, cabinet, sliding tray, bottle holder, towel holder, two hooks for hanging towel
- Four twin plastic castors
- Washable and disinfectable

DIMENSIONS and BASIC INFORMATION

- Overall 830 x 480 x 480 (mm)
- Castors 50 (mm) diameter
- Bedside Cabinet net weight 15 Kg
- Max. load capacity 100 Kg

STANDARDS

- ISO 9001
- ISO 13485
- CE

AVAILABLE COLORS



Trisco MATTRESS TS M2 9010



TECHNICAL INFORMATION

- Anti-bacterial, anti-sweating and smooth artificial leather surface with Maclon fabric
- CNC cutting sponge made of polyurethane with 30kg /m³ density
- Sturdy metal zipper
- Air flow capability inside the mattress
- Detachable, washable and disinfectable cover

DIMENSIONS and BASIC INFORMATION

- Overall 2000 x 900 x 100 (mm)
- Mattress net weight 6 kg

STANDARDS

- ISO 9001
- ISO 13485
- CE



Trisco OVER BED TABLE TS OBT 05

TECHNICAL INFORMATION

- Metal base covered by electrostatic powder coating
- Plastic ABS surface
- Four swiveling castors
- Pneumatically adjustable height fitted with gas spring mechanism which are in housed in aluminum extruded telescopic section for smooth sliding.
- Washable and disinfectable

DIMENSIONS and BASIC INFORMATION

- Overall size of Top 800 x 445 (mm)
- Min / Max height 745 - 995 (mm)
- Table net weight 14 Kg
- Max. load capacity 25 Kg

STANDARDS

- ISO 9001
- ISO 13485
- CE

Trisco

OVER BED TABLE TS OBT 02

TECHNICAL INFORMATION

- Metal base covered by electrostatic powder coating
- ABS Plastic surface
- Four swiveling Twin plastic castors
- Adjustable height with lever mechanism

DIMENSIONS and BASIC INFORMATION

- Overall 800 x 460 (mm)
- Min / Max height 820 - 1200 (mm)
- Table net weight 13 Kg
- Max. load capacity 25 kg

STANDARDS

- ISO 9001
- ISO 13485
- CE



THE ART OF MANUFACTURING



Awards & Recognitions

ISO9001:2008 certificate from BSI

Registered with National Small Industries Corporation Ltd (NSIC)

Nehru Peace Foundation Award 2008

Economic Times best Asian healthcare brands 2017

Member of Confederation of Indian Industry (CII)

Registered in Store Purchase Dpt. Govt. of Kerala

Member of ADITI (Association of Dental Industry & Trade of India)

Member of KEDDA (Kerala Dental Dealers Association)

OUR HAPPY CLIENTS



Quality Certificates



Memberships







TRICHUR SURGICALS

CORPORATE OFFICE

Parijath Building, Patturaikal, Thrissur, Kerala - 680 022.

+91 8594 01 5554 trichur@trisco.in www.trichursurgicals.com



TRICHUR | KOCHI | CALICUT | TRIVANDRUM | BANGALORE | CHENNAI