

OSAKA

PINTURA DECORATIVA

REFORZANTE

DATA SHEET

Update date: 03 - 01 - 2018 ED.02

DESCRIPTION

Transparent reinforcing resin for all kinds of paints, tempera, coatings, etc.

TECHNICAL DATA

	REFORZANTE
Composition:	Acrylic resin in water
^VOC content máx. allowed (2010):	Category A, Subcategory G: 30 g/l
^VOC content máx. product:	Category A, Subcategory H < 5.0g/l
pH:	8.4 - 8.8
Density:	1,01 – 1,04 g/cm3
*Coverage:	-
Viscosity:	100 - 200 mPa·s
Appearance:	Liquid
Color:	Transparent
Pack size:	1 L
Dilution:	Ready to use
Tools:	Roller and brush
Cleaning tools :	Water
**Conditions of applications:	Between 5°C and 35°C
*** Drying:	At least 8 hours
****Storage:	Between 5°C and 35°C

* The coverage may vary depending on the support and the applicator itself.

** Both ambient temperature and surface temperature.

*** According to weather conditions.

**** Avoid frost. Keep container tightly closed. The products are stable for at least one year from the date of manufacture, in perfect storage conditions, closed, with the seal intact and between 5 and 35°C.



OSAKA

PINTURA DECORATIVA

REFORZANTE

DATA SHEET

Update date: 03 - 01 - 2018 ED.02

^Subcategory according to RD 227/2006 and Directive 2004/42/CE

It should be noted that the performance may vary depending on the surface, application conditions and / or applicator. The purchaser / applicator is not exempt from the responsibility of carrying out its own examination of the products supplied, in order to verify its suitability for the intended procedures and purposes.

DIRECTIONS FOR USE

Add to product to be reinforced in desired proportion prior to application Increases hardness and washability. Approximate proportion: Add 1L of **Reforzante** to each 15L/15Kg of product

IMPORTANT

Keep out of the reach of children. In case of contact with eyes, rinse thoroughly with water. If discomfort persists consult a physician and teach the label. In case of accidental ingestion consult a physician immediately.

DISPOSAL CONSIDERATIONS

Do not empty liquid into drains or pipes. Solid waste may be disposed of as normal waste. Follow the "European Standards for Waste Water Based Paints".

The current Data Sheet cancels and replaces any previous Data Sheet.

