



P-MS

TECHNICAL DATA SHEET

DATE: 1-10-26

PETROCHEM – MUTUAL SOLVENT

PRODUCT DESCRIPTION

P-MS is a mutual solvent designed to improve removal of oil-based residues and enhance surface wettability in cementing and spacer systems. It supports improved fluid compatibility and effective cement bonding.

APPLICATIONS

- Oil-based residue removal
- Surface conditioning for cementing systems
- Spacer and pre-flush fluid enhancement

TECHNICAL DATA

- Improves oil and water solubility
- Enhances surface wettability
- Assists in removal of hydrocarbon residues
- Improves fluid compatibility within spacer systems

TYPICAL PROPERTIES

- Appearance: Colorless Liquid
- Specific Gravity: 0.90
- Temperature Range: 450°F (232°C)

RECOMMENDED TREATMENT

- Typical concentration: up to 10% by volume
- Can be used with surfactants and dispersants as required
- Final dosage must be confirmed through laboratory testing under actual system conditions

PACKAGING

- Packaged in 4 × 55-gallon (208 L) drums per pallet
- Bulk or custom packaging options available upon request

SAFETY

- Refer to the Safety Data Sheet (SDS) prior to handling or use

NOTICE

The information provided herein is offered in good faith; however, no warranties, express or implied, are made. Users are responsible for determining product suitability and performance under actual operating conditions.