# P-ASA3

## TECHNICAL DATA SHEET

DATE: JANUARY 1, 2026

**PETROCHEM – ANTI-SETTLING ADDITIVE 3 POWDER**

**PRODUCT DESCRIPTION**

P-ASA3 is a powdered anti settling additive designed to enhance suspension and rheological control in API cementing systems through increased low shear rate viscosity. It improves solids suspension and reduces sedimentation, supporting slurry stability and more uniform fluid properties in low to moderate temperature applications.

**APPLICATIONS**

- Primary and remedial cementing operations using API cements
- Cement slurries requiring enhanced solids suspension
- Systems with higher solids loading

**TECHNICAL DATA**

- Increases low shear rate viscosity to enhance suspension performance
- Improves solids carrying capacity and reduces solids settling under low flow conditions
- Maintains controlled plastic viscosity for efficient fluid placement
- Provides improved cement compatibility compared to conventional suspension additives

**TYPICAL PROPERTIES**

- Appearance: Off White / Tan Powder
- Specific Gravity: 2.07
- Temperature Range: < 300°F (149°C)

**RECOMMENDED TREATMENT**

- Typical concentration range: 0.2% – 1.0% BWOC
- Final dosage should be determined through laboratory testing under actual system conditions

**PACKAGING**

- Packaged in 40 × 50 lb (22.7 kg) sacks per pallet
- Bulk or custom packaging options available upon request

**SAFETY**

- Refer to the Safety Data Sheet (SDS) prior to handling or use

**NOTICE**

The information provided herein is offered in good faith; however, no warranties, express or implied, are made. Users are responsible for determining product suitability and performance under actual operating conditions.