



P-CWL2

TECHNICAL DATA SHEET

DATE: 1-10-26

PETROCHEM – CHEMICAL WASH LIQUID 2

PRODUCT DESCRIPTION

P-CWL2 is a liquid chemical wash designed for removal of water-based and oil-based drilling fluids in cementing and spacer systems. It enhances mud displacement and reduces slurry contamination, supporting effective cement placement in more demanding conditions.

APPLICATIONS

- Water-based and oil-based drilling fluid removal
- Chemical wash spacers for cementing systems
- Pre-flush applications ahead of cement slurries

TECHNICAL DATA

- Disperses and removes water-based and oil-based drilling fluids
- Reduces mud contamination and slurry instability
- Promotes turbulent flow at low pump rates
- Improves pipe and formation surface condition

TYPICAL PROPERTIES

- Appearance: Clear Yellow / Amber Liquid
- Specific Gravity: 1.01
- Temperature Range: 450°F (232°C)

RECOMMENDED TREATMENT

- Typical concentration: 4 – 5 gal/bbl of wash fluid
- Final dosage must be confirmed through laboratory testing under actual system conditions

PACKAGING

- Packaged in 4 × 55-gallon (208 L) drums per pallet
- Bulk or custom packaging options available upon request

SAFETY

- Refer to the Safety Data Sheet (SDS) prior to handling or use

NOTICE

The information provided herein is offered in good faith; however, no warranties, express or implied, are made. Users are responsible for determining product suitability and performance under actual operating conditions.