



P-NSL2

TECHNICAL DATA SHEET

DATE: 1-10-26

PETROCHEM – NONIONIC SURFACTANT LIQUID 2

PRODUCT DESCRIPTION

P-NSL2 is a nonionic surfactant designed to reduce surface and interfacial tension in spacer and chemical wash systems. It improves wettability and fluid compatibility, supporting effective mud removal and cement placement.

APPLICATIONS

- Surfactant for spacer and chemical wash systems
- Oil-based mud compatibility enhancement
- Surface wetting and fluid conditioning

TECHNICAL DATA

- Reduces surface and interfacial tension
- Improves wettability of formation and casing surfaces
- Enhances compatibility between fluid systems
- Supports effective mud removal and fluid displacement

TYPICAL PROPERTIES

- Appearance: Clear Yellow Liquid
- Specific Gravity: 1.06
- Temperature Range: 450°F (232°C)

RECOMMENDED TREATMENT

- Typical concentration: 1 – 2 gal/bbl in wash systems
- Adjust dosage based on system requirements
- Final dosage must be confirmed through laboratory testing under actual system conditions

PACKAGING

- Packaged in 4 × 55-gallon (208 L) drums per pallet
- Bulk or custom packaging options available upon request

SAFETY

- Refer to the Safety Data Sheet (SDS) prior to handling or use

NOTICE

The information provided herein is offered in good faith; however, no warranties, express or implied, are made. Users are responsible for determining product suitability and performance under actual operating conditions.