P-ASA3L

TECHNICAL DATA SHEET

DATE: JANUARY 1, 2026

PETROCHEM – ANTI-SETTLING ADDITIVE 3 LIQUID

PRODUCT DESCRIPTION

P-ASA3L is a liquid anti settling additive designed to enhance slurry stability and suspension performance in API cementing systems by improving solids suspension and reducing settling. It supports uniform slurry properties in low to moderate temperature applications and in systems with higher solids loading.

APPLICATIONS

- Primary and remedial cementing operations using API cements
- Cement slurries requiring enhanced solids suspension and settling control
- Systems with higher solids loading or low to moderate temperature conditions

TECHNICAL DATA

- Enhances solids suspension and reduces sedimentation under low flow conditions
- Improves solids carrying capacity and slurry uniformity
- Maintains controlled rheological properties for efficient fluid placement
- Provides improved cement compatibility compared to conventional suspension additives

TYPICAL PROPERTIES

- Appearance: Off White / Tan Liquid
- Specific Gravity: 1.10
- Temperature Range: < 300°F (149°C)

RECOMMENDED TREATMENT

- Typical concentration range: 0.1 – 0.5 gal/sk
- Final dosage should be determined through laboratory testing under actual system conditions

PACKAGING

- Packaged in 4 × 55-gallon (208 L) drums per pallet
- Bulk or custom packaging options available upon request

SAFETY

- Refer to the Safety Data Sheet (SDS) prior to handling or use

NOTICE

The information provided herein is offered in good faith; however, no warranties, express or implied, are made. Users are responsible for determining product suitability and performance under actual operating conditions.