



# P-ASA2

## TECHNICAL DATA SHEET

1/10/26

### P-ASA2 (PETROCHEM - ANTI-SETTLING ADDITIVE 2 POWDER)

#### TECHNICAL DATA

- **P-ASA2** is a powdered additive developed to optimize the rheological profile of drilling fluids by increasing viscosity at low shear rates.
- **P-ASA2** maintains plastic viscosity at a minimum value (while increasing low shear rate viscosity).
- **P-ASA2** improves suspension & solids carrying capacity, (especially under low flow rate condition).
- **P-ASA2** is more cement compatible than other biopolymers for use in the formulation of cement spacer fluids.

#### APPLICATIONS

- Effective for all water & brine-based fluid systems, including seawater.
- Suspends solids in fresh or brine water.

#### PROPERTIES

- Appearance: Off White / Tan (Powder)
- Specific Gravity: 1.50
- Temperature Range: Stable to 200°F

#### RECOMMENDED TREATMENT

- The normal concentration range of **P-ASA2** is 0.2% to 1.0% BWOC.
- Lab testing is recommended prior to use in the field.

#### PACKAGING

- **P-ASA2** is packaged in 40 x 50 lb. Sacks / Pallet.

#### SAFETY

- Read the SDS before use.