



TECHNICAL PARAMETERS

Printhead	EPSON I3200-A1		Nozzle Quantity	3200
Printhead Quantity	4		Print Width	1900mm
Ink Color	CMYK		Print Height	2-5mm
Resolution	360*1200 / 360*1800 / 720*1200 / 720*1800(DPI)		Media Transfer	Auto Media Feeding and Taking-up System, Roll to Roll
Speed *Tested on linear print without feather	2 Pass	150 m²/h	Drying Method	Extra Dryer Device
	3 Pass	110 m ² /h	Ink Supply Method	Siphon Positive Pressure Ink Supply
	4 Pass	90 m ² /h	Head Moisture Method	Auto Head Cleaning and Moisturize
	* speed is tested on full-size media without feather function		Print Media	Transfer Paper
Ink Type	Sublimation Ink		Transmission interface	Gigabit LAN
Computer System	Win7 64bit, Win10 64bit		File Forms	TIFF JPG EPS PDF
Operate Environment	Temp.: 20-25℃,Humidity: 35-65%		RIP Software	Maintop6.0/Photoprint 12/ONYX 18
Dimension	Printer Size: 3284*1050*1720mm Packing Size: 3458*1150*1780mm		Power Supply	210-230V 50\60HZ 16A Print Power: 1500W Dryer Power: Max. 7000W
Computer Configuration	Win7 64bit, Win10, Hard Disk: NTFS, C Disk Space: More than 100G, Hard DiskWD500G, GPU: ATI Discrete GPU, CPU: Above Intel i5/i7, Gigabit LAN.			
Standard Configuration	Ink level Alarm System		Weight	N.W.: 650KG G.W.: 780KG

PRODUCT FEATURES

Support 4 Epson head printing. Speed of 2 pass can reach up to 150sm/h. Introduce Gigabit data transmission port, which can meet the demand of high resolution huge file transmission and guarantees the stability.

Adopt updated integrated capping station module.

Dislocated carriage base plate is precision machined, which makes head position adjustment is more convenient.

Equipped with constant tention taking-up system with imported motor, which ensures that media taking-up tension is constant and stable from beginning to end, excellent taking-up effect can be achieved.

Name brand core parts with high quality, THK guide, NSK bearing, IGUS chain, LEADSHINE servo motor etc.,



