



QUADRA

WELL POINT PUMP SERIES

INDUSTRY EXCELLENCE, WHERE PERFORMANCE AND DURABILITY MEET

PUMP TO PERFECTION



12255 104 Avenue,
Grande Prairie, AB
T8V 8A7, Canada

57-3347 262 Street,
Aldergrove, BC
V4W 3V9, Canada

12005 Cleveland Gibbs Road,
Roanoke, TX
76262, USA



[WELL POINT PUMP SERIES]

DESCRIPTION

THE QUADRAWAVE SERIES OF WELLPOINT PUMPS WERE DESIGNED TO EXCEED INDUSTRY STANDARDS. THESE UNITS ARE CAPABLE OF 2200 GPM @ 120FT OF HEAD WITH AID FROM A NON-CLOG, SOLID HANDLING CENTRIFUGAL STYLE PUMP END, INDUSTRY LEADING AIR SEPARATION TECHNOLOGY, AND A HIGH OUTPUT, OIL-FREE, ZERO MAINTENANCE DIRECT DRIVE CLAW VACUUM PUMP.

APPLICATIONS



Industrial



Oil & Gas



Waste Water



Environmental



Construction



Mining

FEATURES

Stainless Steel Internal Components

Non-Clog, Solid Handling, Run Dry System

High Volume (120 CFM) Claw Vacuum Pump

Air Separation Technology

Silicone Carbide Mechanical Seal

SPECIFICATIONS

Discharge Size	4"-8" (100-200 mm) ANSI Flanges
Power Output	50hp Diesel or Electric
Max Flow	2200 GPM
Max Head	120ft
Speed	1800 RPM
Water Temp Limit	(80° C)
Solids Handling	2.50"
Standard Compact Fuel Tank	300 Liter
Dry Weight	3500 lbs

