



QUADRA

DIESEL PUMP SERIES

INDUSTRY EXCELLENCE, WHERE PERFORMANCE AND DURABILITY MEET

PUMP TO PERFECTION



[QPD-108HH17]

[QPD-64HH22]

[QPD-86HH22]

[QPD-66MH12]

[QPD-1210HH22]

Jeff Belanger
+1(604) 782-4774
Jeff@quadrapumps.com

57-3347 262 Street,
Aldergrove, BC
V4W 3V9, Canada

12255 104 Avenue,
Grande Prairie, AB
T8V 8A7, Canada

DESCRIPTION

THE LINE OF CENTRIFUGAL PUMPS WE CARRY ARE DEVELOPED TO EFFECTIVELY MEET THE PERFORMANCE REQUIREMENTS AND DURABILITY TO POWER THE NEEDS OF A WIDE RANGE OF INDUSTRY APPLICATIONS WORLDWIDE.

QUADRA QPD-64HH22 DIESEL POWERED PUMP SERIES HAS A STEEL EXTERIOR CONSTRUCTION, HEAVY DUTY HIGH TENSILE BEARING HOUSING WITH FULL STAINLESS STEEL INTERNAL WORKING COMPONENTS. THIS HIGH QUALITY DESIGN PROVIDES PREMIUM EFFICIENCY FOR HIGH HEAD/FLOW APPLICATIONS, FEATURING A STATE OF THE ART AUTOMATIC VAC ASSIST CHAMBER AND AN ENDURA SILICONE CARBIDE RUN DRY SEAL SYSTEM.

APPLICATIONS



Industrial



Oil & Gas



Waste Water



Environmental



Construction



Mining



[QPD-64HH22]

FEATURES

Complete Containment | Fuel Heating | PAS Systems | Telemetry | Engineered Lifting Points | Welded D Links

LED Lighting | Brake Equalizing | Levelling System | Safety Zone Controls | Glycol Heater | Viscous Fan Coupling

Components equipped for durable conditions | Optimizes efficiency and maximum life span of pump

PUMP PACKAGE DATA

275 HP Industrial Power Unit

6 Cylinder Turbo Charged | Liquid Cooled | 12 Volt | LCD Control Panel | 1 Year Warranty

Highway Rated Trailer

Mid Size Tandem Axle | 17.5" Trailer Tires | 400 L Fuel Cell | Lifting Bale | Choice of Fittings | 8K Stabilizers | Brakes + Lights

QUADRA PUMPS

LIQUID INTELLIGENCE



CORNELL PUMP END




SPECIFICATIONS

4622MX

Max. Flow	1680 GPM
Discharge Size	4"
Suction Size	6"
Solids Handling	0.98"
Max. Speed	1900 RPM
Shut Off Head	660'

Performances shown are for S.G. 1.0
60°F water, frame mounted configuration
with Cyclo seal. Other mounting styles or
S.G. may require curve adjustments.

Speed	Impeller Dia.	Style	Volute	Solids Dia.	N _s	Suction	Discharge	No. Vanes
VARIOUS	21.95"	ENCLOSED	SINGLE	.98"	552	6"	4"	4






PIONEER PUMP

SPECIFICATIONS

PP64C21

Max. Flow	1500 GPM
Discharge Size	4"
Suction Size	6"
Solids Handling	0.88"
Max. Speed	2000 RPM
Shut Off Head	675'



Model	PP64C21	
Size	6" x 4"	150 mm x 100 mm
Impeller Diameter	21.0"	533 mm
Solids Handling Size	0.88"	22 mm

DWG No.	13570HQ
Revision	000
Drawn By	ESW
Date	10 Mar 2014