

QUADRA PUMPS

powered by innovation

QUADRA
DIESEL PUMP SERIES

INDUSTRY EXCELLENCE, WHERE PERFORMANCE AND DURABILITY MEET

PUMP TO PERFECTION



[QPD-108HH17]

[QPD-64HH22]

[QPD-86HH22]

[QPD-66MH12]

Jeff Belanger
+1(604) 782-4774
Jeff@quadrapumps.com

57-3347 262 Street,
Aldergrove, BC
V4W 3V9, Canada

12255 104 Avenue,
Grande Prairie, AB
T8V 8A7, Canada

QUADRA PUMPS

powered by innovation



DESCRIPTION

THE LINE OF CENTRIFUGAL PUMPS WE CARRY ARE DEVELOPED TO EFFECTIVELY MEET THE PERFORMANCE REQUIREMENTS AND DURABILITY TO POWER THE NEEDS OF A WIDE RANGE OF INDUSTRY APPLICATIONS WORLDWIDE.

QUADRA QPD-86HH22 DIESEL POWERED PUMP SERIES HAS A STEEL EXTERIOR CONSTRUCTION, HEAVY DUTY HIGH TENSILE BEARING HOUSING WITH FULL STAINLESS STEEL INTERNAL WORKING COMPONENTS. THIS HIGH QUALITY DESIGN PROVIDES PREMIUM EFFICIENCY FOR HIGH HEAD/FLOW APPLICATIONS, FEATURING A STATE OF THE ART AUTOMATIC VAC ASSIST CHAMBER AND AN ENDURA SILICONE CARBIDE RUN DRY SEAL SYSTEM.



[QPD-86HH22]

APPLICATIONS



Industrial



Oil & Gas



Waste Water



Environmental



Construction



Mining

FEATURES

Complete Containment | Fuel Heating | PAS Systems | Telemetry | Engineered Lifting Points | Welded D Links

LED Lighting | Brake Equalizing | Levelling System | Safety Zone Controls | Glycol Heater | Viscous Fan Coupling

Components equipped for durable conditions | Optimizes efficiency and maximum life span of pump

PUMP PACKAGE DATA

600 HP Industrial Power Unit

6 Cylinder Turbo Charged | Liquid Cooled | 12 Volt | LCD Control Panel | 1 Year Warranty

Highway Rated Trailer

Full Tandem Axle | 17.5" Trailer Tires | 400 L Fuel Cell | Lifting Bale | Choice of Fittings | 8K Stabilizers | Brakes + Lights

QUADRA PUMPS

powered by innovation




CORNELL PUMP END

SPECIFICATIONS

6822MX

Max. Flow	4250 GPM
Discharge Size	6"
Suction Size	8"
Solids Handling	2.00"
Max. Speed	1900 RPM
Shut Off Head	640'



QUADRA PUMPS

powered by innovation





PIONEER PUMP END

SPECIFICATIONS

PP86C21

Max. Flow	4000 GPM
Discharge Size	6"
Suction Size	8"
Solids Handling	1.5"
Max. Speed	2000 RPM
Shut Off Head	650'



 PIONEER PUMP PERFORMANCE THROUGH INNOVATION™	Model	PP86C21		DWG No.	12860HQ
	Size	8" x 6"	200 mm x 150 mm	Revision	000
	Impeller Diameter	21.0"	533 mm	Drawn By	ESW
	Solids Handling Size	1.5"	38 mm	Date	10 Sep 2013