

QUADRA PUMPS

powered by innovation




QUADRAFLO

SUBMERSIBLE PUMP SERIES



[QPS2-120]

APPLICATIONS



Industrial Oil & Gas Waste Water Environmental Construction Mining

SPECIFICATIONS

Discharge Size	2" NPT
Power Output	1 hp
Max Flow	100 GPM
Max Head	60 ft
Speed	3465 RPM
Voltage	120v
Phase	Single
Amperage	13.0
Type	Dewatering (semi vortex)
Power Cable	32 ft
pH Range	5 - 8
Max. Liquid Temp	104 Degrees F
Weight	63 lbs

DESCRIPTION

QUADRAFLO DURABLE PERFORMANCE PUMPS ARE DESIGNED TO EFFECTIVELY POWER A WIDE RANGE OF APPLICATIONS. PROVIDING EFFICIENT AND RELIABLE SOLUTIONS FOR HIGH VOLUME INDUSTRY PUMP STANDARDS.

QUADRAFLO QPS2-120 2" SUBMERSIBLE PUMP MODEL HAS A STEEL EXTERIOR THAT IS ROBUST AND CAN WITHSTAND ANY ENVIRONMENT. A MECHANICAL DESIGN THAT USES A TRADITIONAL DOUBLE SEAL SYSTEM TO REDUCE CORROSION DURING ABRASIVE APPLICATIONS.

FEATURES

Stainless steel strainer, shaft, impeller, outlet and hardware for maximum corrosion resistance

Pressure enclosed chamber mechanically sealed

Optimizes efficiency and maximum life span of pump

Components equipped for durable conditions

PERFORMANCE CURVE

